

pyAgrum Documentation

Release 0.15.0

Pierre-Henri Wuillemin (Sphinx)

May 09, 2019

Contents

1	pyAgrum library	3
1.1	Functions from pyAgrum	3
1.1.1	Input/Output for bayesian networks	4
1.1.2	Input for influence diagram	4
1.2	Graphs manipulation	5
1.2.1	Edges and Arcs	5
1.2.1.1	Arc	5
1.2.1.2	Edge	6
1.2.2	Directed Graphs	6
1.2.2.1	Digraph	6
1.2.2.2	Directed Acyclic Graph	9
1.2.3	Undirected Graphs	11
1.2.3.1	UndiGraph	11
1.2.3.2	Clique Graph	13
1.2.4	Mixed Graph	17
1.3	Random Variables	21
1.3.1	Common API for Random Discrete Variables	21
1.3.2	Concrete classes for Random Discrete Variables	23
1.3.2.1	LabelizedVariable	23
1.3.2.2	DiscretizedVariable	26
1.3.2.3	RangeVariable	28
1.4	Potential and Instantiation	31
1.4.1	Instantiation	32
1.4.2	Potential	37
1.5	Bayesian Network	42
1.5.1	Model	43
1.5.2	Exact Inference	54
1.5.2.1	Lazy Propagation	54
1.5.2.2	Shafer Shenoy Inference	61
1.5.2.3	Variable Elimination	67
1.5.3	Approximate Inference	73
1.5.3.1	Loopy Belief Propagation	73
1.5.3.2	Sampling	79
1.5.3.2.1	Gibbs Sampling	79
1.5.3.2.2	Monte Carlo Sampling	85
1.5.3.2.3	Weighted Sampling	92
1.5.3.2.4	Importance Sampling	98
1.5.3.3	Loopy sampling	104
1.5.3.3.1	Loopy Gibbs Sampling	104
1.5.3.3.2	Loopy Monte Carlo Sampling	111


1.5.3.3.3	Loopy Weighted Sampling	117
1.5.3.3.4	Loopy Importance Sampling	123
1.5.4	Learning	129
1.6	Probabilistic Relational Models	136
1.7	Credal Networks	140
1.7.1	Model	140
1.7.2	Inference	145
1.8	Influence Diagram	150
1.8.1	Model	150
1.8.2	Inference	156
1.9	Other functions from aGrUM	157
1.9.1	Listeners	157
1.9.1.1	LoadListener	157
1.9.1.2	StructuralListener	158
1.9.1.3	ApproximationSchemeListener	158
1.9.1.4	DatabaseGenerationListener	158
1.9.2	Random functions	158
1.9.3	OMP functions	159
1.10	Exceptions from aGrUM	159
2	Python helpers : pyAgrum.lib	165
2.1	Module notebook	165
2.1.1	Helpers	166
2.1.2	Visualization of Potentials	166
2.1.3	Visualization of graphs	166
2.1.4	Visualization of graphical models	166
2.1.5	Visualization of approximation algorithm	166
2.2	Module bn2graph	166
2.2.1	Visualization of Potentials	167
2.2.2	Visualization of Bayesian Networks	167
2.2.3	Hi-level functions	168
2.3	Module dynamic bayesian network	169
2.4	other pyAgrum.lib modules	169
2.4.1	bn2roc	169
2.4.2	bn2csv	170
2.4.3	bn2scores	172
2.4.4	bn_vs_bn	172
2.4.5	pretty_print	173
3	Indices and tables	175
4	Documentation tools	177
4.1	Read me/To do	177
4.1.1	Read me	177
4.1.2	To do	177
4.1.2.1	Type issues	177
4.1.2.2	Exception issues	177
4.1.2.3	Methods to add	178
4.1.2.4	Methods to overload	178
4.1.2.5	Other issues	178
Python Module Index		179

pyAgrum is a Python wrapper for the C++ aGrUM (<http://agrume.org>) library. It provides a high-level interface to the C++ part of aGrUM allowing to create, manage and perform efficient computations with Bayesian Networks.

```


1 import pyAgrum as gum
2 import pyAgrum.lib.notebook as gnb
3
4 bn=gum.fastBN("a->b;c->b->d",3)
5 gnb.sideBySide(bn,
6     bn.cpt("b"),
7     gnb.getJunctionTree(bn),
8     captions=['a BN','a CPT : $P(b|a,c)$','a Junction Tree'])

```




a BN

	b			
a	c	0	1	2
0		0.6061	0.3184	0.0756
1	0	0.8658	0.0427	0.0914
2		0.3972	0.5652	0.0376
0		0.3992	0.1565	0.4443
1	1	0.3431	0.1549	0.5020
2		0.3894	0.1018	0.5088
0		0.3062	0.2622	0.4316
1	2	0.2654	0.3677	0.3669
2		0.0849	0.5190	0.3961

a CPT : $P(b|a,c)$ 

a Junction Tree



(<http://agrume.org>)

The module is generated using the **SWIG** (<https://www.swig.org>) interface generator. Custom-written code was added to make the interface more user friendly.

pyAgrum aims to allow to easily use (as well as to prototype new algorithms on) Bayesian network and other graphical models.

pyAgrum contains

- a comprehensive API documentation (<http://www-desir.lip6.fr/~phw/aGrUM/docs/last/pyAgrum/index.html>),
- examples as jupyter notebooks (<http://www-desir.lip6.fr/~phw/aGrUM/docs/last/notebooks/01-tutorial.ipynb.html>),
- and a website (<http://agrume.org>).

CHAPTER 1

pyAgrum library

1.1 Functions from pyAgrum

Useful functions in pyAgrum

`pyAgrum.about()`

about() for pyAgrum

`pyAgrum.fastBN(arcs, domain_size=2)`

rapid prototyping of BN.

Parameters

- **arcs** – dot-like simple list of arcs (“a->b->c;a->c->d” for instance). The first apparition of a node name can be enhanced with a “[domain_size]” extension. For instance “a[5]->b->c;a[2]->c->d” will create a BN with a variable “a” whos domain size is `a.nbrDim()==5` (the second “a[2]” is not taken into account since the variable has already been created).
- **domain_size** – the domain size of each created variable.

Returns

the created `pyAgrum.BayesNet`

`pyAgrum.getPosterior(bn, evs, target)`

Compute the posterior of a single target (variable) in a BN given evidence

`getPosterior` uses a VariableElimination inference. If more than one target is needed with the same set of evidence or if the same target is needed with more than one set of evidence, this function is not relevant since it creates a new inference engine every time it is called.

Parameters

- **bn** (`pyAgrum.BayesNet` (page 43)) –
- **evs** (*dictionary*) – events map {name/id:val, name/id : [val1, val2], ... }
- **target** – variable name or id

Returns

posterior Potential

1.1.1 Input/Output for bayesian networks

```
pyAgrum.availableBNExts()
```

Returns a string which lists all suffixes for supported BN file formats.

```
pyAgrum.loadBN(filename, listeners=None, verbose=False, **opts)
```

Parameters

- **filename** – the name of the input file
- **listeners** – list of functions to execute
- **verbose** – whether to print or not warning messages
- **system** – (for O3PRM) name of the system to flatten in a BN
- **classpath** – (for O3PRM) list of folders containing classes

Returns a BN from a file using one of the availableBNExts() suffixes.

Listeners could be added in order to monitor its loading.

Examples

```
>>> import pyAgrum as gum
>>>
>>> # creating listeners
>>> def foo_listener(progress):
>>>     if progress==200:
>>>         print(' BN loaded ')
>>>         return
>>>     elif progress==100:
>>>         car='%'
>>>     elif progress%10==0:
>>>         car='#'
>>>     else:
>>>         car='.'
>>>     print(car,end='',flush=True)
>>>
>>> def bar_listener(progress):
>>>     if progress==50:
>>>         print('50%')
>>>
>>> # loadBN with list of listeners
>>> gum.loadBN('../bn.bif',listeners=[foo_listener,bar_listener])
>>> # .....#.....#.....#.....#..50%
>>> # .....#.....#.....#.....#.....% / bn loaded
```

```
pyAgrum.saveBN(bn,filename)
```

save a BN into a file using the format corresponding to one of the availableWriteBNExts() suffixes.

1.1.2 Input for influence diagram

```
pyAgrum.loadID(filename)
```

read a `gum.InfluenceDiagram` from a bifxml file

Parameters **filename** – the name of the input file

Returns an `InfluenceDiagram`

1.2 Graphs manipulation

In aGrUM, graphs are undirected (using edges), directed (using arcs) or mixed (using both arcs and edges). Some other types of graphs are described below. Edges and arcs are represented by pairs of int (nodeId), but these pairs are considered as unordered for edges whereas they are ordered for arcs.

For all types of graphs, nodes are int. If a graph of objects is needed (like `pyAgrum.BayesNet` (page 43)), the objects are mapped to nodeIds.

1.2.1 Edges and Arcs

1.2.1.1 Arc

`class pyAgrum.Arc(*args)`

`pyAgrum.Arc` is the representation of an arc between two nodes represented by int : the head and the tail.

Available ructors: `Arc(tail, head) -> Arc`

`Arc(src) -> Arc`

Parameters

- **tail** (`int`) – the tail
- **head** (`int`) – the head
- **src** – the Arc to copy

`first (Arc self)`

Returns the nodeId of the first node of the arc (the tail)

Return type int

`head (Arc self)`

Returns the id of the head node

Return type int

`other (Arc self, int id)`

Parameters `id` (`int`) – the nodeId of the head or the tail

Returns the nodeId of the other node

Return type int

`second (Arc self)`

Returns the nodeId of the second node of the arc (the head)

Return type int

`tail (Arc self)`

Returns the id of the tail node

Return type int

`thisown`

The membership flag

1.2.1.2 Edge

class pyAgrum.Edge (*args)

pyAgrum.Edge is the representation of an arc between two nodes represented by int : the first and the second.

Available ructors : Edge (aN1, aN2) → Edge

Edge (src) → Edge

Parameters

- **aN1** (*int*) – the nodeId of the first node
- **aN2** (*int*) – the nodeId of the secondnode
- **src** ([pyAgrum.Edge](#) (page 6)) – the Edge to copy

first (*Edge self*)

Returns the nodeId of the first node of the arc (the tail)

Return type int

other (*Edge self, int id*)

Parameters **id** (*int*) – the nodeId of one of the nodes of the Edge

Returns the nodeId of the other node

Return type int

second (*Edge self*)

Returns the nodeId of the second node of the arc (the head)

Return type int

thisown

The membership flag

1.2.2 Directed Graphs

1.2.2.1 Digraph

class pyAgrum.DiGraph (*args)

DiGraph represents a Directed Graph.

Available ructors: DiGraph () → DiGraph

DiGraph (src) → DiGraph

Parameters **src** ([pyAgrum.DiGraph](#) (page 6)) – the digraph to copy

addArc (*DiGraph self, int tail, int head*)

addArc(DiGraph self, int n1, int n2)

Add an arc from tail to head.

Parameters

- **tail** (*int*) – the id of the tail node
- **head** (*int*) – the id of the head node

Raises `gum.InvalidNode` – If head or tail does not belong to the graph nodes.

addNode (*DiGraph self*)

Returns the new NodeId

Return type int

addNodeWithId (*DiGraph self, int id*)
Add a node by choosing a new NodeId.

Parameters **id** (*int*) – The id of the new node

Raises `gum.DuplicateElement` – If the given id is already used

addNodes (*DiGraph self, int n*)
Add n nodes.

Parameters **n** (*int*) – the number of nodes to add.

Returns the new ids

Return type Set of int

arcs (*DiGraph self*)
Returns the list of the arcs

Return type List

children (*DiGraph self, int id*)
Parameters **id** (*int*) – the id of the parent

Returns the set of all the children

Return type Set

clear (*DiGraph self*)
Remove all the nodes and arcs from the graph.

empty (*DiGraph self*)
Check if the graph is empty.

Returns True if the graph is empty

Return type bool

emptyArcs (*DiGraph self*)
Check if the graph doesn't contains arcs.

Returns True if the graph doesn't contains arcs

Return type bool

eraseArc (*DiGraph self, int n1, int n2*)
Erase the arc between n1 and n2.

Parameters

- **n1** (*int*) – the id of the tail node
- **n2** (*int*) – the id of the head node

eraseChildren (*DiGraph self, int n*)
Erase the arcs heading through the node's children.

Parameters **n** (*int*) – the id of the parent node

eraseNode (*DiGraph self, int id*)
Erase the node and all the related arcs.

Parameters **id** (*int*) – the id of the node

eraseParents (*DiGraph self, int n*)
Erase the arcs coming to the node.

Parameters **n** (*int*) – the id of the child node

existsArc (*DiGraph self, int n1, int n2*)

Check if an arc exists bewteen n1 and n2.

Parameters

- **n1** (*int*) – the id of the tail node
- **n2** (*int*) – the id of the head node

Returns True if the arc exists

Return type bool

existsNode (*DiGraph self, int id*)

Check if a node with a certain id exists in the graph.

Parameters **id** (*int*) – the checked id

Returns True if the node exists

Return type bool

ids()

Deprecated method in pyAgrum>0.12.0. See nodes instead.

nodes (*DiGraph self*)

Returns the set of ids

Return type set

parents (*DiGraph self, int id*)

Parameters **id** – The id of the child node

Returns the set of the parents ids.

Return type Set

size (*DiGraph self*)

Returns the number of nodes in the graph

Return type int

sizeArcs (*DiGraph self*)

Returns the number of arcs in the graph

Return type int

thisown

The membership flag

toDot (*DiGraph self*)

Returns a friendly display of the graph in DOT format

Return type str

topologicalOrder (*DiGraph self, bool clear=True*)

Returns the list of the nodes Ids in a topological order

Return type List

Raises `gum.InvalidDirectedCycle` – If this graph contains cycles

1.2.2.2 Directed Acyclic Graph

class pyAgrum.DAG(*args)

DAG represents a Directed Acyclic Graph.

Available ructors: DAG() -> DAG

DAG(src) -> DAG

Parameters **src** – the DAG to copy

addArc (DAG self, int tail, int head)

addArc(DAG self, int n1, int n2)

Add an arc from tail to head.

Parameters

- **tail** (int) – the id of the tail node
- **head** (int) – the id of the head node

Raises

- gum.InvalidDirectedCircle – If any (directed) cycle is created by this arc
- gum.InvalidNode – If head or tail does not belong to the graph nodes

addNode (DiGraph self)

Returns the new NodeId

Return type int

addNodeWithId (DiGraph self, int id)

Add a node by choosing a new NodeId.

Parameters **id** (int) – The id of the new node

Raises gum.DuplicateElement – If the given id is already used

addNodes (DAG self, int n)

arcs (DiGraph self)

Returns the list of the arcs

Return type List

children (DiGraph self, int id)

Parameters **id** (int) – the id of the parent

Returns the set of all the children

Return type Set

clear (DiGraph self)

Remove all the nodes and arcs from the graph.

empty (DiGraph self)

Check if the graph is empty.

Returns True if the graph is empty

Return type bool

emptyArcs (DiGraph self)

Check if the graph doesn't contains arcs.

Returns True if the graph doesn't contains arcs

Return type bool

eraseArc (*DiGraph self, int n1, int n2*)

Erase the arc between n1 and n2.

Parameters

- **n1** (*int*) – the id of the tail node
- **n2** (*int*) – the id of the head node

eraseChildren (*DiGraph self, int n*)

Erase the arcs heading through the node's children.

Parameters **n** (*int*) – the id of the parent node

eraseNode (*DiGraph self, int id*)

Erase the node and all the related arcs.

Parameters **id** (*int*) – the id of the node

eraseParents (*DiGraph self, int n*)

Erase the arcs coming to the node.

Parameters **n** (*int*) – the id of the child node

existsArc (*DiGraph self, int n1, int n2*)

Check if an arc exists bewteen n1 and n2.

Parameters

- **n1** (*int*) – the id of the tail node
- **n2** (*int*) – the id of the head node

Returns True if the arc exists

Return type bool

existsNode (*DiGraph self, int id*)

Check if a node with a certain id exists in the graph.

Parameters **id** (*int*) – the checked id

Returns True if the node exists

Return type bool

ids()

Deprecated method in pyAgrum>0.12.0. See nodes instead.

moralGraph (*DAG self*)

nodes (*DiGraph self*)

Returns the set of ids

Return type set

parents (*DiGraph self, int id*)

Parameters **id** – The id of the child node

Returns the set of the parents ids.

Return type Set

size (*DiGraph self*)

Returns the number of nodes in the graph

Return type int

sizeArcs (*DiGraph self*)

Returns the number of arcs in the graph

Return type int

thisown
The membership flag

toDot (*DiGraph self*)
Returns a friendly display of the graph in DOT format

Return type str

topologicalOrder (*DiGraph self*, *bool clear=True*)
Returns the list of the nodes Ids in a topological order

Return type List
Raises `gum.InvalidDirectedCycle` – If this graph contains cycles

1.2.3 Undirected Graphs

1.2.3.1 UndiGraph

class `pyAgrum.UndiGraph(*args)`
UndiGraph represents an Undirected Graph.

Available ructors: `UndiGraph()` → UndiGraph
`UndiGraph(src)` → UndiGraph

Parameters `src` – the UndiGraph to copy

addEdge (*UndiGraph self*, *int n1*, *int n2*)
Insert a new edge into the graph.

Parameters

- `n1 (int)` – the id of one node of the new inserted edge
- `n2 (int)` – the id of the other node of the new inserted edge

Raises `gum.InvalidNode` – If n1 or n2 does not belong to the graph nodes.

addNode (*UndiGraph self*)

Returns the new NodeId

Return type int

addNodeWithId (*UndiGraph self*, *int id*)
Add a node by choosing a new NodeId.

Parameters `id (int)` – The id of the new node

Raises `gum.DuplicateElement` – If the given id is already used

addNodes (*UndiGraph self*, *int n*)
Add n nodes.

Parameters `n (int)` – the number of nodes to add.

Returns the new ids

Return type Set of int

clear (*UndiGraph self*)
Remove all the nodes and edges from the graph.

edges (*UndiGraph self*)

Returns the list of the edges

Return type List

empty (*UndiGraph self*)

Check if the graph is empty.

Returns True if the graph is empty

Return type bool

emptyEdges (*UndiGraph self*)

Check if the graph doesn't contains edges.

Returns True if the graph doesn't contains edges

Return type bool

eraseEdge (*UndiGraph self, int n1, int n2*)

Erase the edge between n1 and n2.

Parameters

- **n1** (*int*) – the id of the tail node
- **n2** (*int*) – the id of the head node

eraseNeighbours (*UndiGraph self, int n*)

Erase all the edges adjacent to a given node.

Parameters **n** (*int*) – the id of the node

eraseNode (*UndiGraph self, int id*)

Erase the node and all the adjacent edges.

Parameters **id** (*int*) – the id of the node

existsEdge (*UndiGraph self, int n1, int n2*)

Check if an edge exists bewteen n1 and n2.

Parameters

- **n1** (*int*) – the id of one extremity of the edge
- **n2** (*int*) – the id of the other extremity if tge edge

Returns True if the arc exists

Return type bool

existsNode (*UndiGraph self, int id*)

Check if a node with a certain id exists in the graph.

Parameters **id** (*int*) – the checked id

Returns True if the node exists

Return type bool

hasUndirectedCycle (*UndiGraph self*)

Checks whether the graph contains cycles.

Returns True if the graph contains a cycle

Return type bool

ids()

Deprecated method in pyAgrum>0.12.0. See nodes instead.

neighbours (*UndiGraph self, int id*)

Parameters **id** (*int*) – the id of the checked node

Returns The set of edges adjacent to the given node

Return type Set

nodes (*UndiGraph self*)

Returns the set of ids

Return type set

partialUndiGraph (*UndiGraph self, Set nodesSet*)

Parameters **nodesSet** (*Set*) – The set of nodes composing the partial graph

Returns The partial graph formed by the nodes given in parameter

Return type [pyAgrum.UndiGraph](#) (page 11)

size (*UndiGraph self*)

Returns the number of nodes in the graph

Return type int

sizeEdges (*UndiGraph self*)

Returns the number of edges in the graph

Return type int

thisown

The membership flag

toDot (*UndiGraph self*)

Returns a friendly display of the graph in DOT format

Return type str

1.2.3.2 Clique Graph

class [pyAgrum.CliqueGraph](#) (*args)

CliqueGraph represents a Clique Graph.

Available constructors: CliqueGraph() -> CliqueGraph

CliqueGraph(src) -> CliqueGraph

Parameters **src** ([pyAgrum.CliqueGraph](#) (page 13)) – the CliqueGraph to copy

addEdge (*CliqueGraph self, int first, int second*)

Insert a new edge into the graph.

Parameters

- **n1** (*int*) – the id of one node of the new inserted edge
- **n2** (*int*) – the id of the other node of the new inserted edge

Raises gum.InvalidNode – If n1 or n2 does not belong to the graph nodes.

addNode (*CliqueGraph self, Set clique*)

addNode(CliqueGraph self) -> int addNode(CliqueGraph self, int id, Set clique)
addNode(CliqueGraph self, int id)

Returns the new NodeId

Return type int

addNodeWithId (*UndiGraph self, int id*)

Add a node by choosing a new NodeId.

Parameters **id** (*int*) – The id of the new node

Raises gum.DuplicateElement – If the given id is already used

addNodes (*UndiGraph self, int n*)

Add n nodes.

Parameters **n** (*int*) – the number of nodes to add.

Returns the new ids

Return type Set of int

addToClique (*CliqueGraph self, int clique_id, int node_id*)

Change the set of nodes included into a given clique and returns the new set

Parameters

- **clique_id** (*int*) – the id of the clique
- **node_id** (*int*) – the id of the node

Raises

- `gum.NotFound` – If clique_id does not exist
- `gum.DuplicateElement` – If clique_id set already contains the node

clear (*CliqueGraph self*)

Remove all the nodes and edges from the graph.

clearEdges (*CliqueGraph self*)

Remove all edges and their separators

clique (*CliqueGraph self, int clique*)

Parameters **idClique** (*int*) – the id of the clique

Returns The set of nodes included in the clique

Return type Set

Raises `gum.NotFound` – If the clique does not belong to the clique graph

container (*CliqueGraph self, int idNode*)

Parameters **idNode** (*int*) – the id of the node

Returns the id of a clique containing the node

Return type int

Raises `gum.NotFound` – If no clique contains idNode

containerPath (*CliqueGraph self, int node1, int node2*)

Parameters

- **node1** (*int*) – the id of one node
- **node2** (*int*) – the id of the other node

Returns a path from a clique containing node1 to a clique containing node2

Return type List

Raises `gum.NotFound` – If such path cannot be found

edges (*UndiGraph self*)

Returns the list of the edges

Return type List

empty (*UndiGraph self*)

Check if the graph is empty.

Returns True if the graph is empty

Return type bool

emptyEdges (*UndiGraph self*)

Check if the graph doesn't contains edges.

Returns True if the graph doesn't contains edges

Return type bool

eraseEdge (*CliqueGraph self, Edge edge*)

Erase the edge between n1 and n2.

Parameters

- **n1** (*int*) – the id of the tail node
- **n2** (*int*) – the id of the head node

eraseFromClique (*CliqueGraph self, int clique_id, int node_id*)

Remove a node from a clique

Parameters

- **clique_id** (*int*) – the id of the clique
- **node_id** (*int*) – the id of the node

Raises `gum.NotFound` – If clique_id does not exist

eraseNeighbours (*UndiGraph self, int n*)

Erase all the edges adjacent to a given node.

Parameters **n** (*int*) – the id of the node

eraseNode (*CliqueGraph self, int node*)

Erase the node and all the adjacent edges.

Parameters **id** (*int*) – the id of the node

existsEdge (*UndiGraph self, int n1, int n2*)

Check if an edge exists bewteen n1 and n2.

Parameters

- **n1** (*int*) – the id of one extremity of the edge
- **n2** (*int*) – the id of the other extremity if tge edge

Returns True if the arc exists

Return type bool

existsNode (*UndiGraph self, int id*)

Check if a node with a certain id exists in the graph.

Parameters **id** (*int*) – the checked id

Returns True if the node exists

Return type bool

hasRunningIntersection (*CliqueGraph self*)

Returns True if the running intersection property holds

Return type bool

hasUndirectedCycle (*UndiGraph self*)

Checks whether the graph contains cycles.

Returns True if the graph contains a cycle

Return type bool

ids()

Deprecated method in pyAgrum>0.12.0. See nodes instead.

isJoinTree (*CliqueGraph self*)

Returns True if the graph is a join tree

Return type bool

neighbours (*UndiGraph self, int id*)

Parameters **id** (*int*) – the id of the checked node

Returns The set of edges adjacent to the given node

Return type Set

nodes (*UndiGraph self*)

Returns the set of ids

Return type set

partialUndiGraph (*UndiGraph self, Set nodesSet*)

Parameters **nodesSet** (*Set*) – The set of nodes composing the partial graph

Returns The partial graph formed by the nodes given in parameter

Return type [pyAgrum.UndiGraph](#) (page 11)

separator (*CliqueGraph self, int cliq1, int cliq2*)

Parameters

- **edge** ([pyAgrum.Edge](#) (page 6)) – the edge to be checked
- **clique1** (*int*) – one extremity of the edge
- **clique2** (*int*) – the other extremity of the edge

Returns the separator included in a given edge

Return type Set

Raises `gum.NotFound` – If the edge does not belong to the clique graph

setClique (*CliqueGraph self, int idClique, Set new_clique*)

changes the set of nodes included into a given clique

Parameters

- **idClique** (*int*) – the id of the clique
- **new_clique** (*Set*) – the new set of nodes to be included in the clique

Raises `gum.NotFound` – If idClique is not a clique of the graph

size (*UndiGraph self*)

Returns the number of nodes in the graph

Return type int

sizeEdges (*UndiGraph self*)

Returns the number of edges in the graph

Return type int

thisown

The membership flag

toDot (*CliqueGraph self*)

Returns a friendly display of the graph in DOT format

Return type str

toDotWithNames (*bn*)

Parameters

- **bn** ([pyAgrum.BayesNet](#) (page 43)) –
- **Bayesian network** (*a*) –

Returns a friendly display of the graph in DOT format where ids have been changed according to their correspondance in the BN

Return type str

1.2.4 Mixed Graph

class [pyAgrum.MixedGraph](#)(*args)

MixedGraph represents a Clique Graph.

Available ructors: MixedGraph() -> MixedGraph

MixedGraph(src) -> MixedGraph

Parameters **src** ([pyAgrum.MixedGraph](#) (page 17)) – the MixedGraph to copy

addArc (*DiGraph self, int tail, int head*)

addArc(*DiGraph self, int n1, int n2*)

Add an arc from tail to head.

Parameters

- **tail** (*int*) – the id of the tail node
- **head** (*int*) – the id of the head node

Raises `gum.InvalidNode` – If head or tail does not belong to the graph nodes.

addEdge (*UndiGraph self, int n1, int n2*)

Insert a new edge into the graph.

Parameters

- **n1** (*int*) – the id of one node of the new inserted edge
- **n2** (*int*) – the id of the other node of the new inserted edge

Raises `gum.InvalidNode` – If n1 or n2 does not belong to the graph nodes.

addNode (*UndiGraph self*)

Returns the new NodeId

Return type int

addNodeWithId (*UndiGraph self, int id*)

Add a node by choosing a new NodeId.

Parameters **id** (*int*) – The id of the new node

Raises `gum.DuplicateElement` – If the given id is already used

addNodes (*UndiGraph self, int n*)

Add n nodes.

Parameters **n** (*int*) – the number of nodes to add.

Returns the new ids

Return type Set of int

arcs (*DiGraph self*)

Returns the list of the arcs

Return type List

children (*DiGraph self, int id*)

Parameters **id** (*int*) – the id of the parent

Returns the set of all the children

Return type Set

clear (*MixedGraph self*)

Remove all the nodes and edges from the graph.

edges (*UndiGraph self*)

Returns the list of the edges

Return type List

empty (*UndiGraph self*)

Check if the graph is empty.

Returns True if the graph is empty

Return type bool

emptyArcs (*DiGraph self*)

Check if the graph doesn't contains arcs.

Returns True if the graph doesn't contains arcs

Return type bool

emptyEdges (*UndiGraph self*)

Check if the graph doesn't contains edges.

Returns True if the graph doesn't contains edges

Return type bool

eraseArc (*DiGraph self, int n1, int n2*)

Erase the arc between n1 and n2.

Parameters

- **n1** (*int*) – the id of the tail node
- **n2** (*int*) – the id of the head node

eraseChildren (*DiGraph self, int n*)

Erase the arcs heading through the node's children.

Parameters **n** (*int*) – the id of the parent node

eraseEdge (*UndiGraph self, int n1, int n2*)

Erase the edge between n1 and n2.

Parameters

- **n1** (*int*) – the id of the tail node
- **n2** (*int*) – the id of the head node

eraseNeighbours (*UndiGraph self, int n*)

Erase all the edges adjacent to a given node.

Parameters **n** (*int*) – the id of the node

eraseNode (*MixedGraph self, int id*)

Erase the node and all the adjacent edges.

Parameters **id** (*int*) – the id of the node

eraseParents (*DiGraph self, int n*)

Erase the arcs coming to the node.

Parameters **n** (*int*) – the id of the child node

existsArc (*DiGraph self, int n1, int n2*)

Check if an arc exists bewteen n1 and n2.

Parameters

- **n1** (*int*) – the id of the tail node
- **n2** (*int*) – the id of the head node

Returns True if the arc exists

Return type bool

existsEdge (*UndiGraph self, int n1, int n2*)

Check if an edge exists bewteen n1 and n2.

Parameters

- **n1** (*int*) – the id of one extremity of the edge
- **n2** (*int*) – the id of the other extremity if tge edge

Returns True if the arc exists

Return type bool

existsNode (*UndiGraph self, int id*)

Check if a node with a certain id exists in the graph.

Parameters **id** (*int*) – the checked id

Returns True if the node exists

Return type bool

hasUndirectedCycle (*UndiGraph self*)

Checks whether the graph contains cycles.

Returns True if the graph contains a cycle

Return type bool

ids()

Deprecated method in pyAgrum>0.12.0. See nodes instead.

mixedOrientedPath (*MixedGraph self, int node1, int node2*)

Parameters

- **node1** (*int*) – the id form which the path begins
- **node2** (*int*) – the id to witch the path ends

Returns a path from node1 to node2, using edges and/or arcs (following the direction of the arcs)

Return type List

Raises `gum.NotFound` – If no path can be found between the two nodes

mixedUnorientedPath (*MixedGraph self, int node1, int node2*)

Parameters

- **node1** (*int*) – the id from which the path begins
- **node2** (*int*) – the id to which the path ends

Returns a path from node1 to node2, using edges and/or arcs (not necessarily following the direction of the arcs)

Return type List

Raises gum.NotFound – If no path can be found between the two nodes

neighbours (*UndiGraph self, int id*)

Parameters **id** (*int*) – the id of the checked node

Returns The set of edges adjacent to the given node

Return type Set

nodes (*UndiGraph self*)

Returns the set of ids

Return type set

parents (*DiGraph self, int id*)

Parameters **id** – The id of the child node

Returns the set of the parents ids.

Return type Set

partialUndiGraph (*UndiGraph self, Set nodesSet*)

Parameters **nodesSet** (*Set*) – The set of nodes composing the partial graph

Returns The partial graph formed by the nodes given in parameter

Return type [pyAgrum.UndiGraph](#) (page 11)

size (*UndiGraph self*)

Returns the number of nodes in the graph

Return type int

sizeArcs (*DiGraph self*)

Returns the number of arcs in the graph

Return type int

sizeEdges (*UndiGraph self*)

Returns the number of edges in the graph

Return type int

thisown

The membership flag

toDot (*MixedGraph self*)

Returns a friendly display of the graph in DOT format

Return type str

topologicalOrder (*DiGraph self, bool clear=True*)

Returns the list of the nodes Ids in a topological order

Return type List

Raises gum.InvalidDirectedCycle – If this graph contains cycles

1.3 Random Variables

aGrUM/pyAgrum is currently dedicated for discrete probability distributions.

There are 3 types of discrete random variables in aGrUM/pyAgrum: LabelizedVariable, DiscretizedVariable and RangeVariable. The 3 types are mainly provided in order to ease modelization. Derived from DiscreteVariable, they share a common API. They essentially differ by the means to create, name and access to their modalities.

1.3.1 Common API for Random Discrete Variables

class `pyAgrum.DiscreteVariable(*args, **kwargs)`

DiscreteVariable is the base class for discrete random variable.

Available ructors:

```
DiscreteVariable(aName, aDesc='') -> DiscreteVariable
DiscreteVariable(aDRV) -> DiscreteVariable
```

Parameters

- **aName** (*str*) – The name of the variable
- **aDesc** (*str*) – The (optional) description of the variable
- **aDRV** (`pyAgrum.DiscreteVariable` (page 21)) – Another *DiscreteVariable* that will be copied

description (*Variable self*)

Returns the description of the variable

Return type str

domain (*DiscreteVariable self*)

Returns the domain of the variable

Return type str

domainSize (*DiscreteVariable self*)

Returns the number of modalities in the variable domain

Return type int

empty (*DiscreteVariable self*)

Returns True if the domain size < 2

Return type bool

index (*DiscreteVariable self, str label*)

Parameters **label** (*str*) – a label

Returns the indice of the label

Return type int

label (*DiscreteVariable self, int i*)

Parameters **i** (*int*) – the index of the label we wish to return

Returns the indice-th label

Return type str

Raises `gum.OutOfBounds` – If the variable does not contain the label

labels (*DiscreteVariable self*)

Returns a tuple containing the labels

Return type tuple

name (*Variable self*)

Returns the name of the variable

Return type str

numerical (*DiscreteVariable self, int indice*)

Parameters **indice** (*int*) – an index

Returns the numerical representation of the indice-th value

Return type float

setDescription (*Variable self, str theValue*)

set the description of the variable.

Parameters **theValue** (*str*) – the new description of the variable

setName (*Variable self, str theValue*)

sets the name of the variable.

Parameters **theValue** (*str*) – the new description of the variable

thisown

The membership flag

toDiscretizedVar (*DiscreteVariable self*)

Returns the discretized variable

Return type [pyAgrum.DiscretizedVariable](#) (page 26)

Raises `gum.RuntimeError` – If the variable is not a DiscretizedVariable

toLabelizedVar (*DiscreteVariable self*)

Returns the labeled variable

Return type [pyAgrum.LabelizedVariable](#) (page 23)

Raises `gum.RuntimeError` – If the variable is not a LabelizedVariable

toRangeVar (*DiscreteVariable self*)

Returns the range variable

Return type [pyAgrum.RangeVariable](#) (page 28)

Raises `gum.RuntimeError` – If the variable is not a RangeVariable

toStringWithDescription (*DiscreteVariable self*)

Returns a description of the variable

Return type str

varType (*DiscreteVariable self*)

returns the type of variable

Returns the type of the variable, 0: DiscretizedVariable, 1: LabelizedVariable, 2: RangeVariable

Return type int

1.3.2 Concrete classes for Random Discrete Variables

1.3.2.1 LabelizedVariable

`class pyAgrum.LabelizedVariable (*args)`

LabelizedVariable is a discrete random variable with a customizable sequence of labels.

Available ructors:

```
LabelizedVariable(aName, aDesc='', nbrLabel=2) ->
LabelizedVariable

LabelizedVariable(aName, aDesc='') -> LabelizedVariable

LabelizedVariable(aLDRV) -> LabelizedVariable
```

Parameters

- **aName** (*str*) – The name of the variable
- **aDesc** (*str*) – The (optional) description of the variable
- **nbrLabel** (*int*) – The number of labels to create (2 by default)
- **aLDRV** (`pyAgrum.LabelizedVariable` (page 23)) – Another *LabelizedVariable* that will be copied

Examples

```
>>> import pyAgrum as gum
>>>
>>> # creating a variable with 3 labels : '0', '1' and '2'
>>> va=gum.LabelizedVariable('a','a labeled variable',3)
>>> print(va)
>>> ## a<0,1,2>
>>>
>>> va.addLabel('foo')
>>> print(va)
>>> ## a<0,1,2,foo>
>>>
>>> va.chgLabel(1,'bar')
>>> print(va)
>>> a<0,bar,2,foo>
>>>
>>> vb=gum.LabelizedVariable('b','b',0).addLabel('A').addLabel('B').addLabel('C
->')
>>> print(vb)
>>> ## b<A,B,C>
>>>
>>> vb.labels()
>>> ## ('A', 'B', 'C')
>>>
>>> vb.isLabel('E')
>>> ## False
>>>
>>> vb.label(2)
>>> ## 'B'
```

`addLabel (*args)`

Add a label with a new index (we assume that we will NEVER remove a label).

Parameters `aLabel` (*str*) – the label to be added to the labeled variable

Returns the labeled variable

Return type `pyAgrum.LabelizedVariable` (page 23)

Raises `gum.DuplicateElement` – If the variable already contains the label

changeLabel (`LabelizedVariable self, int pos, str aLabel`)

Change the label at the specified index

Parameters

- **pos** (`int`) – the index of the label to be changed

- **aLabel** (`str`) – the label to be added to the labeled variable

Raises

- `gum.DuplicatedElement` – If the variable already contains the new label

- `gum.OutOfBounds` – If the index is greater than the size of the variable

description (`Variable self`)

Returns the description of the variable

Return type str

domain (`LabelizedVariable self`)

Returns the domain of the variable as a string

Return type str

domainSize (`LabelizedVariable self`)

Returns the number of modalities in the variable domain

Return type int

empty (`DiscreteVariable self`)

Returns True if the domain size < 2

Return type bool

eraseLabels (`LabelizedVariable self`)

Erase all the labels from the variable.

index (`LabelizedVariable self, str label`)

Parameters `label` (`str`) – a label

Returns the indice of the label

Return type int

isLabel (`LabelizedVariable self, str aLabel`)

Indicates whether the variable already has the label passed in argument

Parameters `aLabel` (`str`) – the label to be tested

Returns True if the label already exists

Return type bool

label (`LabelizedVariable self, int i`)

Parameters `i` (`int`) – the index of the label we wish to return

Returns the indice-th label

Return type str

Raises `gum.OutOfBounds` – If the variable does not contain the label

labels (`DiscreteVariable self`)

Returns a tuple containing the labels

Return type tuple

name (*Variable self*)

Returns the name of the variable

Return type str

numerical (*LabelizedVariable self, int indice*)

Parameters **indice** (*int*) – an index

Returns the numerical representation of the indice-th value

Return type float

posLabel (*LabelizedVariable self, str label*)

setDescription (*Variable self, str theValue*)

set the description of the variable.

Parameters **theValue** (*str*) – the new description of the variable

setName (*Variable self, str theValue*)

sets the name of the variable.

Parameters **theValue** (*str*) – the new description of the variable

thisown

The membership flag

toDiscretizedVar (*DiscreteVariable self*)

Returns the discretized variable

Return type [pyAgrum.DiscretizedVariable](#) (page 26)

Raises `gum.RuntimeError` – If the variable is not a DiscretizedVariable

toLabelizedVar (*DiscreteVariable self*)

Returns the labeled variable

Return type [pyAgrum.LabelizedVariable](#) (page 23)

Raises `gum.RuntimeError` – If the variable is not a LabelizedVariable

toRangeVar (*DiscreteVariable self*)

Returns the range variable

Return type [pyAgrum.RangeVariable](#) (page 28)

Raises `gum.RuntimeError` – If the variable is not a RangeVariable

toStringWithDescription (*DiscreteVariable self*)

Returns a description of the variable

Return type str

varType (*LabelizedVariable self*)

returns the type of variable

Returns the type of the variable, 0: DiscretizedVariable, 1: LabelizedVariable, 2: RangeVariable

Return type int

1.3.2.2 DiscretizedVariable

```
class pyAgrum.DiscretizedVariable(*args)
DiscretizedVariable is a discrete random variable with a set of ticks defining intervals.
```

Available ructors:

```
DiscretizedVariable(aName, aDesc='') -> DiscretizedVariable
DiscretizedVariable(aDDRV) -> DiscretizedVariable
```

Parameters

- **aName** (*str*) – The name of the variable
- **aDesc** (*str*) – The (optional) description of the variable
- **aDDRV** ([pyAgrum.DiscretizedVariable](#) (page 26)) – Another *DiscretizedVariable* that will be copied

Examples

```
>>> import pyAgrum as gum
>>>
>>> vX=gum.DiscretizedVariable('X','X has been discretized')
>>> vX.addTick(1).addTick(2).addTick(3).addTick(3.1415) #doctest: +ELLIPSIS
>>> ## <pyAgrum.pyAgrum.DiscretizedVariable;...>
>>> print(vX)
>>> ## X<[1;2[, [2;3[, [3;3.1415]>
>>>
>>> vX.isTick(4)
>>> ## False
>>>
>>> vX.labels()
>>> ## '[1;2[, [2;3[, [3;3.1415]'
>>>
>>> # where is the real value 2.5 ?
>>> vX.index('2.5')
>>> ## 1
```

addTick (*args)

Parameters **aTick** (*double*) – the Tick to be added

Returns the discretized variable

Return type [pyAgrum.DiscretizedVariable](#) (page 26)

Raises `gum.DefaultInLabel` – If the tick is already defined

description (*Variable self*)

Returns the description of the variable

Return type str

domain (*DiscretizedVariable self*)

Returns the domain of the variable as a string

Return type str

domainSize (*DiscretizedVariable self*)

Returns the number of modalities in the variable domain

Return type int

empty (*DiscreteVariable self*)

Returns True if the domain size < 2

Return type bool

eraseTicks (*DiscretizedVariable self*)

erase all the Ticks

index (*DiscretizedVariable self, str label*)

Parameters **label** (*str*) – a label

Returns the indice of the label

Return type int

isTick (*DiscretizedVariable self, double aTick*)

Parameters **aTick** (*double*) – the Tick to be tested

Returns True if the Tick already exists

Return type bool

label (*DiscretizedVariable self, int i*)

Parameters **i** (*int*) – the index of the label we wish to return

Returns the indice-th label

Return type str

Raises `gum.OutOfBounds` – If the variable does not contain the label

labels (*DiscreteVariable self*)

Returns a tuple containing the labels

Return type tuple

name (*Variable self*)

Returns the name of the variable

Return type str

numerical (*DiscretizedVariable self, int indice*)

Parameters **indice** (*int*) – an index

Returns the numerical representation of the indice-th value

Return type float

setDescription (*Variable self, str theValue*)

set the description of the variable.

Parameters **theValue** (*str*) – the new description of the variable

setName (*Variable self, str theValue*)

sets the name of the variable.

Parameters **theValue** (*str*) – the new description of the variable

thisown

The membership flag

tick (*DiscretizedVariable self, int i*)

Indicate the index of the Tick

Parameters **i** (*int*) – the index of the Tick

Returns **aTick** – the index-th Tick

Return type double

Raises `gum.NotFound` – If the index is greater than the number of Ticks

ticks (*DiscretizedVariable self*)

Returns a tuple containing all the Ticks

Return type tuple

toDiscretizedVar (*DiscreteVariable self*)

Returns the discretized variable

Return type `pyAgrum.DiscretizedVariable` (page 26)

Raises `gum.RuntimeError` – If the variable is not a DiscretizedVariable

toLabelizedVar (*DiscreteVariable self*)

Returns the labeled variable

Return type `pyAgrum.LabelizedVariable` (page 23)

Raises `gum.RuntimeError` – If the variable is not a LabelizedVariable

toRangeVar (*DiscreteVariable self*)

Returns the range variable

Return type `pyAgrum.RangeVariable` (page 28)

Raises `gum.RuntimeError` – If the variable is not a RangeVariable

toStringWithDescription (*DiscreteVariable self*)

Returns a description of the variable

Return type str

varType (*DiscretizedVariable self*)

returns the type of variable

Returns the type of the variable, 0: DiscretizedVariable, 1: LabelizedVariable, 2: RangeVariable

Return type int

1.3.2.3 RangeVariable

class `pyAgrum.RangeVariable(*args)`

RangeVariable represents a variable with a range of integers as domain.

Available ructors:

```
RangeVariable(aName, aDesc='',minVal, maxVal) ->
RangeVariable

RangeVariable(aName, aDesc='',minVal) -> RangeVariable

RangeVariable(aName, aDesc='') -> RangeVariable

RangeVariable(arV) -> RangeVariable
```

Parameters

- **aName** (`str`) – The name of the variable
- **aDesc** (`str`) – The (optional) description of the variable
- **minVal** (`int`) – The minimal integer of the interval
- **maxVal** (`int`) – The maximal integer of the interval

- **aDV** (`pyAgrum.RangeVariable` (page 28)) – Another *RangeVariable* that will be copied

Examples

```
>>> import pyAgrum as gum
>>>
>>> vI=gum.gum.RangeVariable('I','I in [4,10]',4,10)
>>> print(vI)
>>> ## I[4-10]
>>>
>>> vX.maxVal()
>>> ## 10
>>>
>>> vX.belongs(1)
>>> ## False
>>>
>>> # where is the value 5 ?
>>> vX.index('5')
>>> ## 1
>>>
>>> vi.labels()
>>> ## ('4', '5', '6', '7', '8', '9', '10')
```

belongs (*RangeVariable self, long val*)

Parameters **val** (*long*) – the value to be tested

Returns True if the value in parameters belongs to the variable's interval.

Return type bool

description (*Variable self*)

Returns the description of the variable

Return type str

domain (*RangeVariable self*)

Returns the domain of the variable

Return type str

domainSize (*RangeVariable self*)

Returns the number of modalities in the variable domain

Return type int

empty (*DiscreteVariable self*)

Returns True if the domain size < 2

Return type bool

index (*RangeVariable self, str arg2*)

Parameters **arg2** (*str*) – a label

Returns the indice of the label

Return type int

label (*RangeVariable self, int indice*)

Parameters **indice** (*int*) – the index of the label we wish to return

Returns the indice-th label

Return type str

Raises gum.OutOfBounds – If the variable does not contain the label

labels (*DiscreteVariable self*)

Returns a tuple containing the labels

Return type tuple

maxVal (*RangeVariable self*)

Returns the upper bound of the variable.

Return type long

minVal (*RangeVariable self*)

Returns the lower bound of the variable

Return type long

name (*Variable self*)

Returns the name of the variable

Return type str

numerical (*RangeVariable self, int indice*)

Parameters **indice** (*int*) – an index

Returns the numerical representation of the indice-th value

Return type float

setDescription (*Variable self, str theValue*)

set the description of the variable.

Parameters **theValue** (*str*) – the new description of the variable

setMaxVal (*RangeVariable self, long maxVal*)

Set a new value of the upper bound

Parameters **maxVal** (*long*) – The new value of the upper bound

Warning: An error should be raised if the value is lower than the lower bound.

setMinVal (*RangeVariable self, long minValue*)

Set a new value of the lower bound

Parameters **minVal** (*long*) – The new value of the lower bound

Warning: An error should be raised if the value is higher than the upper bound.

setName (*Variable self, str theValue*)

sets the name of the variable.

Parameters **theValue** (*str*) – the new description of the variable

thisown

The membership flag

toDiscretizedVar (*DiscreteVariable self*)

Returns the discretized variable

Return type [pyAgrum.DiscretizedVariable](#) (page 26)

Raises `gum.RuntimeError` – If the variable is not a DiscretizedVariable

toLabelizedVar (*DiscreteVariable self*)

Returns the labeled variable

Return type `pyAgrum.LabelizedVariable` (page 23)

Raises `gum.RuntimeError` – If the variable is not a LabelizedVariable

toRangeVar (*DiscreteVariable self*)

Returns the range variable

Return type `pyAgrum.RangeVariable` (page 28)

Raises `gum.RuntimeError` – If the variable is not a RangeVariable

toStringWithDescription (*DiscreteVariable self*)

Returns a description of the variable

Return type str

varType (*RangeVariable self*)

returns the type of variable

Returns the type of the variable, 0: DiscretizedVariable, 1: LabelizedVariable, 2: RangeVariable

Return type int

1.4 Potential and Instantiation

`pyAgrum.Potential` (page 37) is a multi-dimensional array with a `pyAgrum.DiscreteVariable` (page 21) associated to each dimension. It is used to represent probabilities and utilities tables in aGrUMs' multidimensional (graphical) models with some conventions.

- The data are stored by iterating over each variable in the sequence.

```
>>> a=gum.RangeVariable("A","variable A",1,3)
>>> b=gum.RangeVariable("B","variable B",1,2)
>>> p=gum.Potential().add(a).add(b).fillWith([1,2,3,4,5,6]);
>>> print(p)
<A:1|B:1> :: 1 /<A:2|B:1> :: 2 /<A:3|B:1> :: 3 /<A:1|B:2> :: 4 /<A:2|B:2> :: 5 /
    <A:3|B:2> :: 6
```

- If a `pyAgrum.Potential` (page 37) with the sequence of `pyAgrum.DiscreteVariable` (page 21) X,Y,Z represents a conditional probability Table (CPT), it will be P(X|Y,Z).

```
>>> print(p.normalizeAsCPT())
<A:1|B:1> :: 0.166667 /<A:2|B:1> :: 0.333333 /<A:3|B:1> :: 0.5 /<A:1|B:2> :: 0.
    <A:2|B:2> :: 0.333333 /<A:3|B:2> :: 0.4
```

- For addressing and looping in a `pyAgrum.Potential` (page 37) structure, pyAgrum provides Instantiation class which represents a multi-dimensionnal index.

```
>>> I=gum.Instantiation(p)
>>> print(I)
<A:1|B:1>
>>> I.inc();print(I)
<A:2|B:1>
>>> I.inc();print(I)
<A:3|B:1>
>>> I.inc();print(I)
```

(continues on next page)

(continued from previous page)

```
<A:1|B:2>
>>> I.setFirst();print ("{} -> {}".format(I,p.get(I)))
<A:1|B:1> -> 0.1666666666666666
>>> I["B"]="2";print ("{} -> {}".format(I,p.get(I)))
<A:1|B:2> -> 0.2666666666666666
```

- *pyAgrum.Potential* (page 37) include tensor operators (see for instance this [notebook](#) (<http://www-desir.lip6.fr/~phw/aGrUM/docs/last/notebooks/05-potentials.ipynb.html>)).

```
>>> c=gum.RangeVariable("C","variable C",1,5)
>>> q=gum.Potential().add(a).add(c).fillWith(1)
>>> print(p+q)
<A:1|C:1|B:1> :: 2 /<A:2|C:1|B:1> :: 3 /<A:3|C:1|B:1> :: 4 /<A:1|C:2|B:1> :: 2 /
-><A:2|C:2|B:1> :: 3 /<A:3|C:2|B:1> :: 4 /<A:1|C:3|B:1> :: 2 /<A:2|C:3|B:1> :: 3 /
-><A:3|C:3|B:1> :: 4 /<A:1|C:4|B:1> :: 2 /<A:2|C:4|B:1> :: 3 /<A:3|C:4|B:1> :: 4 /
-><A:1|C:5|B:1> :: 2 /<A:2|C:5|B:1> :: 3 /<A:3|C:5|B:1> :: 4 /<A:1|C:1|B:2> :: 5 /
-><A:2|C:1|B:2> :: 6 /<A:3|C:1|B:2> :: 7 /<A:1|C:2|B:2> :: 5 /<A:2|C:2|B:2> :: 6 /
-><A:3|C:2|B:2> :: 7 /<A:1|C:3|B:2> :: 5 /<A:2|C:3|B:2> :: 6 /<A:3|C:3|B:2> :: 7 /
-><A:1|C:4|B:2> :: 5 /<A:2|C:4|B:2> :: 6 /<A:3|C:4|B:2> :: 7 /<A:1|C:5|B:2> :: 5 /
-><A:2|C:5|B:2> :: 6 /<A:3|C:5|B:2> :: 7
>>> print((p*q).margSumOut(["B","C"])) # marginalize p*q over B and C(using sum)
<A:1> :: 25 /<A:2> :: 35 /<A:3> :: 45
```

1.4.1 Instantiation

class `pyAgrum.Instantiation(*args)`

Class for assigning/browsing values to tuples of discrete variables.

Instantiation is designed to assign values to tuples of variables and to efficiently loop over values of subsets of variables.

Available ructors:

```
Instantiation() -> Instantiation
Instantiation(ai) -> Instantiation
```

Parameters `ai` ([pyAgrum.Instantiation](#) (page 32)) – The Instantiation we copy

Returns

- *pyAgrum.Instantiation* – An empty tuple or a copy of the one in parameters
- *Instantiation is subscriptable therefore values can be easily accessed/modified.*

Examples

```
>>> ## Access the value of A in an instantiation ai
>>> valueOfA = ai['A']
>>> ## Modify the value
>>> ai['A'] = newValueOfA
```

add (*Instantiation self, DiscreteVariable v*)

Adds a new variable in the Instantiation.

Parameters `v` ([pyAgrum.DiscreteVariable](#) (page 21)) – The new variable added to the Instantiation

Raises `DuplicateElement` (page 159) – If the variable is already in this Instantiation

chgVal (*Instantiation self, DiscreteVariable v, int newval*)

chgVal(Instantiation self, DiscreteVariable v, int newval) -> Instantiation chgVal(Instantiation self, int varPos, int newval) -> Instantiation chgVal(Instantiation self, str var, int newval) -> Instantiation chgVal(Instantiation self, str var, str newval) -> Instantiation

Assign newval to v (or to the variable at position varPos) in the Instantiation.

Parameters

- **v** (`pyAgrum.DiscreteVariable` (page 21) or string) – The variable whose value is assigned (or its name)
- **varPos** (`int`) – The index of the variable whose value is assigned in the tuple of variables of the Instantiation
- **newval** (`int or string`) – The index of the value assigned (or its name)

Returns The modified instantiation**Return type** `pyAgrum.Instantiation` (page 32)**Raises**

- `NotFound` (page 162) – If variable v does not belong to the instantiation.
- `OutOfBounds` – If newval is not a possible value for the variable.

clear (*Instantiation self*)

Erase all variables from an Instantiation.

contains (*Instantiation self, DiscreteVariable v*)

contains(Instantiation self, DiscreteVariable v) -> bool

Indicates whether a given variable belongs to the Instantiation.

Parameters **v** (`pyAgrum.DiscreteVariable` (page 21)) – The variable for which the test is made.

Returns True if the variable is in the Instantiation.

Return type bool**dec** (*Instantiation self*)

Operator –.

decIn (*Instantiation self, Instantiation i*)

Operator – for the variables in i.

Parameters **i** (`pyAgrum.Instantiation` (page 32)) – The set of variables to decrement in this Instantiation

decNotVar (*Instantiation self, DiscreteVariable v*)

Operator – for vars which are not v.

Parameters **v** (`pyAgrum.DiscreteVariable` (page 21)) – The variable not to decrement in this Instantiation.

decOut (*Instantiation self, Instantiation i*)

Operator – for the variables not in i.

Parameters **i** (`pyAgrum.Instantiation` (page 32)) – The set of variables to not decrement in this Instantiation.

decVar (*Instantiation self, DiscreteVariable v*)

Operator – for variable v only.

Parameters **v** (`pyAgrum.DiscreteVariable` (page 21)) – The variable to decrement in this Instantiation.

Raises `NotFound` (page 162) – If variable v does not belong to the Instantiation.

domainSize (*Instantiation self*)

Returns The product of the variable's domain size in the Instantiation.

Return type int

empty (*Instantiation self*)

Returns True if the instantiation is empty.

Return type bool

end (*Instantiation self*)

Returns True if the Instantiation reached the end.

Return type bool

erase (*Instantiation self, DiscreteVariable v*)

Parameters **v** ([pyAgrum.DiscreteVariable](#) (page 21)) – The variable to be removed from this Instantiation.

Raises [NotFound](#) (page 162) – If v does not belong to this Instantiation.

fromdict (*Instantiation self, PyObject * dict*)

Change the values in an instantiation from a dict (variable_name:value) where value can be a position (int) or a label (string).

If a variable_name does not occur in the instantiation, nothing is done.

Warning: OutOfBounds raised if a value cannot be found.

hamming (*Instantiation self*)

Returns the hamming distance of this instantiation.

Return type int

inOverflow (*Instantiation self*)

Returns True if the current value of the tuple is correct

Return type bool

inc (*Instantiation self*)

Operator ++.

incIn (*Instantiation self, Instantiation i*)

Operator ++ for the variables in i.

Parameters **i** ([pyAgrum.Instantiation](#) (page 32)) – The set of variables to increment in this Instantiation.

incNotVar (*Instantiation self, DiscreteVariable v*)

Operator ++ for vars which are not v.

Parameters **v** ([pyAgrum.DiscreteVariable](#) (page 21)) – The variable not to increment in this Instantiation.

incOut (*Instantiation self, Instantiation i*)

Operator ++ for the variables not in i.

Parameters **i** ([Instantiation](#) (page 32)) – The set of variable to not increment in this Instantiation.

incVar (*Instantiation self, DiscreteVariable v*)

Operator ++ for variable v only.

Parameters **v** ([pyAgrum.DiscreteVariable](#) (page 21)) – The variable to increment in this Instantiation.

Raises `NotFound` (page 162) – If variable v does not belong to the Instantiation.

nbrDim (*Instantiation self*)

Returns The number of variables in the Instantiation.

Return type int

pos (*Instantiation self, DiscreteVariable v*)

Returns the position of the variable v.

Return type int

Parameters `v` (`pyAgrum.DiscreteVariable` (page 21)) – the variable for which its position is return.

Raises `NotFound` (page 162) – If v does not belong to the instantiation.

rend (*Instantiation self*)

Returns True if the Instantiation reached the rend.

Return type bool

reorder (*Instantiation self, pyAgrum.Sequence< pyAgrum.DiscreteVariable * > v*)
reorder(*Instantiation self, Instantiation i*)

Reorder vars of this instantiation giving the order in v (or i).

Parameters

- `i` (`pyAgrum.Instantiation` (page 32)) – The sequence of variables with which to reorder this Instantiation.
- `v` (`list`) – The new order of variables for this Instantiation.

setFirst (*Instantiation self*)

Assign the first values to the tuple of the Instantiation.

setFirstIn (*Instantiation self, Instantiation i*)

Assign the first values in the Instantiation for the variables in i.

Parameters `i` (`pyAgrum.Instantiation` (page 32)) – The variables to which their first value is assigned in this Instantiation.

setFirstNotVar (*Instantiation self, DiscreteVariable v*)

Assign the first values to variables different of v.

Parameters `v` (`pyAgrum.DiscreteVariable` (page 21)) – The variable that will not be set to its first value in this Instantiation.

setFirstOut (*Instantiation self, Instantiation i*)

Assign the first values in the Instantiation for the variables not in i.

Parameters `i` (`pyAgrum.Instantiation` (page 32)) – The variable that will not be set to their first value in this Instantiation.

setFirstVar (*Instantiation self, DiscreteVariable v*)

Assign the first value in the Instantiation for var v.

Parameters `v` (`pyAgrum.DiscreteVariable` (page 21)) – The variable that will be set to its first value in this Instantiation.

setLast (*Instantiation self*)

Assign the last values in the Instantiation.

setLastIn (*Instantiation self, Instantiation i*)

Assign the last values in the Instantiation for the variables in i.

Parameters `i` (`pyAgrum.Instantiation` (page 32)) – The variables to which their last value is assigned in this Instantiation.

setLastNotVar (*Instantiation self, DiscreteVariable v*)

Assign the last values to variables different of v.

Parameters **v** ([pyAgrum.DiscreteVariable](#) (page 21)) – The variable that will not be set to its last value in this Instantiation.

setLastOut (*Instantiation self, Instantiation i*)

Assign the last values in the Instantiation for the variables not in i.

Parameters **i** ([pyAgrum.Instantiation](#) (page 32)) – The variables that will not be set to their last value in this Instantiation.

setLastVar (*Instantiation self, DiscreteVariable v*)

Assign the last value in the Instantiation for var v.

Parameters **v** ([pyAgrum.DiscreteVariable](#) (page 21)) – The variable that will be set to its last value in this Instantiation.

setVals (*Instantiation self, Instantiation i*)

Assign the values from i in the Instantiation.

Parameters **i** ([pyAgrum.Instantiation](#) (page 32)) – An Instantiation in which the new values are searched

Returns a reference to the instantiation

Return type [pyAgrum.Instantiation](#) (page 32)

thisown

The membership flag

toDict (*Instantiation self, bool withLabels=False*)

Create a dict (variable_name:value) from an instantiation

Parameters **withLabels** (`boolean`) – The value will be a label (string) if True. It will be a position (int) if False.

Returns The dictionary

Return type Dict

unsetEnd (*Instantiation self*)

Alias for unsetOverflow().

unsetOverflow (*Instantiation self*)

Removes the flag overflow.

val (*Instantiation self, int i*)

val(Instantiation self, DiscreteVariable var) -> int

Parameters

- **i** (`int`) – The index of the variable.
- **var** ([pyAgrum.DiscreteVariable](#) (page 21)) – The variable the value of which we wish to know

Returns the current value of the variable.

Return type int

Raises [NotFound](#) (page 162) – If the element cannot be found.

variable (*Instantiation self, int i*)

variable(Instantiation self, str name) -> DiscreteVariable

Parameters **i** (`int`) – The index of the variable

Returns the variable at position i in the tuple.

Return type [pyAgrum.DiscreteVariable](#) (page 21)

Raises `NotFound` (page 162) – If the element cannot be found.

variablesSequence (*Instantiation self*)

Returns the sequence of DiscreteVariable of this instantiation.

Return type List

1.4.2 Potential

class `pyAgrum.Potential(*args)`

Class representing a potential.

Available ructors:

`Potential() -> Potential`

`Potential(src) -> Potential`

Parameters `src` (`pyAgrum.Potential` (page 37)) – The Potential to copy

Returns The new Potential

Return type `pyAgrum.Potential` (page 37)

KL (*Potential self, Potential p*)

Check the compatibility and compute the Kullback-Leibler divergence between the potential and.

Parameters `p` (`pyAgrum.Potential` (page 37)) – the potential from which we want to calculate the divergence.

Returns The value of the divergence

Return type float

Raises

- `gum.InvalidArgument` – If p is not compatible with the potential (dimension, variables)
- `gum.FatalError` – If a zero is found in p or the potential and not in the other.

abs (*Potential self*)

Apply abs on every element of the container

Returns a reference to the modified potential.

Return type `pyAgrum.Potential` (page 37)

add (*Potential self, DiscreteVariable v*)

Add a discrete variable to the potential.

Parameters `v` (`pyAgrum.DiscreteVariable` (page 21)) – the var to be added

Raises

- `DuplicateElement` (page 159) – If the variable is already in this Potential.
- `InvalidArgument` (page 161) – If the variable is empty.

argmax (*Potential self*)

argmin (*Potential self*)

contains (*Potential self, DiscreteVariable v*)

Parameters `v` (`pyAgrum.Potential` (page 37)) – a DiscreteVariable.

Returns True if the var is in the potential

Return type bool

draw (*Potential self*)

draw a value using the potential as a probability table.

Returns the index of the drawn value

Return type int

empty (*Potential self*)

Returns Returns true if no variable is in the potential.

Return type bool

entropy (*Potential self*)

Returns the entropy of the potential

Return type double

extract (*Potential self, Instantiation inst*)

extract(Potential self, PyObject * dict) -> Potential

create a new Potential extracted from self given a partial instantiation.

Parameters

- **inst** (*pyAgrum.instantiation*) – a partial instantiation
- **dict** (*dict*) – a dictionnary containing discrete variables (?)

Returns the new Potential

Return type *pyAgrum.Potential* (page 37)

fill (*v*)

Deprecated method in pyAgrum>0.12.0. See fillWith instead.

fillWith (*Potential self, Potential src*)

fillWith(Potential self, Potential src, Vector_string mapSrc) -> Potential
 fillWith(Potential self, Vector v) -> Potential
 fillWith(Potential self, double v) -> Potential

Automatically fills the potential with v.

Parameters **v** (number or list or *pyAgrum.Potential* the number of parameters of the Potential) – a value or a list/*pyAgrum.Potential* containing the values to fill the Potential with.

Warning: if v is a list, the size of the list must be the if v is a *pyAgrum.Potential*. It must to contain variables with exactly the same names and labels but not necessarily the same variables.

Returns a reference to the modified potentia

Return type *pyAgrum.Potential* (page 37)

Raises gum.SizeError – If v size’s does not matches the domain size.

findAll (*Potential self, double v*)

get (*Potential self, Instantiation i*)

Parameters **i** (*pyAgrum.Instantiation* (page 32)) – an Instantiation

Returns the value in the Potential at the position given by the instantiation

Return type double

isNonZeroMap (*Potential self*)

Returns a boolean-like potential using the predicate isNonZero

Return type *pyAgrum.Potential* (page 37)

argMaxIn (*Potential self, PyObject * varnames*)

Projection using max as operation.

Parameters **varnames** (*set*) – the set of vars to keep

Returns the projected Potential

Return type *pyAgrum.Potential* (page 37)

argMaxOut (*Potential self, PyObject * varnames*)

Projection using max as operation.

Parameters **varnames** (*set*) – the set of vars to eliminate

Returns the projected Potential

Return type *pyAgrum.Potential* (page 37)

Raises `gum.InvalidArgument` – If varnames contains only one variable that does not exist in the Potential

argMinIn (*Potential self, PyObject * varnames*)

Projection using min as operation.

Parameters **varnames** (*set*) – the set of vars to keep

Returns the projected Potential

Return type *pyAgrum.Potential* (page 37)

argMinOut (*Potential self, PyObject * varnames*)

Projection using min as operation.

Parameters **varnames** (*set*) – the set of vars to eliminate

Returns the projected Potential

Return type *pyAgrum.Potential* (page 37)

Warning: `InvalidArgument` raised if varnames contains only one variable that does not exist in the Potential

argProdIn (*Potential self, PyObject * varnames*)

Projection using multiplication as operation.

Parameters **varnames** (*set*) – the set of vars to keep

Returns the projected Potential

Return type *pyAgrum.Potential* (page 37)

argProdOut (*Potential self, PyObject * varnames*)

Projection using multiplication as operation.

Parameters **varnames** (*set*) – the set of vars to eliminate

Returns the projected Potential

Return type *pyAgrum.Potential* (page 37)

Raises `gum.InvalidArgument` – If varnames contains only one variable that does not exist in the Potential

argSumIn (*Potential self, PyObject * varnames*)

Projection using sum as operation.

Parameters **varnames** (*set*) – the set of vars to keep

Returns the projected Potential

Return type *pyAgrum.Potential* (page 37)

margSumOut (*Potential self, PyObject * varnames*)

Projection using sum as operation.

Parameters **varnames** (*set*) – the set of vars to eliminate

Returns the projected Potential

Return type *pyAgrum.Potential* (page 37)

Raises *gum.InvalidArgument* – If varnames contains only one variable that does not exist in the Potential

max (*Potential self*)

Returns the maximum of all elements in the Potential

Return type double

maxNonOne (*Potential self*)

Returns the maximum of non one elements in the Potential

Return type double

Raises *gum.NotFound* – If all value == 1.0

min (*Potential self*)

Returns the min of all elements in the Potential

Return type double

minNonZero (*Potential self*)

Returns the min of non zero elements in the Potential

Return type double

Raises *gum.NotFound* – If all value == 0.0

nbrDim (*Potential self*)

Returns the number of vars in the multidimensional container.

Return type int

newFactory (*Potential self*)

Erase the Potential content and create a new empty one.

Returns a reference to the new Potential

Return type *pyAgrum.Potential* (page 37)

normalize (*Potential self*)

Normalize the Potential (do nothing if sum is 0)

Returns a reference to the normalized Potential

Return type *pyAgrum.Potential* (page 37)

normalizeAsCPT (*Potential self*)

Normalize the Potential as a CPT

Returns a reference to the normalized Potential

Return type *pyAgrum.Potential* (page 37)

Raises *gum.FatalError* – If some distribution sums to 0

pos (*Potential self, DiscreteVariable v*)

Parameters **v** (*pyAgrum.DiscreteVariable* (page 21)) – The variable for which the index is returned.

Returns

Return type Returns the index of a variable.

Raises `gum.NotFound` – If v is not in this multidimensional matrix.

product (*Potential self*)

Returns the product of all elements in the Potential

Return type double

putFirst (*Potential self, PyObject * varname*)

Parameters `v` (`pyAgrum.DiscreteVariable` (page 21)) – The variable for which the index should be 0.

Returns a reference to the modified potential

Return type `pyAgrum.Potential` (page 37)

Raises `gum.InvalidArgument` – If the var is not in the potential

remove (*Potential self, DiscreteVariable var*)

Parameters `v` (`pyAgrum.DiscreteVariable` (page 21)) – The variable to be removed

Returns a reference to the modified potential

Return type `pyAgrum.Potential` (page 37)

Warning: IndexError raised if the var is not in the potential

reorganize (*Potential self, vector< pyAgrum.DiscreteVariable *, allocator< pyAgrum.DiscreteVariable *> > vars*)
`reorganize(Potential self, PyObject * varnames) -> Potential`

Create a new Potential with another order.

Returns `varnames` – a list of the var names in the new order

Return type list

Returns a reference to the modified potential

Return type `pyAgrum.Potential` (page 37)

scale (*Potential self, double v*)

Create a new potential multiplied by v.

Parameters `v` (`double`) – a multiplier

Returns

Return type a reference to the modified potential

set (*Potential self, Instantiation i, double value*)

Change the value pointed by i

Parameters

- `i` (`pyAgrum.Instantiation` (page 32)) – The Instantiation to be changed
- `value` (`double`) – The new value of the Instantiation

sq (*Potential self*)

Square all the values in the Potential

sum (*Potential self*)

Returns the sum of all elements in the Potential

Return type double

thisown

The membership flag

toarray()

Returns the potential as an array

Return type array

tolist()

Returns the potential as a list

Return type list

translate (*Potential self, double v*)

Create a new potential added with v.

Parameters *v* (*double*) – The value to be added

Returns

Return type a reference to the modified potential

var_dims

Returns a list containing the dimensions of each variables in the potential

Return type list

var_names

Returns a list containing the name of each variables in the potential

Return type list

Warning: Listed in reverse from the variable enumeration order

variable (*Potential self, int i*)

variable(Potential self, str name) -> DiscreteVariable

Parameters *i* (*int*) – An index of this multidimensional matrix.

Returns

Return type the varible at the ith index

Raises gum.NotFound – If i does not reference a variable in this multidimensional matrix.

variablesSequence()

Returns a list containing the sequence of variables

Return type list

1.5 Bayesian Network

The Bayesian Network is the main object of pyAgrum. A Bayesian network is a probabilistic graphical model. It represents a joint distribution over a set of random variables. In pyAgrum, the variables are (for now) only discrete. A Bayesian network uses a directed acyclic graph (DAG) to represent conditional independencies in the joint distribution. These conditional independencies allow to factorize the joint distribution, thereby allowing to compactly represent very large ones. Moreover, inference algorithms can also use this graph to speed up the computations. Finally, the Bayesian networks can be learnt from data.

1.5.1 Model

class pyAgrum.BayesNet (*args)

BayesNet represents a Bayesian Network.

Available ructors: BayesNet (name=' ') -> BayesNet

BayesNet (source) -> BayesNet

Parameters

- **name** (*str*) – the name of the Bayes Net (optional)
- **source** ([pyAgrum.BayesNet](#) (page 43)) – the Bayesian network to copy

add (BayesNet self, DiscreteVariable var)

add(BayesNet self, str name, unsigned int nbrmod) -> int add(BayesNet self, DiscreteVariable var, pyAgrum.MultiDimImplementation aContent) -> int add(BayesNet self, DiscreteVariable var, int id) -> int add(BayesNet self, DiscreteVariable var, pyAgrum.MultiDimImplementation aContent, int id) -> int

Add a variable to the pyAgrum.BayesNet.

Parameters

- **variable** ([pyAgrum.DiscreteVariable](#) (page 21)) – the variable added
- **name** (*str*) – the variable name
- **nbrmod** (*int*) – the numbre of modalities for the new variable
- **id** (*int*) – the variable forced id in the pyAgrum.BayesNet

Returns the id of the new node

Return type int

Raises

- gum.DuplicateLabel – If variable.name() is already used in this pyAgrum.BayesNet.
- gum.NotAllowed – If nbrmod<2
- gum.DuplicateElement – If id is already used.

addAMPLITUDE (BayesNet self, DiscreteVariable var)

Others aggregators

Parameters **variable** ([pyAgrum.DiscreteVariable](#) (page 21)) – the variable to be added

Returns the id of the added value

Return type int

addAND (BayesNet self, DiscreteVariable var)

Add a variable, it's associate node and an AND implementation.

The id of the new variable is automatically generated.

Parameters **variable** ([pyAgrum.DiscreteVariable](#) (page 21)) – The variable added by copy.

Returns the id of the added variable.

Return type int

Raises gum.SizeError – If variable.domainSize()>2

addArc (*BayesNet self, int tail, int head*)
addArc(*BayesNet self, str tail, str head*)

Add an arc in the BN, and update arc.head's CPT.

Parameters

- **head** – a variable's id (int)
- **tail** – a variable's id (int)
- **head** – a variable's name (str)
- **tail** – a variable's name (str)

Raises `gum.InvalidEdge` – If arc.tail and/or arc.head are not in the BN.

addCOUNT (*BayesNet self, DiscreteVariable var, int value=1*)

Others aggregators

Parameters **variable** ([pyAgrum.DiscreteVariable](#) (page 21)) – the variable to be added

Returns the id of the added value

Return type int

addEXISTS (*BayesNet self, DiscreteVariable var, int value=1*)

Others aggregators

Parameters **variable** ([pyAgrum.DiscreteVariable](#) (page 21)) – the variable to be added

Returns the id of the added value

Return type int

addFORALL (*BayesNet self, DiscreteVariable var, int value=1*)

Others aggregators

Parameters **variable** ([pyAgrum.DiscreteVariable](#) (page 21)) – the variable to be added

Returns the id of the added variable.

Return type int

addLogit (*BayesNet self, DiscreteVariable var, double external_weight, int id*)

addLogit(*BayesNet self, DiscreteVariable var, double external_weight*) -> int

Add a variable, its associate node and a Logit implementation.

(The id of the new variable can be automatically generated.)

Parameters

- **variable** ([pyAgrum.DiscreteVariable](#) (page 21)) – The variable added by copy
- **externalWeight** (`double`) – the added external weight
- **id** (`int`) – The proposed id for the variable.

Returns the id of the added variable.

Return type int

Raises `gum.DuplicateElement` – If id is already used

addMAX (*BayesNet self, DiscreteVariable var*)

Others aggregators

Parameters **variable** ([pyAgrum.DiscreteVariable](#) (page 21)) – the variable to be added

Returns the id of the added value

Return type int

addMEDIAN (*BayesNet self, DiscreteVariable var*)

Others aggregators

Parameters **variable** (`pyAgrum.DiscreteVariable` (page 21)) – the variable to be added

Returns the id of the added value

Return type int

addMIN (*BayesNet self, DiscreteVariable var*)

Others aggregators

Parameters **variable** (`pyAgrum.DiscreteVariable` (page 21)) – the variable to be added

Returns the id of the added value

Return type int

addNoisyAND (*BayesNet self, DiscreteVariable var, double external_weight, int id*)

`addNoisyAND(BayesNet self, DiscreteVariable var, double external_weight) -> int`

Add a variable, its associate node and a noisyAND implementation.

(The id of the new variable can be automatically generated.)

Parameters

- **variable** (`pyAgrum.DiscreteVariable` (page 21)) – The variable added by copy
- **externalWeight** (`double`) – the added external weight
- **id** (`int`) – The proposed id for the variable.

Returns the id of the added variable.

Return type int

Raises `gum.DuplicateElement` – If id is already used

addNoisyOR (*BayesNet self, DiscreteVariable var, double external_weight*)

`addNoisyOR(BayesNet self, DiscreteVariable var, double external_weight, int id) -> int`

Add a variable, it's associate node and a noisyOR implementation.

Since it seems that the ‘classical’ noisyOR is the Compound noisyOR, we keep the addNoisyOR as an alias for addNoisyORCompound.

(The id of the new variable can be automatically generated.)

Parameters

- **variable** (`pyAgrum.DiscreteVariable` (page 21)) – The variable added by copy
- **externalWeight** (`double`) – the added external weight
- **id** (`int`) – The proposed id for the variable.

Returns the id of the added variable.

Return type int

Raises `gum.DuplicateElement` – If id is already used

addNoisyORCompound (*BayesNet self, DiscreteVariable var, double external_weight*)
 addNoisyORCompound(BayesNet self, DiscreteVariable var, double external_weight, int id) -> int
 Add a variable, it's associate node and a noisyOR implementation.
 Since it seems that the ‘classical’ noisyOR is the Compound noisyOR, we keep the addNoisyOR as an alias for addNoisyORCompound.
 (The id of the new variable can be automatically generated.)

Parameters

- **variable** ([pyAgrum.DiscreteVariable](#) (page 21)) – The variable added by copy
- **externalWeight** (*double*) – the added external weight
- **id** (*int*) – The proposed id for the variable.

Returns the id of the added variable.

Return type int

Raises `gum.DuplicateElement` – If id is already used

addNoisyORNet (*BayesNet self, DiscreteVariable var, double external_weight*)
 addNoisyORNet(BayesNet self, DiscreteVariable var, double external_weight, int id) -> int
 Add a variable, its associate node and a noisyOR implementation.
 Since it seems that the ‘classical’ noisyOR is the Compound noisyOR, we keep the addNoisyOR as an alias for addNoisyORCompound.
 (The id of the new variable can be automatically generated.)

Parameters

- **variable** ([pyAgrum.DiscreteVariable](#) (page 21)) – The variable added by copy
- **externalWeight** (*double*) – the added external weight
- **id** (*int*) – The proposed id for the variable.

Returns the id of the added variable.

Return type int

addOR (*BayesNet self, DiscreteVariable var*)
 Add a variable, it's associate node and an OR implementation.
 The id of the new variable is automatically generated.

Warning: If parents are not boolean, all value>1 is True

Parameters **variable** ([pyAgrum.DiscreteVariable](#) (page 21)) – The variable added by copy

Returns the id of the added variable.

Return type int

Raises `gum.SizeError` – If variable.domainSize()>2

addStructureListener (*whenNodeAdded=None, whenNodeDeleted=None, whenArcAdded=None, whenArcDeleted=None*)
 Add the listeners in parameters to the list of existing ones.

Parameters

- **whenNodeAdded** (*lambda expression*) – a function for when a node is added
- **whenNodeDeleted** (*lambda expression*) – a function for when a node is removed
- **whenArcAdded** (*lambda expression*) – a function for when an arc is added
- **whenArcDeleted** (*lambda expression*) – a function for when an arc is removed

addWeightedArc (*BayesNet self, int tail, int head, double causalWeight*)

addWeightedArc(BayesNet self, str tail, str head, double causalWeight)

Add an arc in the BN, and update arc.head's CPT.

Parameters

- **head** – a variable's id (int)
- **tail** – a variable's id (int)
- **head** – a variable's name (str)
- **tail** – a variable's name (str)
- **causalWeight** (double) – the added causal weight

Raises

- gum.InvalidArc – If arc.tail and/or arc.head are not in the BN.
- gum.InvalidArc – If variable in arc.head is not a NoisyOR variable.

arcs (*IBayesNet self*)

Returns The list of arcs in the IBayesNet

Return type list

beginTopologyTransformation (*BayesNet self*)

When inserting/removing arcs, node CPTs change their dimension with a cost in time. begin Multiple Change for all CPTs These functions delay the CPTs change to be done just once at the end of a sequence of topology modification, begins a sequence of insertions/deletions of arcs without changing the dimensions of the CPTs.

changePotential (*BayesNet self, int id, Potential newPot*)

changePotential(BayesNet self, str name, Potential newPot)

change the CPT associated to nodeId to newPot delete the old CPT associated to nodeId.

Parameters

- **newPot** ([pyAgrum.Potential](#) (page 37)) – the new potential
- **NodeId** (int) – the id of the node
- **name** (str) – the name of the variable

Raises gum.NotAllowed – If newPot has not the same signature as __probaMap[NodeId]

changeVariableLabel (*BayesNet self, int id, str old_label, str new_label*)

changeVariableLabel(BayesNet self, str name, str old_label, str new_label)

change the label of the variable associated to nodeId to the new value.

Parameters

- **id** (int) – the id of the node
- **name** (str) – the name of the variable
- **old_label** (str) – the new label
- **new_label** (str) – the new label

Raises `gum.NotFound` – if id/name is not a variable or if old_label does not exist.

changeVariableName (*BayesNet self*, *int id*, *str new_name*)
`changeVariableName(BayesNet self, str name, str new_name)`

Changes a variable's name in the pyAgrum.BayesNet.

This will change the pyAgrum.DiscreteVariable names in the pyAgrum.BayesNet.

Parameters

- **new_name** (*str*) – the new name of the variable
- **NodeId** (*int*) – the id of the node
- **name** (*str*) – the name of the variable

Raises

- `gum.DuplicateLabel` – If new_name is already used in this BayesNet.
- `gum.NotFound` – If no variable matches id.

children (*IBayesNet self*, *int id*)

Parameters **id** (*int*) – the id of the parent

Returns the set of all the children

Return type Set

completeInstantiation (*DAGmodel self*)

Get an instantiation over all the variables of the model.

Returns the complete instantiation

Return type pyAgrum.instantiation

cpt (*BayesNet self*, *int varId*)

`cpt(BayesNet self, str name) -> Potential`

Returns the CPT of a variable.

Parameters

- **VarId** (*int*) – A variable's id in the pyAgrum.BayesNet.
- **name** (*str*) – A variable's name in the pyAgrum.BayesNet.

Returns The variable's CPT.

Return type [pyAgrum.Potential](#) (page 37)

Raises `gum.NotFound` – If no variable's id matches varId.

dag (*BayesNet self*)

Returns a ant reference to the dag of this BayesNet.

Return type [pyAgrum.DAG](#) (page 9)

dim (*IBayesNet self*)

Returns the dimension (the number of free parameters) in this BayesNet.

Returns the dimension of the BayesNet

Return type int

empty (*DAGmodel self*)

Returns True if the model is empty

Return type bool

endTopologyTransformation (*BayesNet self*)

Terminates a sequence of insertions/deletions of arcs by adjusting all CPTs dimensions. End Multiple Change for all CPTs.

Returns

Return type [pyAgrum.BayesNet](#) (page 43)

erase (*BayesNet self, int varId*)

`erase(BayesNet self, str name) erase(BayesNet self, DiscreteVariable var)`

Remove a variable from the pyAgrum.BayesNet.

Removes the corresponding variable from the pyAgrum.BayesNet and from all of its children pyAgrum.Potential.

If no variable matches the given id, then nothing is done.

Parameters

- **id** (*int*) – The variable's id to remove.
- **name** (*str*) – The variable's name to remove.
- **var** ([pyAgrum.DiscreteVariable](#) (page 21)) – A reference on the variable to remove.

eraseArc (*BayesNet self, Arc arc*)

`eraseArc(BayesNet self, int tail, int head) eraseArc(BayesNet self, str tail, str head)`

Removes an arc in the BN, and update head's CTP.

If (tail, head) doesn't exist, the nothing happens.

Parameters

- **arc** ([pyAgrum.Arc](#) (page 5)) – The arc to be removed.
- **head** – a variable's id (int)
- **tail** – a variable's id (int)
- **head** – a variable's name (str)
- **tail** – a variable's name (str)

static fastPrototype (*str dotlike, int domainSize=2*)

Create a bn with a dotlike syntax : ‘a->b->c;b->d;’.

The domain size maybe specified using ‘a[10]’.

Note that if the dotlike string contains such a specification for an already defined variable, the first specification will be used.

Parameters

- **dotlike** (*str*) – the string containing the specification
- **domainSize** (*int*) – the default domain size for variables

Returns the resulting bayesian network

Return type [pyAgrum.BayesNet](#) (page 43)

generateCPT (*BayesNet self, int node*)

`generateCPT(BayesNet self, str name)`

Randomly generate CPT for a given node in a given structure.

Parameters

- **node** (*int*) – The variable's id.
- **name** (*str*) – The variable's name.

generateCPTs (*BayesNet self*)

Randomly generates CPTs for a given structure.

hasSameStructure (*DAGmodel self, DAGmodel other*)

Parameters `pyAgrum.DAGmodel1` – a direct acyclic model

Returns True if all the named node are the same and all the named arcs are the same

Return type bool

idFromName (*BayesNet self, str name*)

Returns a variable's id given its name in the graph.

Parameters `name (str)` – The variable's name from which the id is returned.

Returns The variable's node id.

Return type int

Raises `gum.NotFound` – If name does not match a variable in the graph

ids()

Deprecated method in pyAgrum>0.12.0. See nodes instead.

jointProbability (*IBayesNet self, Instantiation i*)

Parameters `i (pyAgrum.instantiation)` – an instantiation of the variables

Returns a parameter of the joint probability for the BayesNet

Return type double

Warning: a variable not present in the instantiation is assumed to be instantiated to 0

loadBIF (*BayesNet self, str name, PyObject * l=(PyObject *) 0*)

Load a BIF file.

Parameters

- **name** (`str`) – the file's name
- **l** (`list`) – list of functions to execute

Raises

- `gum.IOError` – If file not found
- `gum.FatalError` – If file is not valid

loadBIFXML (*BayesNet self, str name, PyObject * l=(PyObject *) 0*)

Load a BIFXML file.

Parameters

- **name** (`str`) – the name's file
- **l** (`list`) – list of functions to execute

Raises

- `gum.IOError` – If file not found
- `gum.FatalError` – If file is not valid

loadDSL (*BayesNet self, str name, PyObject * l=(PyObject *) 0*)

Load a DSL file.

Parameters

- **name** (`str`) – the file's name

- **l** (*list*) – list of functions to execute

Raises

- `gum.IOError` – If file not found
- `gum.FatalError` – If file is not valid

loadNET (*BayesNet self, str name, PyObject * l=(PyObject *) 0*)

Load a NET file.

Parameters

- **name** (*str*) – the name's file
- **l** (*list*) – list of functions to execute

Raises

- `gum.IOError` – If file not found
- `gum.FatalError` – If file is not valid

loadO3PRM (*BayesNet self, str name, str system="", str classpath="", PyObject * l=(PyObject *) 0*)

Load an O3PRM file.

Warning: The O3PRM language is the only language allowing to manipulate not only DiscretizedVariable but also RangeVariable and LabelizedVariable.

Parameters

- **name** (*str*) – the file's name
- **system** (*str*) – the system's name
- **classpath** (*str*) – the classpath
- **l** (*list*) – list of functions to execute

Raises

- `gum.IOError` – If file not found
- `gum.FatalError` – If file is not valid

loadUAI (*BayesNet self, str name, PyObject * l=(PyObject *) 0*)

Load an UAI file.

Parameters

- **name** (*str*) – the name's file
- **l** (*list*) – list of functions to execute

Raises

- `gum.IOError` – If file not found
- `gum.FatalError` – If file is not valid

log10DomainSize (*BayesNet self*)**Returns** The log10 domain size of the joint probability for the model.**Return type** double**log2JointProbability** (*IBayesNet self, Instantiation i*)**Parameters** **i** (`pyAgrum.instantiation`) – an instantiation of the variables**Returns** a parameter of the log joint probability for the BayesNet

Return type double

Warning: a variable not present in the instantiation is assumed to be instantiated to 0

maxNonOneParam (*IBayesNet self*)

Returns The biggest value (not equal to 1) in the CPTs of the BayesNet

Return type double

maxParam (*IBayesNet self*)

Returns the biggest value in the CPTs of the BayesNet

Return type double

maxVarDomainSize (*IBayesNet self*)

Returns the biggest domain size among the variables of the BayesNet

Return type int

minNonZeroParam (*IBayesNet self*)

Returns the smallest value (not equal to 0) in the CPTs of the IBayesNet

Return type double

minParam (*IBayesNet self*)

Returns the smallest value in the CPTs of the IBayesNet

Return type double

minimalCondSet (*IBayesNet self, int target, Set soids*)

minimalCondSet(IBayesNet self, Set targets, Set soids) -> Set minimalCondSet(IBayesNet self, int target, PyObject * list) -> PyObject minimalCondSet(IBayesNet self, PyObject * targets, PyObject * list) -> PyObject *

Returns, given one or many targets and a list of variables, the minimal set of those needed to calculate the target/targets.

Parameters

- **target** (*int*) – The id of the target
- **targets** (*list*) – The ids of the targets
- **list** (*list*) – The list of available variables

Returns The minimal set of variables

Return type Set

moralGraph (*DAGmodel self, bool clear=True*)

Returns the moral graph of the BayesNet, formed by adding edges between all pairs of nodes that have a common child, and then making all edges in the graph undirected.

Returns The moral graph

Return type *pyAgrum.UndiGraph* (page 11)

names (*IBayesNet self*)

Returns The names of the graph variables

Return type list

nodeId (*BayesNet self, DiscreteVariable var*)

Parameters **var** (*pyAgrum.DiscreteVariable* (page 21)) – a variable

Returns the id of the variable

Return type int

Raises gum.IndexError – If the graph does not contain the variable

nodes (*BayesNet self*)

Returns the set of ids

Return type set

parents (*IBayesNet self, int id*)

Parameters **id** – The id of the child node

Returns the set of the parents ids.

Return type Set

reverseArc (*BayesNet self, int tail, int head*)
reverseArc(*BayesNet self, str tail, str head*) **reverseArc**(*BayesNet self, Arc arc*)

Reverses an arc while preserving the same joint distribution.

Parameters

- **tail** – (int) the id of the tail variable
- **head** – (int) the id of the head variable
- **tail** – (str) the name of the tail variable
- **head** – (str) the name of the head variable
- **arc** ([pyAgrum.Arc \(page 5\)](#)) – an arc

Raises gum.InvalidArc – If the arc does not exist or if its reversal would induce a directed cycle.

saveBIF (*BayesNet self, str name*)
Save the BayesNet in a BIF file.

Parameters **name** (*str*) – the file's name

saveBIFXML (*BayesNet self, str name*)
Save the BayesNet in a BIFXML file.

Parameters **name** (*str*) – the file's name

saveDSL (*BayesNet self, str name*)
Save the BayesNet in a DSL file.

Parameters **name** (*str*) – the file's name

saveNET (*BayesNet self, str name*)
Save the BayesNet in a NET file.

Parameters **name** (*str*) – the file's name

saveO3PRM (*BayesNet self, str name*)
Save the BayesNet in an O3PRM file.

Warning: The O3PRM language is the only language allowing to manipulate not only DiscretizedVariable but also RangeVariable and LabelizedVariable.

Parameters **name** (*str*) – the file's name

saveUAI (*BayesNet self, str name*)
Save the BayesNet in an UAI file.

Parameters `name` (*str*) – the file’s name
size (*BayesNet self*)
 Returns the number of nodes in the graph
 Return type int
sizeArcs (*DAGmodel self*)
 Returns the number of arcs in the graph
 Return type int
thisown
 The membership flag
toDot (*IBayesNet self*)
 Returns a friendly display of the graph in DOT format
 Return type str
topologicalOrder (*DAGmodel self*, *bool clear=True*)
 Returns the list of the nodes Ids in a topological order
 Return type List
 Raises `gum.InvalidDirectedCycle` – If this graph contains cycles
variable (*BayesNet self*, *int id*)
 variable(*BayesNet self*, *str name*) -> *DiscreteVariable*
Parameters

- `id` (*int*) – a variable’s id
- `name` (*str*) – a variable’s name

Returns the variable
Return type *pyAgrum.DiscreteVariable* (page 21)
Raises `gum.IndexError` – If the graph does not contain the variable
variableFromName (*BayesNet self*, *str name*)
Parameters `name` (*str*) – a variable’s name
Returns the variable
Return type *pyAgrum.DiscreteVariable* (page 21)
Raises `gum.IndexError` – If the graph does not contain the variable
variableNodeMap (*BayesNet self*)
Returns the variable node map
Return type *pyAgrum.variableNodeMap*

1.5.2 Exact Inference

1.5.2.1 Lazy Propagation

```
class pyAgrum.LazyPropagation(*args)
    Class used for Lazy Propagation

    Available ructors: LazyPropagation(bn) -> LazyPropagation

    Parameters bn (pyAgrum.BayesNet (page 43)) – a Bayesian network
```

BN (*LazyPropagation self*)

Returns A ant reference over the IBayesNet referenced by this class.

Return type pyAgrum.IBayesNet

Raises gum.UndefinedElement – If no Bayes net has been assigned to the inference.

H (*LazyPropagation self, int X*)

H(*LazyPropagation self, str nodeName*) -> double

Parameters

- **x** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Returns the computed Shanon's entropy of a node given the observation

Return type double

I (*LazyPropagation self, int X, int Y*)**Parameters**

- **x** (*int*) – a node Id
- **y** (*int*) – another node Id

Returns the computed Shanon's entropy of a node given the observation

Return type double

VI (*LazyPropagation self, int X, int Y*)**Parameters**

- **x** (*int*) – a node Id
- **y** (*int*) – another node Id

Returns variation of information between X and Y

Return type double

addAllTargets (*LazyPropagation self*)

Add all the nodes as targets.

addEvidence (*LazyPropagation self, int id, int val*)

addEvidence(*LazyPropagation self, str nodeName, int val*) addEvidence(*LazyPropagation self, int id, str val*) addEvidence(*LazyPropagation self, str nodeName, str val*) addEvidence(*LazyPropagation self, int id, Vector vals*) addEvidence(*LazyPropagation self, str nodeName, Vector vals*)

Adds a new evidence on a node (might be soft or hard).

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*int*) – a node name
- **val** – (*int*) a node value
- **val** – (*str*) the label of the node value
- **vals** (*list*) – a list of values

Raises

- gum.InvalidArgument – If the node already has an evidence
- gum.InvalidArgument – If val is not a value for the node
- gum.InvalidArgument – If the size of vals is different from the domain side of the node

- `gum.FatalError` – If vals is a vector of 0s
- `gum.UndefinedElement` – If the node does not belong to the Bayesian network

addJointTarget (*LazyPropagation self, PyObject *list*)

Add a list of nodes as a new joint target. As a collateral effect, every node is added as a marginal target.

Parameters `list` – a list of names of nodes

Raises `gum.UndefinedElement` – If some node(s) do not belong to the Bayesian network

addTarget (*LazyPropagation self, int target*)

`addTarget(LazyPropagation self, str nodeName)`

Add a marginal target to the list of targets.

Parameters

- `target (int)` – a node Id
- `nodeName (str)` – a node name

Raises `gum.UndefinedElement` – If target is not a NodeId in the Bayes net

chgEvidence (*LazyPropagation self, int id, int val*)

`chgEvidence(LazyPropagation self, str nodeName, int val)` `chgEvidence(LazyPropagation self, int id, str val)` `chgEvidence(LazyPropagation self, str nodeName, str val)` `chgEvidence(LazyPropagation self, int id, Vector vals)` `chgEvidence(LazyPropagation self, str nodeName, Vector vals)`

Change the value of an already existing evidence on a node (might be soft or hard).

Parameters

- `id (int)` – a node Id
- `nodeName (int)` – a node name
- `val – (int)` a node value
- `val – (str)` the label of the node value
- `vals (list)` – a list of values

Raises

- `gum.InvalidArgument` – If the node does not already have an evidence
- `gum.InvalidArgument` – If val is not a value for the node
- `gum.InvalidArgument` – If the size of vals is different from the domain side of the node
- `gum.FatalError` – If vals is a vector of 0s
- `gum.UndefinedElement` – If the node does not belong to the Bayesian network

eraseAllEvidence (*LazyPropagation self*)

Removes all the evidence entered into the network.

eraseAllJointTargets (*LazyPropagation self*)

Clear all previously defined joint targets.

eraseAllMarginalTargets (*LazyPropagation self*)

Clear all the previously defined marginal targets.

eraseAllTargets (*LazyPropagation self*)

Clear all previously defined targets (marginal and joint targets).

As a result, no posterior can be computed (since we can only compute the posteriors of the marginal or joint targets that have been added by the user).

eraseEvidence (*LazyPropagation self, int id*)
eraseEvidence(*LazyPropagation self, str nodeName*)

Remove the evidence, if any, corresponding to the node Id or name.

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*int*) – a node name

Raises `gum.IndexError` – If the node does not belong to the Bayesian network

eraseJointTarget (*LazyPropagation self, PyObject * list*)
eraseJointTarget(*LazyPropagation self*, *list*)

Remove, if existing, the joint target.

Parameters **list** – a list of names or Ids of nodes

Raises

- `gum.IndexError` – If one of the node does not belong to the Bayesian network
- `gum.UndefinedElement` – If node Id is not in the Bayesian network

eraseTarget (*LazyPropagation self, int target*)
eraseTarget(*LazyPropagation self, str nodeName*)

Remove, if existing, the marginal target.

Parameters

- **target** (*int*) – a node Id
- **nodeName** (*int*) – a node name

Raises

- `gum.IndexError` – If one of the node does not belong to the Bayesian network
- `gum.UndefinedElement` – If node Id is not in the Bayesian network

evidenceImpact (*LazyPropagation self, int target, PyObject * evs*)
evidenceImpact(*LazyPropagation self, str target, Vector_string evs*) -> Potential

Create a `pyAgrum.Potential` for $P(\text{target}|\text{levs})$ (for all instantiation of target and evs)

Parameters

- **target** (*set*) – a set of targets ids or names.
- **evs** (*set*) – a set of nodes ids or names.

Warning: if some evs are d-separated, they are not included in the Potential.

Returns a Potential for $P(\text{targets}|\text{levs})$

Return type `pyAgrum.Potential` (page 37)

evidenceJointImpact (*LazyPropagation self, PyObject * targets, PyObject * evs*)
evidenceJointImpact(*LazyPropagation self, Vector_string targets, Vector_string evs*) -> Potential

Create a `pyAgrum.Potential` for $P(\text{joint targets}|\text{levs})$ (for all instantiation of targets and evs)

Parameters

- **targets** – (int) a node Id
- **targets** – (str) a node name
- **evs** (*set*) – a set of nodes ids or names.

Returns a Potential for $P(\text{target}|\text{levs})$

Return type `pyAgrum.Potential` (page 37)

Raises `gum.Exception` – If some evidene entered into the Bayes net are incompatible
(their joint proba = 0)

evidenceProbability (`LazyPropagation self`)

Returns the probability of evidence

Return type double

hardEvidenceNodes (`LazyPropagation self`)

Returns the set of nodes with hard evidence

Return type set

hasEvidence (`LazyPropagation self, int id`)

`hasEvidence(LazyPropagation self, str nodeName) -> bool`

Parameters

- **id** (`int`) – a node Id
- **nodeName** (`str`) – a node name

Returns True if some node(s) (or the one in parameters) have received evidence

Return type bool

Raises `gum.IndexError` – If the node does not belong to the Bayesian network

hasHardEvidence (`LazyPropagation self, str nodeName`)

Parameters

- **id** (`int`) – a node Id
- **nodeName** (`str`) – a node name

Returns True if node has received a hard evidence

Return type bool

Raises `gum.IndexError` – If the node does not belong to the Bayesian network

hasSoftEvidence (`LazyPropagation self, int id`)

`hasSoftEvidence(LazyPropagation self, str nodeName) -> bool`

Parameters

- **id** (`int`) – a node Id
- **nodeName** (`str`) – a node name

Returns True if node has received a soft evidence

Return type bool

Raises `gum.IndexError` – If the node does not belong to the Bayesian network

isJointTarget (`LazyPropagation self, PyObject * list`)

Parameters `list` – a list of nodes ids or names.

Returns True if target is a joint target.

Return type bool

Raises

- `gum.IndexError` – If the node does not belong to the Bayesian network
- `gum.UndefinedElement` – If node Id is not in the Bayesian network

isTarget (*LazyPropagation self, int variable*)
 isTarget(LazyPropagation self, str nodeName) -> bool

Parameters

- **variable** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Returns True if variable is a (marginal) target**Return type** bool**Raises**

- gum.IndexError – If the node does not belong to the Bayesian network
- gum.UndefinedElement – If node Id is not in the Bayesian network

joinTree (*LazyPropagation self*)**Returns** the current join tree used**Return type** *pyAgrum.CliqueGraph* (page 13)**jointMutualInformation** (*LazyPropagation self, PyObject * targets*)**jointPosterior** (*LazyPropagation self, PyObject * list*)

Compute the joint posterior of a set of nodes.

Parameters **list** – the list of nodes whose posterior joint probability is wanted

Warning: The order of the variables given by the list here or when the jointTarget is declared can not be assumed to be used bu the Potential.

Returns a ref to the posterior joint probability of the set of nodes.**Return type** *pyAgrum.Potential* (page 37)**Raises** gum.UndefinedElement – If an element of nodes is not in targets**jointTargets** (*LazyPropagation self*)**Returns** the list of target sets**Return type** list**junctionTree** (*LazyPropagation self*)**Returns** the current junction tree**Return type** *pyAgrum.CliqueGraph* (page 13)**makeInference** (*LazyPropagation self*)

Perform the heavy computations needed to compute the targets' posteriors

In a Junction tree propagation scheme, for instance, the heavy computations are those of the messages sent in the JT. This is precisely what makeInference should compute. Later, the computations of the posteriors can be done ‘lightly’ by multiplying and projecting those messages.

nbrEvidence (*LazyPropagation self*)**Returns** the number of evidence entered into the Bayesian network**Return type** int**nbrHardEvidence** (*LazyPropagation self*)**Returns** the number of hard evidence entered into the Bayesian network**Return type** int

nbrJointTargets (*LazyPropagation self*)

Returns the number of joint targets

Return type int

nbrSoftEvidence (*LazyPropagation self*)

Returns the number of soft evidence entered into the Bayesian network

Return type int

nbrTargets (*LazyPropagation self*)

Returns the number of marginal targets

Return type int

posterior (*LazyPropagation self, int var*)

posterior(*LazyPropagation self*, str *nodeName*) -> Potential

Computes and returns the posterior of a node.

Parameters

- **var** (*int*) – the node Id of the node for which we need a posterior probability
- **nodeName** (*str*) – the node name of the node for which we need a posterior probability

Returns a ref to the posterior probability of the node

Return type *pyAgrum.Potential* (page 37)

Raises *gum.UndefinedElement* – If an element of nodes is not in targets

setEvidence (*evidces*)

Erase all the evidences and apply addEvidence(key,value) for every pairs in evidces.

Parameters **evidces** (*dict*) – a dict of evidences

Raises

- *gum.InvalidArgument* – If one value is not a value for the node
- *gum.InvalidArgument* – If the size of a value is different from the domain side of the node
- *gum.FatalError* – If one value is a vector of 0s
- *gum.UndefinedElement* – If one node does not belong to the Bayesian network

setTargets (*targets*)

Remove all the targets and add the ones in parameter.

Parameters **targets** (*set*) – a set of targets

Raises *gum.UndefinedElement* – If one target is not in the Bayes net

softEvidenceNodes (*LazyPropagation self*)

Returns the set of nodes with soft evidence

Return type set

targets (*LazyPropagation self*)

Returns the list of marginal targets

Return type list

thisown

The membership flag

updateEvidence (*evidces*)

Apply chgEvidence(key,value) for every pairs in evidces (or addEvidence).

Parameters **evidces** (*dict*) – a dict of evidences

Raises

- gum.InvalidArgument – If one value is not a value for the node
- gum.InvalidArgument – If the size of a value is different from the domain side of the node
- gum.FatalError – If one value is a vector of 0s
- gum.UndefinedElement – If one node does not belong to the Bayesian network

1.5.2.2 Shafer Shenoy Inference

class pyAgrum.**ShaferShenoyInference** (*args)

Class used for Shafer-Shenoy inferences.

Available ructors: ShaferShenoyInference (bn) → ShaferShenoyInference

Parameters **bn** (pyAgrum.BayesNet (page 43)) – a Bayesian network

BN (*ShaferShenoyInference self*)

Returns A ant reference over the IBayesNet referenced by this class.

Return type pyAgrum.IBayesNet

Raises gum.UndefinedElement – If no Bayes net has been assigned to the inference.

H (*ShaferShenoyInference self, int X*)

H(*ShaferShenoyInference self, str nodeName*) -> double

Parameters

- **X** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Returns the computed Shanon's entropy of a node given the observation

Return type double

I (*ShaferShenoyInference self, int X, int Y*)

Parameters

- **X** (*int*) – a node Id
- **Y** (*int*) – another node Id

Returns the computed Shanon's entropy of a node given the observation

Return type double

VI (*ShaferShenoyInference self, int X, int Y*)

Parameters

- **X** (*int*) – a node Id
- **Y** (*int*) – another node Id

Returns variation of information between X and Y

Return type double

addAllTargets (*ShaferShenoyInference self*)

Add all the nodes as targets.

addEvidence (*ShaferShenoyInference self, int id, int val*)
addEvidence(ShaferShenoyInference self, str nodeName, int val) addEvidence(ShaferShenoyInference self, int id, str val) addEvidence(ShaferShenoyInference self, str nodeName, str val) addEvidence(ShaferShenoyInference self, int id, Vector vals) addEvidence(ShaferShenoyInference self, str nodeName, Vector vals)

Adds a new evidence on a node (might be soft or hard).

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*int*) – a node name
- **val** – (int) a node value
- **val** – (str) the label of the node value
- **vals** (*list*) – a list of values

Raises

- gum.InvalidArgument – If the node already has an evidence
- gum.InvalidArgument – If val is not a value for the node
- gum.InvalidArgument – If the size of vals is different from the domain side of the node
- gum.FatalError – If vals is a vector of 0s
- gum.UndefinedElement – If the node does not belong to the Bayesian network

addJointTarget (*ShaferShenoyInference self, PyObject *list*)

Add a list of nodes as a new joint target. As a collateral effect, every node is added as a marginal target.

Parameters **list** – a list of names of nodes

Raises gum.UndefinedElement – If some node(s) do not belong to the Bayesian network

addTarget (*ShaferShenoyInference self, int target*)

addTarget(ShaferShenoyInference self, str nodeName)

Add a marginal target to the list of targets.

Parameters

- **target** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Raises gum.UndefinedElement – If target is not a NodeId in the Bayes net

chgEvidence (*ShaferShenoyInference self, int id, int val*)

chgEvidence(ShaferShenoyInference self, str nodeName, int val) chgEvidence(ShaferShenoyInference self, int id, str val) chgEvidence(ShaferShenoyInference self, str nodeName, str val) chgEvidence(ShaferShenoyInference self, int id, Vector vals) chgEvidence(ShaferShenoyInference self, str nodeName, Vector vals)

Change the value of an already existing evidence on a node (might be soft or hard).

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*int*) – a node name
- **val** – (int) a node value
- **val** – (str) the label of the node value

- **vals** (*list*) – a list of values

Raises

- gum.InvalidArgument – If the node does not already have an evidence
- gum.InvalidArgument – If val is not a value for the node
- gum.InvalidArgument – If the size of vals is different from the domain side of the node
- gum.FatalError – If vals is a vector of 0s
- gum.UndefinedElement – If the node does not belong to the Bayesian network

eraseAllEvidence (*ShaferShenoyInference self*)

Removes all the evidence entered into the network.

eraseAllJointTargets (*ShaferShenoyInference self*)

Clear all previously defined joint targets.

eraseAllMarginalTargets (*ShaferShenoyInference self*)

Clear all the previously defined marginal targets.

eraseAllTargets (*ShaferShenoyInference self*)

Clear all previously defined targets (marginal and joint targets).

As a result, no posterior can be computed (since we can only compute the posteriors of the marginal or joint targets that have been added by the user).

eraseEvidence (*ShaferShenoyInference self, int id*)

`eraseEvidence(ShaferShenoyInference self, str nodeName)`

Remove the evidence, if any, corresponding to the node Id or name.

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*int*) – a node name

Raises gum.IndexError – If the node does not belong to the Bayesian network

eraseJointTarget (*ShaferShenoyInference self, PyObject * list*)

Remove, if existing, the joint target.

Parameters **list** – a list of names or Ids of nodes

Raises

- gum.IndexError – If one of the node does not belong to the Bayesian network
- gum.UndefinedElement – If node Id is not in the Bayesian network

eraseTarget (*ShaferShenoyInference self, int target*)

`eraseTarget(ShaferShenoyInference self, str nodeName)`

Remove, if existing, the marginal target.

Parameters

- **target** (*int*) – a node Id
- **nodeName** (*int*) – a node name

Raises

- gum.IndexError – If one of the node does not belong to the Bayesian network
- gum.UndefinedElement – If node Id is not in the Bayesian network

evidenceImpact (*ShaferShenoyInference self, int target, PyObject * evs*)
evidenceImpact(ShaferShenoyInference self, str target, Vector_string evs) -> Potential
Create a pyAgrum.Potential for P(targetlevs) (for all instantiation of target and evs)

Parameters

- **target** (*set*) – a set of targets ids or names.
- **evs** (*set*) – a set of nodes ids or names.

Warning: if some evs are d-separated, they are not included in the Potential.

Returns a Potential for P(targetslevs)

Return type *pyAgrum.Potential* (page 37)

evidenceJointImpact (*ShaferShenoyInference self, PyObject * targets, PyObject * evs*)
evidenceJointImpact(ShaferShenoyInference self, Vector_string targets, Vector_string evs) -> Potential
Create a pyAgrum.Potential for P(joint targetslevs) (for all instantiation of targets and evs)

Parameters

- **targets** – (int) a node Id
- **targets** – (str) a node name
- **evs** (*set*) – a set of nodes ids or names.

Returns a Potential for P(targetlevs)

Return type *pyAgrum.Potential* (page 37)

Raises *gum.Exception* – If some evidene entered into the Bayes net are incompatible
(their joint proba = 0)

evidenceProbability (*ShaferShenoyInference self*)

Returns the probability of evidence

Return type double

hardEvidenceNodes (*ShaferShenoyInference self*)

Returns the set of nodes with hard evidence

Return type set

hasEvidence (*ShaferShenoyInference self, int id*)

hasEvidence(ShaferShenoyInference self, str nodeName) -> bool

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Returns True if some node(s) (or the one in parameters) have received evidence

Return type bool

Raises *gum.IndexError* – If the node does not belong to the Bayesian network

hasHardEvidence (*ShaferShenoyInference self, str nodeName*)

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Returns True if node has received a hard evidence

Return type bool

Raises gum.IndexError – If the node does not belong to the Bayesian network

hasSoftEvidence (*ShaferShenoyInference self, int id*)

hasSoftEvidence(*ShaferShenoyInference self, str nodeName*) -> bool

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Returns True if node has received a soft evidence

Return type bool

Raises gum.IndexError – If the node does not belong to the Bayesian network

isJointTarget (*ShaferShenoyInference self, PyObject * list*)

Parameters **list** – a list of nodes ids or names.

Returns True if target is a joint target.

Return type bool

Raises

- gum.IndexError – If the node does not belong to the Bayesian network
- gum.UndefinedElement – If node Id is not in the Bayesian network

isTarget (*ShaferShenoyInference self, int variable*)

isTarget(*ShaferShenoyInference self, str nodeName*) -> bool

Parameters

- **variable** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Returns True if variable is a (marginal) target

Return type bool

Raises

- gum.IndexError – If the node does not belong to the Bayesian network
- gum.UndefinedElement – If node Id is not in the Bayesian network

joinTree (*ShaferShenoyInference self*)

Returns the current join tree used

Return type *pyAgrum.CliqueGraph* (page 13)

jointMutualInformation (*ShaferShenoyInference self, PyObject * targets*)

jointPosterior (*ShaferShenoyInference self, PyObject * list*)

Compute the joint posterior of a set of nodes.

Parameters **list** – the list of nodes whose posterior joint probability is wanted

Warning: The order of the variables given by the list here or when the jointTarget is declared can not be assumed to be used bu the Potential.

Returns a ref to the posterior joint probability of the set of nodes.

Return type *pyAgrum.Potential* (page 37)

Raises `gum.UndefinedElement` – If an element of nodes is not in targets

jointTargets (`ShaferShenoyInference self`)

Returns the list of target sets

Return type list

junctionTree (`ShaferShenoyInference self`)

Returns the current junction tree

Return type `pyAgrum.CliqueGraph` (page 13)

makeInference (`ShaferShenoyInference self`)

Perform the heavy computations needed to compute the targets' posteriors

In a Junction tree propagation scheme, for instance, the heavy computations are those of the messages sent in the JT. This is precisely what makeInference should compute. Later, the computations of the posteriors can be done ‘lightly’ by multiplying and projecting those messages.

nbrEvidence (`ShaferShenoyInference self`)

Returns the number of evidence entered into the Bayesian network

Return type int

nbrHardEvidence (`ShaferShenoyInference self`)

Returns the number of hard evidence entered into the Bayesian network

Return type int

nbrJointTargets (`ShaferShenoyInference self`)

Returns the number of joint targets

Return type int

nbrSoftEvidence (`ShaferShenoyInference self`)

Returns the number of soft evidence entered into the Bayesian network

Return type int

nbrTargets (`ShaferShenoyInference self`)

Returns the number of marginal targets

Return type int

posterior (`ShaferShenoyInference self, int var`)

`posterior(ShaferShenoyInference self, str nodeName) -> Potential`

Computes and returns the posterior of a node.

Parameters

- **var** (`int`) – the node Id of the node for which we need a posterior probability
- **nodeName** (`str`) – the node name of the node for which we need a posterior probability

Returns a ref to the posterior probability of the node

Return type `pyAgrum.Potential` (page 37)

Raises `gum.UndefinedElement` – If an element of nodes is not in targets

setEvidence (`evidces`)

Erase all the evidences and apply addEvidence(key,value) for every pairs in evidces.

Parameters `evidces` (`dict`) – a dict of evidences

Raises

- gum.InvalidArgument – If one value is not a value for the node
- gum.InvalidArgument – If the size of a value is different from the domain side of the node
- gum.FatalError – If one value is a vector of 0s
- gum.UndefinedElement – If one node does not belong to the Bayesian network

setTargets(targets)

Remove all the targets and add the ones in parameter.

Parameters **targets** (*set*) – a set of targets

Raises gum.UndefinedElement – If one target is not in the Bayes net

softEvidenceNodes(ShaferShenoyInference self)

Returns the set of nodes with soft evidence

Return type set

targets(ShaferShenoyInference self)

Returns the list of marginal targets

Return type list

thisown

The membership flag

updateEvidence(evidces)

Apply chgEvidence(key,value) for every pairs in evidces (or addEvidence).

Parameters **evidces** (*dict*) – a dict of evidences

Raises

- gum.InvalidArgument – If one value is not a value for the node
- gum.InvalidArgument – If the size of a value is different from the domain side of the node
- gum.FatalError – If one value is a vector of 0s
- gum.UndefinedElement – If one node does not belong to the Bayesian network

1.5.2.3 Variable Elimination

class pyAgrum.VariableElimination(*args)

Class used for Variable Elimination inference algorithm.

Available ructors: VariableElimination(bn) -> VariableElimination

Parameters **bn** (pyAgrum.BayesNet (page 43)) – a Bayesian network

BN(VariableElimination self)

Returns A ant reference over the IBayesNet referenced by this class.

Return type pyAgrum.IBayesNet

Raises gum.UndefinedElement – If no Bayes net has been assigned to the inference.

H(VariableElimination self, int X)

H(VariableElimination self, str nodeName) -> double

Parameters

- **X** (*int*) – a node Id

- **nodeName** (*str*) – a node name

Returns the computed Shanon's entropy of a node given the observation

Return type double

addAllTargets (*VariableElimination self*)

Add all the nodes as targets.

addEvidence (*VariableElimination self, int id, int val*)

addEvidence(*VariableElimination self, str nodeName, int val*) addEvidence(*VariableElimination self, int id, str val*) addEvidence(*VariableElimination self, str nodeName, str val*) addEvidence(*VariableElimination self, int id, Vector vals*) addEvidence(*VariableElimination self, str nodeName, Vector vals*)

Adds a new evidence on a node (might be soft or hard).

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*int*) – a node name
- **val** – (*int*) a node value
- **val** – (*str*) the label of the node value
- **vals** (*list*) – a list of values

Raises

- `gum.InvalidArgument` – If the node already has an evidence
- `gum.InvalidArgument` – If val is not a value for the node
- `gum.InvalidArgument` – If the size of vals is different from the domain side of the node
- `gum.FatalError` – If vals is a vector of 0s
- `gum.UndefinedElement` – If the node does not belong to the Bayesian network

addJointTarget (*VariableElimination self, PyObject *list*)

Add a list of nodes as a new joint target. As a collateral effect, every node is added as a marginal target.

Parameters **list** – a list of names of nodes

Raises `gum.UndefinedElement` – If some node(s) do not belong to the Bayesian network

addTarget (*VariableElimination self, int target*)

addTarget(*VariableElimination self, str nodeName*)

Add a marginal target to the list of targets.

Parameters

- **target** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Raises `gum.UndefinedElement` – If target is not a NodeId in the Bayes net

chgEvidence (*VariableElimination self, int id, int val*)

chgEvidence(*VariableElimination self, str nodeName, int val*) chgEvidence(*VariableElimination self, int id, str val*) chgEvidence(*VariableElimination self, str nodeName, str val*) chgEvidence(*VariableElimination self, int id, Vector vals*) chgEvidence(*VariableElimination self, str nodeName, Vector vals*)

Change the value of an already existing evidence on a node (might be soft or hard).

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*int*) – a node name
- **val** – (*int*) a node value
- **val** – (*str*) the label of the node value
- **vals** (*list*) – a list of values

Raises

- gum.InvalidArgument – If the node does not already have an evidence
- gum.InvalidArgument – If val is not a value for the node
- gum.InvalidArgument – If the size of vals is different from the domain side of the node
- gum.FatalError – If vals is a vector of 0s
- gum.UndefinedElement – If the node does not belong to the Bayesian network

eraseAllEvidence (*VariableElimination self*)

Removes all the evidence entered into the network.

eraseAllTargets (*VariableElimination self*)

Clear all previously defined targets (marginal and joint targets).

As a result, no posterior can be computed (since we can only compute the posteriors of the marginal or joint targets that have been added by the user).

eraseEvidence (*VariableElimination self, int id*)

`eraseEvidence(VariableElimination self, str nodeName)`

Remove the evidence, if any, corresponding to the node Id or name.

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*int*) – a node name

Raises gum.IndexError – If the node does not belong to the Bayesian network

eraseJointTarget (*VariableElimination self, PyObject * list*)

Remove, if existing, the joint target.

Parameters **list** – a list of names or Ids of nodes

Raises

- gum.IndexError – If one of the node does not belong to the Bayesian network
- gum.UndefinedElement – If node Id is not in the Bayesian network

eraseTarget (*VariableElimination self, int target*)

`eraseTarget(VariableElimination self, str nodeName)`

Remove, if existing, the marginal target.

Parameters

- **target** (*int*) – a node Id
- **nodeName** (*int*) – a node name

Raises

- gum.IndexError – If one of the node does not belong to the Bayesian network
- gum.UndefinedElement – If node Id is not in the Bayesian network

evidenceImpact (*VariableElimination self, int target, PyObject * evs*)
evidenceImpact(VariableElimination self, str target, Vector_string evs) -> Potential
Create a pyAgrum.Potential for P(targetlevs) (for all instantiation of target and evs)

Parameters

- **target** (*set*) – a set of targets ids or names.
- **evs** (*set*) – a set of nodes ids or names.

Warning: if some evs are d-separated, they are not included in the Potential.

Returns a Potential for P(targetslevs)

Return type [pyAgrum.Potential](#) (page 37)

evidenceJointImpact (*VariableElimination self, PyObject * targets, PyObject * evs*)
Create a pyAgrum.Potential for P(joint targetslevs) (for all instantiation of targets and evs)

Parameters

- **targets** – (int) a node Id
- **targets** – (str) a node name
- **evs** (*set*) – a set of nodes ids or names.

Returns a Potential for P(targetlevs)

Return type [pyAgrum.Potential](#) (page 37)

Raises gum.Exception – If some evidene entered into the Bayes net are incompatible
(their joint proba = 0)

hardEvidenceNodes (*VariableElimination self*)

Returns the set of nodes with hard evidence

Return type set

hasEvidence (*VariableElimination self, int id*)
hasEvidence(VariableElimination self, str nodeName) -> bool

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Returns True if some node(s) (or the one in parameters) have received evidence

Return type bool

Raises gum.IndexError – If the node does not belong to the Bayesian network

hasHardEvidence (*VariableElimination self, str nodeName*)

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Returns True if node has received a hard evidence

Return type bool

Raises gum.IndexError – If the node does not belong to the Bayesian network

hasSoftEvidence (*VariableElimination self, int id*)

hasSoftEvidence(VariableElimination self, str nodeName) -> bool

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Returns True if node has received a soft evidence**Return type** bool**Raises** gum.IndexError – If the node does not belong to the Bayesian network**isJointTarget** (*VariableElimination self, PyObject *list*)**Parameters** **list** – a list of nodes ids or names.**Returns** True if target is a joint target.**Return type** bool**Raises**

- gum.IndexError – If the node does not belong to the Bayesian network
- gum.UndefinedElement – If node Id is not in the Bayesian network

isTarget (*VariableElimination self, int variable*)isTarget(*VariableElimination self, str nodeName*) -> bool**Parameters**

- **variable** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Returns True if variable is a (marginal) target**Return type** bool**Raises**

- gum.IndexError – If the node does not belong to the Bayesian network
- gum.UndefinedElement – If node Id is not in the Bayesian network

jointMutualInformation (*VariableElimination self, PyObject *targets*)**jointPosterior** (*VariableElimination self, PyObject *list*)

Compute the joint posterior of a set of nodes.

Parameters **list** – the list of nodes whose posterior joint probability is wanted

Warning: The order of the variables given by the list here or when the jointTarget is declared can not be assumed to be used bu the Potential.

Returns a ref to the posterior joint probability of the set of nodes.**Return type** [pyAgrum.Potential](#) (page 37)**Raises** gum.UndefinedElement – If an element of nodes is not in targets**jointTargets** (*VariableElimination self*)**Returns** the list of target sets**Return type** list**junctionTree** (*VariableElimination self, int id*)**Returns** the current junction tree**Return type** [pyAgrum.CliqueGraph](#) (page 13)

makeInference (*VariableElimination self*)

Perform the heavy computations needed to compute the targets' posteriors

In a Junction tree propagation scheme, for instance, the heavy computations are those of the messages sent in the JT. This is precisely what makeInference should compute. Later, the computations of the posteriors can be done ‘lightly’ by multiplying and projecting those messages.

nbrEvidence (*VariableElimination self*)

Returns the number of evidence entered into the Bayesian network

Return type int

nbrHardEvidence (*VariableElimination self*)

Returns the number of hard evidence entered into the Bayesian network

Return type int

nbrSoftEvidence (*VariableElimination self*)

Returns the number of soft evidence entered into the Bayesian network

Return type int

nbrTargets (*VariableElimination self*)

Returns the number of marginal targets

Return type int

posterior (*VariableElimination self, int var*)

posterior(*VariableElimination self*, str *nodeName*) -> Potential

Computes and returns the posterior of a node.

Parameters

- **var** (int) – the node Id of the node for which we need a posterior probability
- **nodeName** (str) – the node name of the node for which we need a posterior probability

Returns a ref to the posterior probability of the node

Return type [pyAgrum.Potential](#) (page 37)

Raises gum.UndefinedElement – If an element of nodes is not in targets

setEvidence (*evidces*)

Erase all the evidences and apply addEvidence(key,value) for every pairs in evidces.

Parameters **evidces** (*dict*) – a dict of evidences

Raises

- gum.InvalidArgument – If one value is not a value for the node
- gum.InvalidArgument – If the size of a value is different from the domain side of the node
- gum.FatalError – If one value is a vector of 0s
- gum.UndefinedElement – If one node does not belong to the Bayesian network

setTargets (*targets*)

Remove all the targets and add the ones in parameter.

Parameters **targets** (*set*) – a set of targets

Raises gum.UndefinedElement – If one target is not in the Bayes net

softEvidenceNodes (*VariableElimination self*)

Returns the set of nodes with soft evidence

Return type set

targets (*VariableElimination self*)

Returns the list of marginal targets

Return type list

thisown

The membership flag

updateEvidence (*evidces*)

Apply chgEvidence(key,value) for every pairs in evidces (or addEvidence).

Parameters **evidces** (*dict*) – a dict of evidences

Raises

- gum.InvalidArgument – If one value is not a value for the node
- gum.InvalidArgument – If the size of a value is different from the domain side of the node
- gum.FatalError – If one value is a vector of 0s
- gum.UndefinedElement – If one node does not belong to the Bayesian network

1.5.3 Approximate Inference

1.5.3.1 Loopy Belief Propagation

class pyAgrum.**LoopyBeliefPropagation** (*bn: pyAgrum.pyAgrum.IBayesNet*)

Class used for inferences using loopy belief propagation algorithm.

Available ructors: LoopyBeliefPropagation (*bn*) -> LoopyBeliefPropagation

Parameters **bn** ([pyAgrum.BayesNet](#) (page 43)) – a Bayesian network

BN (*LoopyBeliefPropagation self*)

Returns A ant reference over the IBayesNet referenced by this class.

Return type pyAgrum.IBayesNet

Raises gum.UndefinedElement – If no Bayes net has been assigned to the inference.

H (*LoopyBeliefPropagation self, int X*)

H(*LoopyBeliefPropagation self, str nodeName*) -> double

Parameters

- **x** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Returns the computed Shanon's entropy of a node given the observation

Return type double

addAllTargets (*LoopyBeliefPropagation self*)

Add all the nodes as targets.

addEvidence (*LoopyBeliefPropagation self, int id, int val*)

addEvidence(*LoopyBeliefPropagation self, str nodeName, int val*) addEvidence(*LoopyBeliefPropagation self, int id, str val*) addEvidence(*LoopyBeliefPropagation self, str nodeName, str val*) addEvidence(*LoopyBeliefPropagation self, int id, Vector vals*) addEvidence(*LoopyBeliefPropagation self, str nodeName, Vector vals*)

Adds a new evidence on a node (might be soft or hard).

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*int*) – a node name
- **val** – (*int*) a node value
- **val** – (*str*) the label of the node value
- **vals** (*list*) – a list of values

Raises

- gum.InvalidArgument – If the node already has an evidence
- gum.InvalidArgument – If val is not a value for the node
- gum.InvalidArgument – If the size of vals is different from the domain side of the node
- gum.FatalError – If vals is a vector of 0s
- gum.UndefinedElement – If the node does not belong to the Bayesian network

addTarget (*LoopyBeliefPropagation self, int target*)addTarget(*LoopyBeliefPropagation self, str nodeName*)

Add a marginal target to the list of targets.

Parameters

- **target** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Raises gum.UndefinedElement – If target is not a NodeId in the Bayes net**chgEvidence** (*LoopyBeliefPropagation self, int id, int val*)chgEvidence(*LoopyBeliefPropagation self, str nodeName, int val*) chgEvidence(*LoopyBeliefPropagation self, int id, str val*) chgEvidence(*LoopyBeliefPropagation self, str nodeName, str val*) chgEvidence(*LoopyBeliefPropagation self, int id, Vector vals*) chgEvidence(*LoopyBeliefPropagation self, str nodeName, Vector vals*)

Change the value of an already existing evidence on a node (might be soft or hard).

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*int*) – a node name
- **val** – (*int*) a node value
- **val** – (*str*) the label of the node value
- **vals** (*list*) – a list of values

Raises

- gum.InvalidArgument – If the node does not already have an evidence
- gum.InvalidArgument – If val is not a value for the node
- gum.InvalidArgument – If the size of vals is different from the domain side of the node
- gum.FatalError – If vals is a vector of 0s
- gum.UndefinedElement – If the node does not belong to the Bayesian network

currentTime (*LoopyBeliefPropagation self*)**Returns** get the current running time in second (double)

Return type double

epsilon (*LoopyBeliefPropagation self*)

Returns the value of epsilon

Return type double

eraseAllEvidence (*LoopyBeliefPropagation self*)

Removes all the evidence entered into the network.

eraseAllTargets (*LoopyBeliefPropagation self*)

Clear all previously defined targets (marginal and joint targets).

As a result, no posterior can be computed (since we can only compute the posteriors of the marginal or joint targets that have been added by the user).

eraseEvidence (*LoopyBeliefPropagation self, int id*)

eraseEvidence(*LoopyBeliefPropagation self, str nodeName*)

Remove the evidence, if any, corresponding to the node Id or name.

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*int*) – a node name

Raises `gum.IndexError` – If the node does not belong to the Bayesian network

eraseTarget (*LoopyBeliefPropagation self, int target*)

eraseTarget(*LoopyBeliefPropagation self, str nodeName*)

Remove, if existing, the marginal target.

Parameters

- **target** (*int*) – a node Id
- **nodeName** (*int*) – a node name

Raises

- `gum.IndexError` – If one of the node does not belong to the Bayesian network
- `gum.UndefinedElement` – If node Id is not in the Bayesian network

evidenceImpact (*LoopyBeliefPropagation self, int target, PyObject * evs*)

evidenceImpact(*LoopyBeliefPropagation self, str target, Vector_string evs*) -> Potential

Create a `pyAgrum.Potential` for $P(\text{target}|\text{levs})$ (for all instantiation of target and evs)

Parameters

- **target** (*set*) – a set of targets ids or names.
- **evs** (*set*) – a set of nodes ids or names.

Warning: if some evs are d-separated, they are not included in the Potential.

Returns a Potential for $P(\text{targets}|\text{levs})$

Return type `pyAgrum.Potential` (page 37)

hardEvidenceNodes (*LoopyBeliefPropagation self*)

Returns the set of nodes with hard evidence

Return type set

hasEvidence (*LoopyBeliefPropagation self, int id*)
hasEvidence(LoopyBeliefPropagation self, str nodeName) -> bool

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Returns True if some node(s) (or the one in parameters) have received evidence

Return type bool

Raises gum.IndexError – If the node does not belong to the Bayesian network

hasHardEvidence (*LoopyBeliefPropagation self, str nodeName*)

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Returns True if node has received a hard evidence

Return type bool

Raises gum.IndexError – If the node does not belong to the Bayesian network

hasSoftEvidence (*LoopyBeliefPropagation self, int id*)

hasSoftEvidence(LoopyBeliefPropagation self, str nodeName) -> bool

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Returns True if node has received a soft evidence

Return type bool

Raises gum.IndexError – If the node does not belong to the Bayesian network

history (*LoopyBeliefPropagation self*)

Returns the scheme history

Return type tuple

Raises gum.OperationNotAllowed – If the scheme did not performed or if verbosity is set to false

isTarget (*LoopyBeliefPropagation self, int variable*)

isTarget(LoopyBeliefPropagation self, str nodeName) -> bool

Parameters

- **variable** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Returns True if variable is a (marginal) target

Return type bool

Raises

- gum.IndexError – If the node does not belong to the Bayesian network
- gum.UndefinedElement – If node Id is not in the Bayesian network

makeInference (*LoopyBeliefPropagation self*)

Perform the heavy computations needed to compute the targets' posteriors

In a Junction tree propagation scheme, for instance, the heavy computations are those of the messages sent in the JT. This is precisely what `makeInference` should compute. Later, the computations of the posteriors can be done ‘lightly’ by multiplying and projecting those messages.

maxIter (*LoopyBeliefPropagation self*)

Returns the criterion on number of iterations

Return type int

maxTime (*LoopyBeliefPropagation self*)

Returns the timeout(in seconds)

Return type double

messageApproximationScheme (*LoopyBeliefPropagation self*)

Returns the approximation scheme message

Return type str

minEpsilonRate (*LoopyBeliefPropagation self*)

Returns the value of the minimal epsilon rate

Return type double

nbrEvidence (*LoopyBeliefPropagation self*)

Returns the number of evidence entered into the Bayesian network

Return type int

nbrHardEvidence (*LoopyBeliefPropagation self*)

Returns the number of hard evidence entered into the Bayesian network

Return type int

nbrIterations (*LoopyBeliefPropagation self*)

Returns the number of iterations

Return type int

nbrSoftEvidence (*LoopyBeliefPropagation self*)

Returns the number of soft evidence entered into the Bayesian network

Return type int

nbrTargets (*LoopyBeliefPropagation self*)

Returns the number of marginal targets

Return type int

periodSize (*LoopyBeliefPropagation self*)

Returns the number of samples between 2 stopping

Return type int

Raises gum.OutOfLowerBound – If p<1

posterior (*LoopyBeliefPropagation self, int var*)

posterior(LoopyBeliefPropagation self, str nodeName) -> Potential

Computes and returns the posterior of a node.

Parameters

- **var** (*int*) – the node Id of the node for which we need a posterior probability
- **nodeName** (*str*) – the node name of the node for which we need a posterior probability

Returns a ref to the posterior probability of the node

Return type *pyAgrum.Potential* (page 37)

Raises *gum.UndefinedElement* – If an element of nodes is not in targets

setEpsilon (*LoopyBeliefPropagation self, double eps*)

Parameters **eps** (*double*) – the epsilon we want to use

Raises *gum.OutOfLowerBound* – If *eps*<0

setEvidence (*evidces*)

Erase all the evidences and apply addEvidence(key,value) for every pairs in evidces.

Parameters **evidces** (*dict*) – a dict of evidences

Raises

- *gum.InvalidArgument* – If one value is not a value for the node
- *gum.InvalidArgument* – If the size of a value is different from the domain side of the node
- *gum.FatalError* – If one value is a vector of 0s
- *gum.UndefinedElement* – If one node does not belong to the Bayesian network

setMaxIter (*LoopyBeliefPropagation self, int max*)

Parameters **max** (*int*) – the maximum number of iteration

Raises *gum.OutOfLowerBound* – If *max* <= 1

setMaxTime (*LoopyBeliefPropagation self, double timeout*)

Parameters **timeout** (*double*) – stopping criterion on timeout (in seconds)

Raises *gum.OutOfLowerBound* – If *timeout*<=0.0

setMinEpsilonRate (*LoopyBeliefPropagation self, double rate*)

Parameters **rate** (*double*) – the minimal epsilon rate

setPeriodSize (*LoopyBeliefPropagation self, int p*)

Parameters **p** (*int*) – number of samples between 2 stopping

Raises *gum.OutOfLowerBound* – If *p*<1

setTargets (*targets*)

Remove all the targets and add the ones in parameter.

Parameters **targets** (*set*) – a set of targets

Raises *gum.UndefinedElement* – If one target is not in the Bayes net

setVerbosity (*LoopyBeliefPropagation self, bool v*)

Parameters **v** (*bool*) – verbosity

softEvidenceNodes (*LoopyBeliefPropagation self*)

Returns the set of nodes with soft evidence

Return type set

targets (*LoopyBeliefPropagation self*)

Returns the list of marginal targets

Return type list

thisown

The membership flag

updateEvidence (*evidces*)

Apply chgEvidence(key,value) for every pairs in evidces (or addEvidence).

Parameters **evidces** (*dict*) – a dict of evidences

Raises

- gum.InvalidArgument – If one value is not a value for the node
- gum.InvalidArgument – If the size of a value is different from the domain side of the node
- gum.FatalError – If one value is a vector of 0s
- gum.UndefinedElement – If one node does not belong to the Bayesian network

verbosity (*LoopyBeliefPropagation self*)

Returns True if the verbosity is enabled

Return type bool

1.5.3.2 Sampling

1.5.3.2.1 Gibbs Sampling

class pyAgrum.GibbsSampling (*bn: pyAgrum.pyAgrum.IBayesNet*)

Class for making Gibbs sampling inference in bayesian networks.

Available ructors: GibbsSampling (*bn*) –> GibbsSampling

Parameters **bn** ([pyAgrum.BayesNet](#) (page 43)) – a Bayesian network

BN (*GibbsSampling self*)

Returns A ant reference over the IBayesNet referenced by this class.

Return type pyAgrum.IBayesNet

Raises gum.UndefinedElement – If no Bayes net has been assigned to the inference.

H (*GibbsSampling self, int X*)

H(GibbsSampling self, str nodeName) -> double

Parameters

- **X** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Returns the computed Shanon's entropy of a node given the observation

Return type double

addAllTargets (*GibbsSampling self*)

Add all the nodes as targets.

addEvidence (*GibbsSampling self, int id, int val*)

addEvidence(GibbsSampling self, str nodeName, int val) addEvidence(GibbsSampling self, int id, str val) addEvidence(GibbsSampling self, str nodeName, str val) addEvidence(GibbsSampling self, int id, Vector vals) addEvidence(GibbsSampling self, str nodeName, Vector vals)

Adds a new evidence on a node (might be soft or hard).

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*int*) – a node name
- **val** – (*int*) a node value
- **val** – (*str*) the label of the node value
- **vals** (*list*) – a list of values

Raises

- gum.InvalidArgument – If the node already has an evidence
- gum.InvalidArgument – If val is not a value for the node
- gum.InvalidArgument – If the size of vals is different from the domain side of the node
- gum.FatalError – If vals is a vector of 0s
- gum.UndefinedElement – If the node does not belong to the Bayesian network

addTarget (*GibbsSampling self, int target*)

addTarget(*GibbsSampling self, str nodeName*)

Add a marginal target to the list of targets.

Parameters

- **target** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Raises gum.UndefinedElement – If target is not a NodeId in the Bayes net

burnIn (*GibbsSampling self*)

Returns size of burn in on number of iteration

Return type int

chgEvidence (*GibbsSampling self, int id, int val*)

chgEvidence(*GibbsSampling self, str nodeName, int val*) chgEvidence(*GibbsSampling self, int id, str val*) chgEvidence(*GibbsSampling self, str nodeName, str val*) chgEvidence(*GibbsSampling self, int id, Vector vals*) chgEvidence(*GibbsSampling self, str nodeName, Vector vals*)

Change the value of an already existing evidence on a node (might be soft or hard).

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*int*) – a node name
- **val** – (*int*) a node value
- **val** – (*str*) the label of the node value
- **vals** (*list*) – a list of values

Raises

- gum.InvalidArgument – If the node does not already have an evidence
- gum.InvalidArgument – If val is not a value for the node
- gum.InvalidArgument – If the size of vals is different from the domain side of the node
- gum.FatalError – If vals is a vector of 0s
- gum.UndefinedElement – If the node does not belong to the Bayesian network

currentPosterior (*GibbsSampling self, int id*)
 currentPosterior(GibbsSampling self, str name) -> Potential
 Computes and returns the current posterior of a node.

Parameters

- **var** (*int*) – the node Id of the node for which we need a posterior probability
- **nodeName** (*str*) – the node name of the node for which we need a posterior probability

Returns a ref to the current posterior probability of the node**Return type** *pyAgrum.Potential* (page 37)**Raises** *UndefinedElement* (page 163) – If an element of nodes is not in targets**currentTime** (*GibbsSampling self*)**Returns** get the current running time in second (double)**Return type** double**epsilon** (*GibbsSampling self*)**Returns** the value of epsilon**Return type** double**eraseAllEvidence** (*GibbsSampling self*)

Removes all the evidence entered into the network.

eraseAllTargets (*GibbsSampling self*)

Clear all previously defined targets (marginal and joint targets).

As a result, no posterior can be computed (since we can only compute the posteriors of the marginal or joint targets that have been added by the user).

eraseEvidence (*GibbsSampling self, int id*)

eraseEvidence(GibbsSampling self, str nodeName)

Remove the evidence, if any, corresponding to the node Id or name.

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*int*) – a node name

Raises *gum.IndexError* – If the node does not belong to the Bayesian network**eraseTarget** (*GibbsSampling self, int target*)

eraseTarget(GibbsSampling self, str nodeName)

Remove, if existing, the marginal target.

Parameters

- **target** (*int*) – a node Id
- **nodeName** (*int*) – a node name

Raises

- *gum.IndexError* – If one of the node does not belong to the Bayesian network
- *gum.UndefinedElement* – If node Id is not in the Bayesian network

evidenceImpact (*GibbsSampling self, int target, PyObject * evs*)

evidenceImpact(GibbsSampling self, str target, Vector_string evs) -> Potential

Create a *pyAgrum.Potential* for P(target|levs) (for all instantiation of target and evs)**Parameters**

- **target** (*set*) – a set of targets ids or names.
- **evs** (*set*) – a set of nodes ids or names.

Warning: if some evs are d-separated, they are not included in the Potential.

Returns a Potential for P(targetslevs)

Return type *pyAgrum.Potential* (page 37)

hardEvidenceNodes (*GibbsSampling self*)

Returns the set of nodes with hard evidence

Return type set

hasEvidence (*GibbsSampling self, int id*)

hasEvidence(GibbsSampling self, str nodeName) -> bool

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Returns True if some node(s) (or the one in parameters) have received evidence

Return type bool

Raises gum.IndexError – If the node does not belong to the Bayesian network

hasHardEvidence (*GibbsSampling self, str nodeName*)

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Returns True if node has received a hard evidence

Return type bool

Raises gum.IndexError – If the node does not belong to the Bayesian network

hasSoftEvidence (*GibbsSampling self, int id*)

hasSoftEvidence(GibbsSampling self, str nodeName) -> bool

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Returns True if node has received a soft evidence

Return type bool

Raises gum.IndexError – If the node does not belong to the Bayesian network

history (*GibbsSampling self*)

Returns the scheme history

Return type tuple

Raises gum.OperationNotAllowed – If the scheme did not performed or if verbosity is set to false

isDrawnAtRandom (*GibbsSampling self*)

Returns True if variables are drawn at random

Return type bool

isTarget (*GibbsSampling self, int variable*)
isTarget(GibbsSampling self, str nodeName) -> bool

Parameters

- **variable** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Returns True if variable is a (marginal) target

Return type bool

Raises

- gum.IndexError – If the node does not belong to the Bayesian network
- gum.UndefinedElement – If node Id is not in the Bayesian network

makeInference (*GibbsSampling self*)

Perform the heavy computations needed to compute the targets' posteriors

In a Junction tree propagation scheme, for instance, the heavy computations are those of the messages sent in the JT. This is precisely what makeInference should compute. Later, the computations of the posteriors can be done ‘lightly’ by multiplying and projecting those messages.

maxIter (*GibbsSampling self*)

Returns the criterion on number of iterations

Return type int

maxTime (*GibbsSampling self*)

Returns the timeout(in seconds)

Return type double

messageApproximationScheme (*GibbsSampling self*)

Returns the approximation scheme message

Return type str

minEpsilonRate (*GibbsSampling self*)

Returns the value of the minimal epsilon rate

Return type double

nbrDrawnVar (*GibbsSampling self*)

Returns the number of variable drawn at each iteration

Return type int

nbrEvidence (*GibbsSampling self*)

Returns the number of evidence entered into the Bayesian network

Return type int

nbrHardEvidence (*GibbsSampling self*)

Returns the number of hard evidence entered into the Bayesian network

Return type int

nbrIterations (*GibbsSampling self*)

Returns the number of iterations

Return type int

nbrSoftEvidence (*GibbsSampling self*)

Returns the number of soft evidence entered into the Bayesian network

Return type int

nbrTargets (*GibbsSampling self*)

Returns the number of marginal targets

Return type int

periodSize (*GibbsSampling self*)

Returns the number of samples between 2 stopping

Return type int

Raises gum.OutOfLowerBound – If p<1

posterior (*GibbsSampling self, int var*)

posterior(GibbsSampling self, str nodeName) -> Potential

Computes and returns the posterior of a node.

Parameters

- **var** (int) – the node Id of the node for which we need a posterior probability
- **nodeName** (str) – the node name of the node for which we need a posterior probability

Returns a ref to the posterior probability of the node

Return type [pyAgrum.Potential](#) (page 37)

Raises gum.UndefinedElement – If an element of nodes is not in targets

setBurnIn (*GibbsSampling self, int b*)

Parameters **b** (int) – size of burn in on number of iteration

setDrawnAtRandom (*GibbsSampling self, bool _atRandom*)

Parameters **_atRandom** (bool) – indicates if variables should be drawn at random

setEpsilon (*GibbsSampling self, double eps*)

Parameters **eps** (double) – the epsilon we want to use

Raises gum.OutOfLowerBound – If eps<0

setEvidence (*evidces*)

Erase all the evidences and apply addEvidence(key,value) for every pairs in evidces.

Parameters **evidces** (dict) – a dict of evidences

Raises

- gum.InvalidArgument – If one value is not a value for the node
- gum.InvalidArgument – If the size of a value is different from the domain side of the node
- gum.FatalError – If one value is a vector of 0s
- gum.UndefinedElement – If one node does not belong to the Bayesian network

setMaxIter (*GibbsSampling self, int max*)

Parameters **max** (int) – the maximum number of iteration

Raises gum.OutOfLowerBound – If max <= 1

setMaxTime (*GibbsSampling self, double timeout*)

Parameters `timeout` (*double*) – stopping criterion on timeout (in seconds)

Raises `gum.OutOfLowerBound` – If `timeout<=0.0`

setMinEpsilonRate (*GibbsSampling self, double rate*)

Parameters `rate` (*double*) – the minimal epsilon rate

setNbrDrawnVar (*GibbsSampling self, int nbr*)

Parameters `_nbr` (*int*) – the number of variables to be drawn at each iteration

setPeriodSize (*GibbsSampling self, int p*)

Parameters `p` (*int*) – number of samples between 2 stopping

Raises `gum.OutOfLowerBound` – If `p<1`

setTargets (*targets*)

Remove all the targets and add the ones in parameter.

Parameters `targets` (*set*) – a set of targets

Raises `gum.UndefinedElement` – If one target is not in the Bayes net

setVerbosity (*GibbsSampling self, bool v*)

Parameters `v` (*bool*) – verbosity

softEvidenceNodes (*GibbsSampling self*)

Returns the set of nodes with soft evidence

Return type set

targets (*GibbsSampling self*)

Returns the list of marginal targets

Return type list

thisown

The membership flag

updateEvidence (*evidces*)

Apply `chgEvidence(key,value)` for every pairs in evidces (or `addEvidence`).

Parameters `evidces` (*dict*) – a dict of evidences

Raises

- `gum.InvalidArgument` – If one value is not a value for the node
- `gum.InvalidArgument` – If the size of a value is different from the domain side of the node
- `gum.FatalError` – If one value is a vector of 0s
- `gum.UndefinedElement` – If one node does not belong to the Bayesian network

verbosity (*GibbsSampling self*)

Returns True if the verbosity is enabled

Return type bool

1.5.3.2.2 Monte Carlo Sampling

class `pyAgrum.MonteCarloSampling` (*bn: pyAgrum.pyAgrum.IBayesNet*)

Class used for Monte Carlo sampling inference algorithm.

Available ructors: `MonteCarloSampling (bn) -> MonteCarloSampling`

Parameters `bn` (`pyAgrum.BayesNet` (page 43)) – a Bayesian network

BN (*MonteCarloSampling self*)

Returns A ant reference over the IBayesNet referenced by this class.

Return type `pyAgrum.IBayesNet`

Raises `gum.UndefinedElement` – If no Bayes net has been assigned to the inference.

H (*MonteCarloSampling self, int X*)

`H(MonteCarloSampling self, str nodeName) -> double`

Parameters

- `x (int)` – a node Id
- `nodeName (str)` – a node name

Returns the computed Shanon's entropy of a node given the observation

Return type double

addAllTargets (*MonteCarloSampling self*)

Add all the nodes as targets.

addEvidence (*MonteCarloSampling self, int id, int val*)

`addEvidence(MonteCarloSampling self, str nodeName, int val) addEvidence(MonteCarloSampling self, int id, str val) addEvidence(MonteCarloSampling self, str nodeName, str val) addEvidence(MonteCarloSampling self, int id, Vector vals) addEvidence(MonteCarloSampling self, str nodeName, Vector vals)`

Adds a new evidence on a node (might be soft or hard).

Parameters

- `id (int)` – a node Id
- `nodeName (int)` – a node name
- `val – (int)` a node value
- `val – (str)` the label of the node value
- `vals (list)` – a list of values

Raises

- `gum.InvalidArgument` – If the node already has an evidence
- `gum.InvalidArgument` – If val is not a value for the node
- `gum.InvalidArgument` – If the size of vals is different from the domain side of the node
- `gum.FatalError` – If vals is a vector of 0s
- `gum.UndefinedElement` – If the node does not belong to the Bayesian network

addTarget (*MonteCarloSampling self, int target*)

`addTarget(MonteCarloSampling self, str nodeName)`

Add a marginal target to the list of targets.

Parameters

- `target (int)` – a node Id
- `nodeName (str)` – a node name

Raises `gum.UndefinedElement` – If target is not a NodeId in the Bayes net

chgEvidence (*MonteCarloSampling self, int id, int val*)

chgEvidence(MonteCarloSampling self, str nodeName, int val) chgEvidence(MonteCarloSampling self, int id, str val) chgEvidence(MonteCarloSampling self, str nodeName, str val) chgEvidence(MonteCarloSampling self, int id, Vector vals) chgEvidence(MonteCarloSampling self, str nodeName, Vector vals)

Change the value of an already existing evidence on a node (might be soft or hard).

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*int*) – a node name
- **val** – (*int*) a node value
- **val** – (*str*) the label of the node value
- **vals** (*list*) – a list of values

Raises

- gum.InvalidArgument – If the node does not already have an evidence
- gum.InvalidArgument – If val is not a value for the node
- gum.InvalidArgument – If the size of vals is different from the domain side of the node
- gum.FatalError – If vals is a vector of 0s
- gum.UndefinedElement – If the node does not belong to the Bayesian network

currentPosterior (*MonteCarloSampling self, int id*)

currentPosterior(MonteCarloSampling self, str name) -> Potential

Computes and returns the current posterior of a node.

Parameters

- **var** (*int*) – the node Id of the node for which we need a posterior probability
- **nodeName** (*str*) – the node name of the node for which we need a posterior probability

Returns a ref to the current posterior probability of the node

Return type *pyAgrum.Potential* (page 37)

Raises *UndefinedElement* (page 163) – If an element of nodes is not in targets

currentTime (*MonteCarloSampling self*)

Returns get the current running time in second (double)

Return type double

epsilon (*MonteCarloSampling self*)

Returns the value of epsilon

Return type double

eraseAllEvidence (*MonteCarloSampling self*)

Removes all the evidence entered into the network.

eraseAllTargets (*MonteCarloSampling self*)

Clear all previously defined targets (marginal and joint targets).

As a result, no posterior can be computed (since we can only compute the posteriors of the marginal or joint targets that have been added by the user).

eraseEvidence (*MonteCarloSampling self, int id*)
eraseEvidence(*MonteCarloSampling self, str nodeName*)

Remove the evidence, if any, corresponding to the node Id or name.

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*int*) – a node name

Raises `gum.IndexError` – If the node does not belong to the Bayesian network

eraseTarget (*MonteCarloSampling self, int target*)
eraseTarget(*MonteCarloSampling self, str nodeName*)

Remove, if existing, the marginal target.

Parameters

- **target** (*int*) – a node Id
- **nodeName** (*int*) – a node name

Raises

- `gum.IndexError` – If one of the node does not belong to the Bayesian network
- `gum.UndefinedElement` – If node Id is not in the Bayesian network

evidenceImpact (*MonteCarloSampling self, int target, PyObject * evs*)
evidenceImpact(*MonteCarloSampling self, str target, Vector_string evs*) -> Potential

Create a pyAgrum.Potential for P(target|levs) (for all instantiation of target and evs)

Parameters

- **target** (*set*) – a set of targets ids or names.
- **evs** (*set*) – a set of nodes ids or names.

Warning: if some evs are d-separated, they are not included in the Potential.

Returns a Potential for P(targets|levs)

Return type `pyAgrum.Potential` (page 37)

hardEvidenceNodes (*MonteCarloSampling self*)

Returns the set of nodes with hard evidence

Return type set

hasEvidence (*MonteCarloSampling self, int id*)
hasEvidence(*MonteCarloSampling self, str nodeName*) -> bool

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Returns True if some node(s) (or the one in parameters) have received evidence

Return type bool

Raises `gum.IndexError` – If the node does not belong to the Bayesian network

hasHardEvidence (*MonteCarloSampling self, str nodeName*)

Parameters

- **id**(*int*) – a node Id
- **nodeName**(*str*) – a node name

Returns True if node has received a hard evidence

Return type bool

Raises gum.IndexError – If the node does not belong to the Bayesian network

hasSoftEvidence(*MonteCarloSampling self, int id*)

hasSoftEvidence(*MonteCarloSampling self, str nodeName*) -> bool

Parameters

- **id**(*int*) – a node Id
- **nodeName**(*str*) – a node name

Returns True if node has received a soft evidence

Return type bool

Raises gum.IndexError – If the node does not belong to the Bayesian network

history(*MonteCarloSampling self*)

Returns the scheme history

Return type tuple

Raises gum.OperationNotAllowed – If the scheme did not performed or if verbosity is set to false

isTarget(*MonteCarloSampling self, int variable*)

isTarget(*MonteCarloSampling self, str nodeName*) -> bool

Parameters

- **variable**(*int*) – a node Id
- **nodeName**(*str*) – a node name

Returns True if variable is a (marginal) target

Return type bool

Raises

- gum.IndexError – If the node does not belong to the Bayesian network
- gum.UndefinedElement – If node Id is not in the Bayesian network

makeInference(*MonteCarloSampling self*)

Perform the heavy computations needed to compute the targets' posteriors

In a Junction tree propagation scheme, for instance, the heavy computations are those of the messages sent in the JT. This is precisely what makeInference should compute. Later, the computations of the posteriors can be done ‘lightly’ by multiplying and projecting those messages.

maxIter(*MonteCarloSampling self*)

Returns the criterion on number of iterations

Return type int

maxTime(*MonteCarloSampling self*)

Returns the timeout(in seconds)

Return type double

messageApproximationScheme(*MonteCarloSampling self*)

Returns the approximation scheme message

Return type str

minEpsilonRate (*MonteCarloSampling self*)

Returns the value of the minimal epsilon rate

Return type double

nbrEvidence (*MonteCarloSampling self*)

Returns the number of evidence entered into the Bayesian network

Return type int

nbrHardEvidence (*MonteCarloSampling self*)

Returns the number of hard evidence entered into the Bayesian network

Return type int

nbrIterations (*MonteCarloSampling self*)

Returns the number of iterations

Return type int

nbrSoftEvidence (*MonteCarloSampling self*)

Returns the number of soft evidence entered into the Bayesian network

Return type int

nbrTargets (*MonteCarloSampling self*)

Returns the number of marginal targets

Return type int

periodSize (*MonteCarloSampling self*)

Returns the number of samples between 2 stopping

Return type int

Raises gum.OutOfLowerBound – If p<1

posterior (*MonteCarloSampling self, int var*)

posterior(*MonteCarloSampling self, str nodeName*) -> Potential

Computes and returns the posterior of a node.

Parameters

- **var** (*int*) – the node Id of the node for which we need a posterior probability
- **nodeName** (*str*) – the node name of the node for which we need a posterior probability

Returns a ref to the posterior probability of the node

Return type *pyAgrum.Potential* (page 37)

Raises gum.UndefinedElement – If an element of nodes is not in targets

setEpsilon (*MonteCarloSampling self, double eps*)

Parameters **eps** (*double*) – the epsilon we want to use

Raises gum.OutOfLowerBound – If eps<0

setEvidence (*evidces*)

Erase all the evidences and apply addEvidence(key,value) for every pairs in evidces.

Parameters **evidces** (*dict*) – a dict of evidences

Raises

- gum.InvalidArgument – If one value is not a value for the node
- gum.InvalidArgument – If the size of a value is different from the domain side of the node
- gum.FatalError – If one value is a vector of 0s
- gum.UndefinedElement – If one node does not belong to the Bayesian network

setMaxIter (*MonteCarloSampling self, int max*)

Parameters **max** (*int*) – the maximum number of iteration

Raises gum.OutOfLowerBound – If max <= 1

setMaxTime (*MonteCarloSampling self, double timeout*)

Parameters **timeout** (*double*) – stopping criterion on timeout (in seconds)

Raises gum.OutOfLowerBound – If timeout<=0.0

setMinEpsilonRate (*MonteCarloSampling self, double rate*)

Parameters **rate** (*double*) – the minimal epsilon rate

setPeriodSize (*MonteCarloSampling self, int p*)

Parameters **p** (*int*) – number of samples between 2 stopping

Raises gum.OutOfLowerBound – If p<1

setTargets (*targets*)

Remove all the targets and add the ones in parameter.

Parameters **targets** (*set*) – a set of targets

Raises gum.UndefinedElement – If one target is not in the Bayes net

setVerbosity (*MonteCarloSampling self, bool v*)

Parameters **v** (*bool*) – verbosity

softEvidenceNodes (*MonteCarloSampling self*)

Returns the set of nodes with soft evidence

Return type set

targets (*MonteCarloSampling self*)

Returns the list of marginal targets

Return type list

thisown

The membership flag

updateEvidence (*evidces*)

Apply chgEvidence(key,value) for every pairs in evidces (or addEvidence).

Parameters **evidces** (*dict*) – a dict of evidences

Raises

- gum.InvalidArgument – If one value is not a value for the node
- gum.InvalidArgument – If the size of a value is different from the domain side of the node
- gum.FatalError – If one value is a vector of 0s
- gum.UndefinedElement – If one node does not belong to the Bayesian network

verbosity (*MonteCarloSampling self*)

Returns True if the verbosity is enabled

Return type bool

1.5.3.2.3 Weighted Sampling

class pyAgrum.WeightedSampling (*bn: pyAgrum.pyAgrum.IBayesNet*)

Class used for Weighted sampling inference algorithm.

Available ructors: WeightedSampling (*bn*) -> WeightedSampling

Parameters **bn** ([pyAgrum.BayesNet](#) (page 43)) – a Bayesian network

BN (*WeightedSampling self*)

Returns A ant reference over the IBayesNet referenced by this class.

Return type pyAgrum.IBayesNet

Raises gum.UndefinedElement – If no Bayes net has been assigned to the inference.

H (*WeightedSampling self, int X*)

H(*WeightedSampling self, str nodeName*) -> double

Parameters

- **x** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Returns the computed Shanon's entropy of a node given the observation

Return type double

addAllTargets (*WeightedSampling self*)

Add all the nodes as targets.

addEvidence (*WeightedSampling self, int id, int val*)

addEvidence(*WeightedSampling self, str nodeName, int val*) addEvidence(*WeightedSampling self, int id, str val*) addEvidence(*WeightedSampling self, str nodeName, str val*) addEvidence(*WeightedSampling self, int id, Vector vals*) addEvidence(*WeightedSampling self, str nodeName, Vector vals*)

Adds a new evidence on a node (might be soft or hard).

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*int*) – a node name
- **val** – (*int*) a node value
- **val** – (*str*) the label of the node value
- **vals** (*list*) – a list of values

Raises

- gum.InvalidArgument – If the node already has an evidence
- gum.InvalidArgument – If val is not a value for the node
- gum.InvalidArgument – If the size of vals is different from the domain side of the node
- gum.FatalError – If vals is a vector of 0s
- gum.UndefinedElement – If the node does not belong to the Bayesian network

addTarget (*WeightedSampling self, int target*)
 addTarget(*WeightedSampling self, str nodeName*)

Add a marginal target to the list of targets.

Parameters

- **target** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Raises `gum.UndefinedElement` – If target is not a NodeId in the Bayes net

chgEvidence (*WeightedSampling self, int id, int val*)
 chgEvidence(*WeightedSampling self, str nodeName, int val*) chgEvidence(*WeightedSampling self, int id, str val*) chgEvidence(*WeightedSampling self, str nodeName, str val*) chgEvidence(*WeightedSampling self, int id, Vector vals*) chgEvidence(*WeightedSampling self, str nodeName, Vector vals*)

Change the value of an already existing evidence on a node (might be soft or hard).

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*int*) – a node name
- **val** – (*int*) a node value
- **val** – (*str*) the label of the node value
- **vals** (*list*) – a list of values

Raises

- `gum.InvalidArgument` – If the node does not already have an evidence
- `gum.InvalidArgument` – If val is not a value for the node
- `gum.InvalidArgument` – If the size of vals is different from the domain side of the node
- `gum.FatalError` – If vals is a vector of 0s
- `gum.UndefinedElement` – If the node does not belong to the Bayesian network

currentPosterior (*WeightedSampling self, int id*)
 currentPosterior(*WeightedSampling self, str name*) -> Potential

Computes and returns the current posterior of a node.

Parameters

- **var** (*int*) – the node Id of the node for which we need a posterior probability
- **nodeName** (*str*) – the node name of the node for which we need a posterior probability

Returns a ref to the current posterior probability of the node

Return type `pyAgrum.Potential` (page 37)

Raises `UndefinedElement` (page 163) – If an element of nodes is not in targets

currentTime (*WeightedSampling self*)

Returns get the current running time in second (double)

Return type double

epsilon (*WeightedSampling self*)

Returns the value of epsilon

Return type double

eraseAllEvidence (*WeightedSampling self*)

Removes all the evidence entered into the network.

eraseAllTargets (*WeightedSampling self*)

Clear all previously defined targets (marginal and joint targets).

As a result, no posterior can be computed (since we can only compute the posteriors of the marginal or joint targets that have been added by the user).

eraseEvidence (*WeightedSampling self, int id*)

eraseEvidence(*WeightedSampling self, str nodeName*)

Remove the evidence, if any, corresponding to the node Id or name.

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*int*) – a node name

Raises `gum.IndexError` – If the node does not belong to the Bayesian network

eraseTarget (*WeightedSampling self, int target*)

eraseTarget(*WeightedSampling self, str nodeName*)

Remove, if existing, the marginal target.

Parameters

- **target** (*int*) – a node Id
- **nodeName** (*int*) – a node name

Raises

- `gum.IndexError` – If one of the node does not belong to the Bayesian network
- `gum.UndefinedElement` – If node Id is not in the Bayesian network

evidenceImpact (*WeightedSampling self, int target, PyObject * evs*)

evidenceImpact(*WeightedSampling self, str target, Vector_string evs*) -> Potential

Create a pyAgrum.Potential for P(targetlevs) (for all instantiation of target and evs)

Parameters

- **target** (*set*) – a set of targets ids or names.
- **evs** (*set*) – a set of nodes ids or names.

Warning: if some evs are d-separated, they are not included in the Potential.

Returns a Potential for P(targetslevs)

Return type [pyAgrum.Potential](#) (page 37)

hardEvidenceNodes (*WeightedSampling self*)

Returns the set of nodes with hard evidence

Return type set

hasEvidence (*WeightedSampling self, int id*)

hasEvidence(*WeightedSampling self, str nodeName*) -> bool

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Returns True if some node(s) (or the one in parameters) have received evidence

Return type bool

Raises gum.IndexError – If the node does not belong to the Bayesian network

hasHardEvidence (*WeightedSampling self, str nodeName*)

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Returns True if node has received a hard evidence

Return type bool

Raises gum.IndexError – If the node does not belong to the Bayesian network

hasSoftEvidence (*WeightedSampling self, int id*)

hasSoftEvidence(*WeightedSampling self, str nodeName*) -> bool

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Returns True if node has received a soft evidence

Return type bool

Raises gum.IndexError – If the node does not belong to the Bayesian network

history (*WeightedSampling self*)

Returns the scheme history

Return type tuple

Raises gum.OperationNotAllowed – If the scheme did not performed or if verbosity is set to false

isTarget (*WeightedSampling self, int variable*)

isTarget(*WeightedSampling self, str nodeName*) -> bool

Parameters

- **variable** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Returns True if variable is a (marginal) target

Return type bool

Raises

- gum.IndexError – If the node does not belong to the Bayesian network
- gum.UndefinedElement – If node Id is not in the Bayesian network

makeInference (*WeightedSampling self*)

Perform the heavy computations needed to compute the targets' posteriors

In a Junction tree propagation scheme, for instance, the heavy computations are those of the messages sent in the JT. This is precisely what makeInference should compute. Later, the computations of the posteriors can be done ‘lightly’ by multiplying and projecting those messages.

maxIter (*WeightedSampling self*)

Returns the criterion on number of iterations

Return type int

maxTime (*WeightedSampling self*)
 Returns the timeout(in seconds)
 Return type double

messageApproximationScheme (*WeightedSampling self*)
 Returns the approximation scheme message
 Return type str

minEpsilonRate (*WeightedSampling self*)
 Returns the value of the minimal epsilon rate
 Return type double

nbrEvidence (*WeightedSampling self*)
 Returns the number of evidence entered into the Bayesian network
 Return type int

nbrHardEvidence (*WeightedSampling self*)
 Returns the number of hard evidence entered into the Bayesian network
 Return type int

nbrIterations (*WeightedSampling self*)
 Returns the number of iterations
 Return type int

nbrSoftEvidence (*WeightedSampling self*)
 Returns the number of soft evidence entered into the Bayesian network
 Return type int

nbrTargets (*WeightedSampling self*)
 Returns the number of marginal targets
 Return type int

periodSize (*WeightedSampling self*)
 Returns the number of samples between 2 stopping
 Return type int
 Raises gum.OutOfLowerBound – If p<1

posterior (*WeightedSampling self, int var*)
 posterior(*WeightedSampling self, str nodeName*) -> Potential
 Computes and returns the posterior of a node.

Parameters

- **var** (*int*) – the node Id of the node for which we need a posterior probability
- **nodeName** (*str*) – the node name of the node for which we need a posterior probability

Returns a ref to the posterior probability of the node
 Return type *pyAgrum.Potential* (page 37)
 Raises gum.UndefinedElement – If an element of nodes is not in targets

setEpsilon (*WeightedSampling self, double eps*)
 Parameters **eps** (*double*) – the epsilon we want to use

Raises gum.OutOfLowerBound – If $\text{eps} < 0$

setEvidence (*evidces*)
 Erase all the evidences and apply addEvidence(key,value) for every pairs in evidces.

Parameters **evidces** (*dict*) – a dict of evidences

Raises

- gum.InvalidArgument – If one value is not a value for the node
- gum.InvalidArgument – If the size of a value is different from the domain side of the node
- gum.FatalError – If one value is a vector of 0s
- gum.UndefinedElement – If one node does not belong to the Bayesian network

setMaxIter (*WeightedSampling self, int max*)
Parameters **max** (*int*) – the maximum number of iteration
Raises gum.OutOfLowerBound – If $\text{max} \leq 1$

setMaxTime (*WeightedSampling self, double timeout*)
Parameters **timeout** (*double*) – stopping criterion on timeout (in seconds)
Raises gum.OutOfLowerBound – If $\text{timeout} \leq 0.0$

setMinEpsilonRate (*WeightedSampling self, double rate*)
Parameters **rate** (*double*) – the minimal epsilon rate

setPeriodSize (*WeightedSampling self, int p*)
Parameters **p** (*int*) – number of samples between 2 stopping
Raises gum.OutOfLowerBound – If $\text{p} < 1$

setTargets (*targets*)
 Remove all the targets and add the ones in parameter.

Parameters **targets** (*set*) – a set of targets
Raises gum.UndefinedElement – If one target is not in the Bayes net

setVerbosity (*WeightedSampling self, bool v*)
Parameters **v** (*bool*) – verbosity

softEvidenceNodes (*WeightedSampling self*)
Returns the set of nodes with soft evidence
Return type set

targets (*WeightedSampling self*)
Returns the list of marginal targets
Return type list

thisown
 The membership flag

updateEvidence (*evidces*)
 Apply chgEvidence(key,value) for every pairs in evidces (or addEvidence).

Parameters **evidces** (*dict*) – a dict of evidences
Raises

- gum.InvalidArgument – If one value is not a value for the node

- gum.InvalidArgument – If the size of a value is different from the domain side of the node
- gum.FatalError – If one value is a vector of 0s
- gum.UndefinedElement – If one node does not belong to the Bayesian network

verbosity (*WeightedSampling self*)

Returns True if the verbosity is enabled

Return type bool

1.5.3.2.4 Importance Sampling

class pyAgrum.ImportanceSampling (*bn: pyAgrum.pyAgrum.IBayesNet*)

Class used for inferences using the Importance Sampling algorithm.

Available ructors: ImportanceSampling (*bn*) -> ImportanceSampling

Parameters **bn** ([pyAgrum.BayesNet](#) (page 43)) – a Bayesian network

BN (*ImportanceSampling self*)

Returns A ant reference over the IBayesNet referenced by this class.

Return type pyAgrum.IBayesNet

Raises gum.UndefinedElement – If no Bayes net has been assigned to the inference.

H (*ImportanceSampling self, int X*)

H(ImportanceSampling self, str nodeName) -> double

Parameters

- **x** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Returns the computed Shanon's entropy of a node given the observation

Return type double

addAllTargets (*ImportanceSampling self*)

Add all the nodes as targets.

addEvidence (*ImportanceSampling self, int id, int val*)

addEvidence(ImportanceSampling self, str nodeName, int val) addEvidence(ImportanceSampling self, int id, str val) addEvidence(ImportanceSampling self, str nodeName, str val) addEvidence(ImportanceSampling self, int id, Vector vals) addEvidence(ImportanceSampling self, str nodeName, Vector vals)

Adds a new evidence on a node (might be soft or hard).

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*int*) – a node name
- **val** – (int) a node value
- **val** – (str) the label of the node value
- **vals** (*list*) – a list of values

Raises

- gum.InvalidArgument – If the node already has an evidence
- gum.InvalidArgument – If val is not a value for the node

- gum.InvalidArgument – If the size of vals is different from the domain side of the node
- gum.FatalError – If vals is a vector of 0s
- gum.UndefinedElement – If the node does not belong to the Bayesian network

addTarget (*ImportanceSampling self, int target*)
 addTarget(*ImportanceSampling self, str nodeName*)

Add a marginal target to the list of targets.

Parameters

- **target** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Raises gum.UndefinedElement – If target is not a NodeId in the Bayes net

chgEvidence (*ImportanceSampling self, int id, int val*)

chgEvidence(*ImportanceSampling self, str nodeName, int val*) chgEvidence(*ImportanceSampling self, int id, str val*) chgEvidence(*ImportanceSampling self, str nodeName, str val*) chgEvidence(*ImportanceSampling self, int id, Vector vals*) chgEvidence(*ImportanceSampling self, str nodeName, Vector vals*)

Change the value of an already existing evidence on a node (might be soft or hard).

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*int*) – a node name
- **val** – (*int*) a node value
- **val** – (*str*) the label of the node value
- **vals** (*list*) – a list of values

Raises

- gum.InvalidArgument – If the node does not already have an evidence
- gum.InvalidArgument – If val is not a value for the node
- gum.InvalidArgument – If the size of vals is different from the domain side of the node
- gum.FatalError – If vals is a vector of 0s
- gum.UndefinedElement – If the node does not belong to the Bayesian network

currentPosterior (*ImportanceSampling self, int id*)

currentPosterior(*ImportanceSampling self, str name*) -> Potential

Computes and returns the current posterior of a node.

Parameters

- **var** (*int*) – the node Id of the node for which we need a posterior probability
- **nodeName** (*str*) – the node name of the node for which we need a posterior probability

Returns a ref to the current posterior probability of the node

Return type *pyAgrum.Potential* (page 37)

Raises *UndefinedElement* (page 163) – If an element of nodes is not in targets

currentTime (*ImportanceSampling self*)

Returns get the current running time in second (double)

Return type double

epsilon (*ImportanceSampling self*)

Returns the value of epsilon

Return type double

eraseAllEvidence (*ImportanceSampling self*)

Removes all the evidence entered into the network.

eraseAllTargets (*ImportanceSampling self*)

Clear all previously defined targets (marginal and joint targets).

As a result, no posterior can be computed (since we can only compute the posteriors of the marginal or joint targets that have been added by the user).

eraseEvidence (*ImportanceSampling self, int id*)

eraseEvidence(*ImportanceSampling self, str nodeName*)

Remove the evidence, if any, corresponding to the node Id or name.

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*int*) – a node name

Raises `gum.IndexError` – If the node does not belong to the Bayesian network

eraseTarget (*ImportanceSampling self, int target*)

eraseTarget(*ImportanceSampling self, str nodeName*)

Remove, if existing, the marginal target.

Parameters

- **target** (*int*) – a node Id
- **nodeName** (*int*) – a node name

Raises

- `gum.IndexError` – If one of the node does not belong to the Bayesian network
- `gum.UndefinedElement` – If node Id is not in the Bayesian network

evidenceImpact (*ImportanceSampling self, int target, PyObject * evs*)

evidenceImpact(*ImportanceSampling self, str target, Vector_string evs*) -> Potential

Create a `pyAgrum.Potential` for $P(\text{target}|\text{levs})$ (for all instantiation of target and evs)

Parameters

- **target** (*set*) – a set of targets ids or names.
- **evs** (*set*) – a set of nodes ids or names.

Warning: if some evs are d-separated, they are not included in the Potential.

Returns a Potential for $P(\text{targets}|\text{levs})$

Return type `pyAgrum.Potential` (page 37)

hardEvidenceNodes (*ImportanceSampling self*)

Returns the set of nodes with hard evidence

Return type set

hasEvidence (*ImportanceSampling self, int id*)
 hasEvidence(ImportanceSampling self, str nodeName) -> bool

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Returns True if some node(s) (or the one in parameters) have received evidence

Return type bool

Raises gum.IndexError – If the node does not belong to the Bayesian network

hasHardEvidence (*ImportanceSampling self, str nodeName*)

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Returns True if node has received a hard evidence

Return type bool

Raises gum.IndexError – If the node does not belong to the Bayesian network

hasSoftEvidence (*ImportanceSampling self, int id*)

hasSoftEvidence(ImportanceSampling self, str nodeName) -> bool

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Returns True if node has received a soft evidence

Return type bool

Raises gum.IndexError – If the node does not belong to the Bayesian network

history (*ImportanceSampling self*)

Returns the scheme history

Return type tuple

Raises gum.OperationNotAllowed – If the scheme did not performed or if verbosity is set to false

isTarget (*ImportanceSampling self, int variable*)

isTarget(ImportanceSampling self, str nodeName) -> bool

Parameters

- **variable** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Returns True if variable is a (marginal) target

Return type bool

Raises

- gum.IndexError – If the node does not belong to the Bayesian network
- gum.UndefinedElement – If node Id is not in the Bayesian network

makeInference (*ImportanceSampling self*)

Perform the heavy computations needed to compute the targets' posteriors

In a Junction tree propagation scheme, for instance, the heavy computations are those of the messages sent in the JT. This is precisely what makeInference should compute. Later, the computations of the posteriors can be done ‘lightly’ by multiplying and projecting those messages.

maxIter (*ImportanceSampling self*)

Returns the criterion on number of iterations

Return type int

maxTime (*ImportanceSampling self*)

Returns the timeout(in seconds)

Return type double

messageApproximationScheme (*ImportanceSampling self*)

Returns the approximation scheme message

Return type str

minEpsilonRate (*ImportanceSampling self*)

Returns the value of the minimal epsilon rate

Return type double

nbrEvidence (*ImportanceSampling self*)

Returns the number of evidence entered into the Bayesian network

Return type int

nbrHardEvidence (*ImportanceSampling self*)

Returns the number of hard evidence entered into the Bayesian network

Return type int

nbrIterations (*ImportanceSampling self*)

Returns the number of iterations

Return type int

nbrSoftEvidence (*ImportanceSampling self*)

Returns the number of soft evidence entered into the Bayesian network

Return type int

nbrTargets (*ImportanceSampling self*)

Returns the number of marginal targets

Return type int

periodSize (*ImportanceSampling self*)

Returns the number of samples between 2 stopping

Return type int

Raises gum.OutOfLowerBound – If p<1

posterior (*ImportanceSampling self, int var*)

posterior(*ImportanceSampling self, str nodeName*) -> Potential

Computes and returns the posterior of a node.

Parameters

- **var** (*int*) – the node Id of the node for which we need a posterior probability
- **nodeName** (*str*) – the node name of the node for which we need a posterior probability

Returns a ref to the posterior probability of the node

Return type *pyAgrum.Potential* (page 37)

Raises *gum.UndefinedElement* – If an element of nodes is not in targets

setEpsilon (*ImportanceSampling self, double eps*)

Parameters **eps** (*double*) – the epsilon we want to use

Raises *gum.OutOfLowerBound* – If *eps*<0

setEvidence (*evidces*)

Erase all the evidences and apply addEvidence(key,value) for every pairs in evidces.

Parameters **evidces** (*dict*) – a dict of evidences

Raises

- *gum.InvalidArgument* – If one value is not a value for the node
- *gum.InvalidArgument* – If the size of a value is different from the domain side of the node
- *gum.FatalError* – If one value is a vector of 0s
- *gum.UndefinedElement* – If one node does not belong to the Bayesian network

setMaxIter (*ImportanceSampling self, int max*)

Parameters **max** (*int*) – the maximum number of iteration

Raises *gum.OutOfLowerBound* – If *max* <= 1

setMaxTime (*ImportanceSampling self, double timeout*)

Parameters **timeout** (*double*) – stopping criterion on timeout (in seconds)

Raises *gum.OutOfLowerBound* – If *timeout*<=0.0

setMinEpsilonRate (*ImportanceSampling self, double rate*)

Parameters **rate** (*double*) – the minimal epsilon rate

setPeriodSize (*ImportanceSampling self, int p*)

Parameters **p** (*int*) – number of samples between 2 stopping

Raises *gum.OutOfLowerBound* – If *p*<1

setTargets (*targets*)

Remove all the targets and add the ones in parameter.

Parameters **targets** (*set*) – a set of targets

Raises *gum.UndefinedElement* – If one target is not in the Bayes net

setVerbosity (*ImportanceSampling self, bool v*)

Parameters **v** (*bool*) – verbosity

softEvidenceNodes (*ImportanceSampling self*)

Returns the set of nodes with soft evidence

Return type set

targets (*ImportanceSampling self*)

Returns the list of marginal targets

Return type list

thisown

The membership flag

updateEvidence (*evidces*)

Apply chgEvidence(key,value) for every pairs in evidces (or addEvidence).

Parameters **evidces** (*dict*) – a dict of evidences

Raises

- gum.InvalidArgument – If one value is not a value for the node
- gum.InvalidArgument – If the size of a value is different from the domain side of the node
- gum.FatalError – If one value is a vector of 0s
- gum.UndefinedElement – If one node does not belong to the Bayesian network

verbosity (*ImportanceSampling self*)

Returns True if the verbosity is enabled

Return type bool

1.5.3.3 Loopy sampling

1.5.3.3.1 Loopy Gibbs Sampling

class pyAgrum.**LoopyGibbsSampling** (*bn*: pyAgrum.pyAgrum.IBayesNet)

Class used for inferences using a loopy version of Gibbs sampling.

Available ructors: LoopyGibbsSampling (*bn*) → LoopyGibbsSampling

Parameters **bn** (pyAgrum.BayesNet (page 43)) – a Bayesian network

BN (*LoopyGibbsSampling self*)

Returns A ant reference over the IBayesNet referenced by this class.

Return type pyAgrum.IBayesNet

Raises gum.UndefinedElement – If no Bayes net has been assigned to the inference.

H (*LoopyGibbsSampling self, int X*)

H(LoopyGibbsSampling self, str nodeName) -> double

Parameters

- **X** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Returns the computed Shanon's entropy of a node given the observation

Return type double

addAllTargets (*LoopyGibbsSampling self*)

Add all the nodes as targets.

addEvidence (*LoopyGibbsSampling self, int id, int val*)

addEvidence(LoopyGibbsSampling self, str nodeName, int val) addEvidence(LoopyGibbsSampling self, int id, str val) addEvidence(LoopyGibbsSampling self, str nodeName, str val) addEvidence(LoopyGibbsSampling self, int id, Vector vals) addEvidence(LoopyGibbsSampling self, str nodeName, Vector vals)

Adds a new evidence on a node (might be soft or hard).

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*int*) – a node name
- **val** – (*int*) a node value
- **val** – (*str*) the label of the node value
- **vals** (*list*) – a list of values

Raises

- gum.InvalidArgument – If the node already has an evidence
- gum.InvalidArgument – If val is not a value for the node
- gum.InvalidArgument – If the size of vals is different from the domain side of the node
- gum.FatalError – If vals is a vector of 0s
- gum.UndefinedElement – If the node does not belong to the Bayesian network

addTarget (*LoopyGibbsSampling self, int target*)
 addTarget(*LoopyGibbsSampling self, str nodeName*)

Add a marginal target to the list of targets.

Parameters

- **target** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Raises gum.UndefinedElement – If target is not a NodeId in the Bayes net

burnIn (*LoopyGibbsSampling self*)

Returns size of burn in on number of iteration

Return type int

chgEvidence (*LoopyGibbsSampling self, int id, int val*)

chgEvidence(*LoopyGibbsSampling self, str nodeName, int val*) chgEvidence(*LoopyGibbsSampling self, int id, str val*) chgEvidence(*LoopyGibbsSampling self, str nodeName, str val*) chgEvidence(*LoopyGibbsSampling self, int id, Vector vals*) chgEvidence(*LoopyGibbsSampling self, str nodeName, Vector vals*)

Change the value of an already existing evidence on a node (might be soft or hard).

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*int*) – a node name
- **val** – (*int*) a node value
- **val** – (*str*) the label of the node value
- **vals** (*list*) – a list of values

Raises

- gum.InvalidArgument – If the node does not already have an evidence
- gum.InvalidArgument – If val is not a value for the node
- gum.InvalidArgument – If the size of vals is different from the domain side of the node
- gum.FatalError – If vals is a vector of 0s

- `gum.UndefinedElement` – If the node does not belong to the Bayesian network

currentPosterior (*LoopyGibbsSampling self, int id*)
`currentPosterior(LoopyGibbsSampling self, str name)` -> Potential

Computes and returns the current posterior of a node.

Parameters

- **var** (*int*) – the node Id of the node for which we need a posterior probability
- **nodeName** (*str*) – the node name of the node for which we need a posterior probability

Returns a ref to the current posterior probability of the node

Return type `pyAgrum.Potential` (page 37)

Raises `UndefinedElement` (page 163) – If an element of nodes is not in targets

currentTime (*LoopyGibbsSampling self*)

Returns get the current running time in second (double)

Return type double

epsilon (*LoopyGibbsSampling self*)

Returns the value of epsilon

Return type double

eraseAllEvidence (*LoopyGibbsSampling self*)

Removes all the evidence entered into the network.

eraseAllTargets (*LoopyGibbsSampling self*)

Clear all previously defined targets (marginal and joint targets).

As a result, no posterior can be computed (since we can only compute the posteriors of the marginal or joint targets that have been added by the user).

eraseEvidence (*LoopyGibbsSampling self, int id*)

`eraseEvidence(LoopyGibbsSampling self, str nodeName)`

Remove the evidence, if any, corresponding to the node Id or name.

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*int*) – a node name

Raises `gum.IndexError` – If the node does not belong to the Bayesian network

eraseTarget (*LoopyGibbsSampling self, int target*)

`eraseTarget(LoopyGibbsSampling self, str nodeName)`

Remove, if existing, the marginal target.

Parameters

- **target** (*int*) – a node Id
- **nodeName** (*int*) – a node name

Raises

- `gum.IndexError` – If one of the node does not belong to the Bayesian network
- `gum.UndefinedElement` – If node Id is not in the Bayesian network

evidenceImpact (*LoopyGibbsSampling self, int target, PyObject * evs*)

`evidenceImpact(LoopyGibbsSampling self, str target, Vector_string evs)` -> Potential

Create a `pyAgrum.Potential` for $P(\text{target}|\text{levs})$ (for all instantiation of target and evs)

Parameters

- **target** (*set*) – a set of targets ids or names.
- **evs** (*set*) – a set of nodes ids or names.

Warning: if some evs are d-separated, they are not included in the Potential.

Returns a Potential for $P(\text{targets}|\text{levs})$

Return type *pyAgrum.Potential* (page 37)

hardEvidenceNodes (*LoopyGibbsSampling self*)

Returns the set of nodes with hard evidence

Return type set

hasEvidence (*LoopyGibbsSampling self, int id*)

hasEvidence(*LoopyGibbsSampling self, str nodeName*) -> bool

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Returns True if some node(s) (or the one in parameters) have received evidence

Return type bool

Raises `gum.IndexError` – If the node does not belong to the Bayesian network

hasHardEvidence (*LoopyGibbsSampling self, str nodeName*)

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Returns True if node has received a hard evidence

Return type bool

Raises `gum.IndexError` – If the node does not belong to the Bayesian network

hasSoftEvidence (*LoopyGibbsSampling self, int id*)

hasSoftEvidence(*LoopyGibbsSampling self, str nodeName*) -> bool

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Returns True if node has received a soft evidence

Return type bool

Raises `gum.IndexError` – If the node does not belong to the Bayesian network

history (*LoopyGibbsSampling self*)

Returns the scheme history

Return type tuple

Raises `gum.OperationNotAllowed` – If the scheme did not performed or if verbosity is set to false

isDrawnAtRandom (*LoopyGibbsSampling self*)

Returns True if variables are drawn at random

Return type bool

isTarget (*LoopyGibbsSampling self*, *int variable*)
isTarget(LoopyGibbsSampling self, str nodeName) -> bool

Parameters

- **variable** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Returns True if variable is a (marginal) target

Return type bool

Raises

- `gum.IndexError` – If the node does not belong to the Bayesian network
- `gum.UndefinedElement` – If node Id is not in the Bayesian network

makeInference (*LoopyGibbsSampling self*)

Perform the heavy computations needed to compute the targets' posteriors

In a Junction tree propagation scheme, for instance, the heavy computations are those of the messages sent in the JT. This is precisely what makeInference should compute. Later, the computations of the posteriors can be done ‘lightly’ by multiplying and projecting those messages.

maxIter (*LoopyGibbsSampling self*)

Returns the criterion on number of iterations

Return type int

maxTime (*LoopyGibbsSampling self*)

Returns the timeout(in seconds)

Return type double

messageApproximationScheme (*LoopyGibbsSampling self*)

Returns the approximation scheme message

Return type str

minEpsilonRate (*LoopyGibbsSampling self*)

Returns the value of the minimal epsilon rate

Return type double

nbrDrawnVar (*LoopyGibbsSampling self*)

Returns the number of variable drawn at each iteration

Return type int

nbrEvidence (*LoopyGibbsSampling self*)

Returns the number of evidence entered into the Bayesian network

Return type int

nbrHardEvidence (*LoopyGibbsSampling self*)

Returns the number of hard evidence entered into the Bayesian network

Return type int

nbrIterations (*LoopyGibbsSampling self*)

Returns the number of iterations

Return type int

nbrSoftEvidence (*LoopyGibbsSampling self*)

Returns the number of soft evidence entered into the Bayesian network

Return type int

nbrTargets (*LoopyGibbsSampling self*)

Returns the number of marginal targets

Return type int

periodSize (*LoopyGibbsSampling self*)

Returns the number of samples between 2 stopping

Return type int

Raises gum.OutOfLowerBound – If p<1

posterior (*LoopyGibbsSampling self, int var*)
posterior(*LoopyGibbsSampling self, str nodeName*) -> Potential

Computes and returns the posterior of a node.

Parameters

- **var** (*int*) – the node Id of the node for which we need a posterior probability
- **nodeName** (*str*) – the node name of the node for which we need a posterior probability

Returns a ref to the posterior probability of the node

Return type *pyAgrum.Potential* (page 37)

Raises gum.UndefinedElement – If an element of nodes is not in targets

setBurnIn (*LoopyGibbsSampling self, int b*)

Parameters **b** (*int*) – size of burn in on number of iteration

setDrawnAtRandom (*LoopyGibbsSampling self, bool _atRandom*)

Parameters **_atRandom** (*bool*) – indicates if variables should be drawn at random

setEpsilon (*LoopyGibbsSampling self, double eps*)

Parameters **eps** (*double*) – the epsilon we want to use

Raises gum.OutOfLowerBound – If eps<0

setEvidence (*evidces*)
Erase all the evidences and apply addEvidence(key,value) for every pairs in evidces.

Parameters **evidces** (*dict*) – a dict of evidences

Raises

- gum.InvalidArgument – If one value is not a value for the node
- gum.InvalidArgument – If the size of a value is different from the domain side of the node
- gum.FatalError – If one value is a vector of 0s
- gum.UndefinedElement – If one node does not belong to the Bayesian network

setMaxIter (*LoopyGibbsSampling self, int max*)

Parameters **max** (*int*) – the maximum number of iteration

Raises gum.OutOfLowerBound – If max <= 1

setMaxTime (*LoopyGibbsSampling self, double timeout*)
 Parameters **timeout** (*double*) – stopping criterion on timeout (in seconds)
 Raises `gum.OutOfLowerBound` – If `timeout<=0.0`

setMinEpsilonRate (*LoopyGibbsSampling self, double rate*)
 Parameters **rate** (*double*) – the minimal epsilon rate

setNbrDrawnVar (*LoopyGibbsSampling self, int _nbr*)
 Parameters **_nbr** (*int*) – the number of variables to be drawn at each iteration

setPeriodSize (*LoopyGibbsSampling self, int p*)
 Parameters **p** (*int*) – number of samples between 2 stopping
 Raises `gum.OutOfLowerBound` – If `p<1`

setTargets (*targets*)
 Returns Remove all the targets and add the ones in parameter.
 Parameters **targets** (*set*) – a set of targets
 Raises `gum.UndefinedElement` – If one target is not in the Bayes net

setVerbosity (*LoopyGibbsSampling self, bool v*)
 Parameters **v** (*bool*) – verbosity

setVirtualLBPSize (*LoopyGibbsSampling self, double vlpysize*)
 Parameters **vlpysize** (*double*) – the size of the virtual LBP

softEvidenceNodes (*LoopyGibbsSampling self*)
 Returns the set of nodes with soft evidence
 Return type set

targets (*LoopyGibbsSampling self*)
 Returns the list of marginal targets
 Return type list

thisown
 The membership flag

updateEvidence (*evidces*)
 Apply `chgEvidence(key,value)` for every pairs in evidces (or `addEvidence`).
 Parameters **evidces** (*dict*) – a dict of evidences
 Raises

- `gum.InvalidArgument` – If one value is not a value for the node
- `gum.InvalidArgument` – If the size of a value is different from the domain side of the node
- `gum.FatalError` – If one value is a vector of 0s
- `gum.UndefinedElement` – If one node does not belong to the Bayesian network

verbosity (*LoopyGibbsSampling self*)
 Returns True if the verbosity is enabled
 Return type bool

1.5.3.3.2 Loopy Monte Carlo Sampling

class pyAgrum.**LoopyMonteCarloSampling** (*bn*: pyAgrum.pyAgrum.IBayesNet)
 Proxy of C++ pyAgrum.LoopySamplingInference<double,pyAgrum.MonteCarloSampling> class.

BN (*LoopyMonteCarloSampling self*)

Returns A ant reference over the IBayesNet referenced by this class.

Return type pyAgrum.IBayesNet

Raises gum.UndefinedElement – If no Bayes net has been assigned to the inference.

H (*LoopyMonteCarloSampling self, int X*)

H(*LoopyMonteCarloSampling self, str nodeName*) -> double

Parameters

- **x** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Returns the computed Shanon's entropy of a node given the observation

Return type double

addAllTargets (*LoopyMonteCarloSampling self*)

Add all the nodes as targets.

addEvidence (*LoopyMonteCarloSampling self, int id, int val*)

addEvidence(*LoopyMonteCarloSampling self, str nodeName, int val*) addEvidence(*LoopyMonteCarloSampling self, int id, str val*) addEvidence(*LoopyMonteCarloSampling self, str nodeName, str val*) addEvidence(*LoopyMonteCarloSampling self, int id, Vector vals*) addEvidence(*LoopyMonteCarloSampling self, str nodeName, Vector vals*)

Adds a new evidence on a node (might be soft or hard).

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*int*) – a node name
- **val** – (int) a node value
- **val** – (str) the label of the node value
- **vals** (*list*) – a list of values

Raises

- gum.InvalidArgument – If the node already has an evidence
- gum.InvalidArgument – If val is not a value for the node
- gum.InvalidArgument – If the size of vals is different from the domain side of the node
- gum.FatalError – If vals is a vector of 0s
- gum.UndefinedElement – If the node does not belong to the Bayesian network

addTarget (*LoopyMonteCarloSampling self, int target*)

addTarget(*LoopyMonteCarloSampling self, str nodeName*)

Add a marginal target to the list of targets.

Parameters

- **target** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Raises `gum.UndefinedElement` – If target is not a NodeId in the Bayes net

chgEvidence (*LoopyMonteCarloSampling self, int id, int val*)

```
chgEvidence(LoopyMonteCarloSampling self, str nodeName, int val) chgEvidence(LoopyMonteCarloSampling self, int id, str val) chgEvidence(LoopyMonteCarloSampling self, str nodeName, str val) chgEvidence(LoopyMonteCarloSampling self, int id, Vector vals)
chgEvidence(LoopyMonteCarloSampling self, str nodeName, Vector vals)
```

Change the value of an already existing evidence on a node (might be soft or hard).

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*int*) – a node name
- **val** – (*int*) a node value
- **val** – (*str*) the label of the node value
- **vals** (*list*) – a list of values

Raises

- `gum.InvalidArgument` – If the node does not already have an evidence
- `gum.InvalidArgument` – If val is not a value for the node
- `gum.InvalidArgument` – If the size of vals is different from the domain side of the node
- `gum.FatalError` – If vals is a vector of 0s
- `gum.UndefinedElement` – If the node does not belong to the Bayesian network

currentPosterior (*LoopyMonteCarloSampling self, int id*)

`currentPosterior(LoopyMonteCarloSampling self, str name) -> Potential`

Computes and returns the current posterior of a node.

Parameters

- **var** (*int*) – the node Id of the node for which we need a posterior probability
- **nodeName** (*str*) – the node name of the node for which we need a posterior probability

Returns a ref to the current posterior probability of the node

Return type `pyAgrum.Potential` (page 37)

Raises `UndefinedElement` (page 163) – If an element of nodes is not in targets

currentTime (*LoopyMonteCarloSampling self*)

Returns get the current running time in second (double)

Return type double

epsilon (*LoopyMonteCarloSampling self*)

Returns the value of epsilon

Return type double

eraseAllEvidence (*LoopyMonteCarloSampling self*)

Removes all the evidence entered into the network.

eraseAllTargets (*LoopyMonteCarloSampling self*)

Clear all previously defined targets (marginal and joint targets).

As a result, no posterior can be computed (since we can only compute the posteriors of the marginal or joint targets that have been added by the user).

eraseEvidence (*LoopyMonteCarloSampling self, int id*)
 eraseEvidence(*LoopyMonteCarloSampling self, str nodeName*)
 Remove the evidence, if any, corresponding to the node Id or name.

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*int*) – a node name

Raises `gum.IndexError` – If the node does not belong to the Bayesian network

eraseTarget (*LoopyMonteCarloSampling self, int target*)
 eraseTarget(*LoopyMonteCarloSampling self, str nodeName*)
 Remove, if existing, the marginal target.

Parameters

- **target** (*int*) – a node Id
- **nodeName** (*int*) – a node name

Raises

- `gum.IndexError` – If one of the node does not belong to the Bayesian network
- `gum.UndefinedElement` – If node Id is not in the Bayesian network

evidenceImpact (*LoopyMonteCarloSampling self, int target, PyObject * evs*)
 evidenceImpact(*LoopyMonteCarloSampling self, str target, Vector_string evs*) -> `Potential`
 Create a pyAgrum.Potential for $P(\text{target}|\text{levs})$ (for all instantiation of target and evs)

Parameters

- **target** (*set*) – a set of targets ids or names.
- **evs** (*set*) – a set of nodes ids or names.

Warning: if some evs are d-separated, they are not included in the Potential.

Returns a Potential for $P(\text{targets}|\text{levs})$

Return type `pyAgrum.Potential` (page 37)

hardEvidenceNodes (*LoopyMonteCarloSampling self*)

Returns the set of nodes with hard evidence

Return type `set`

hasEvidence (*LoopyMonteCarloSampling self, int id*)
 hasEvidence(*LoopyMonteCarloSampling self, str nodeName*) -> `bool`

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Returns True if some node(s) (or the one in parameters) have received evidence

Return type `bool`

Raises `gum.IndexError` – If the node does not belong to the Bayesian network

hasHardEvidence (*LoopyMonteCarloSampling self, str nodeName*)

Parameters

- **id**(*int*) – a node Id
- **nodeName**(*str*) – a node name

Returns True if node has received a hard evidence

Return type bool

Raises gum.IndexError – If the node does not belong to the Bayesian network

hasSoftEvidence(*LoopyMonteCarloSampling self, int id*)

hasSoftEvidence(*LoopyMonteCarloSampling self, str nodeName*) -> bool

Parameters

- **id**(*int*) – a node Id
- **nodeName**(*str*) – a node name

Returns True if node has received a soft evidence

Return type bool

Raises gum.IndexError – If the node does not belong to the Bayesian network

history(*LoopyMonteCarloSampling self*)

Returns the scheme history

Return type tuple

Raises gum.OperationNotAllowed – If the scheme did not performed or if verbosity is set to false

isTarget(*LoopyMonteCarloSampling self, int variable*)

isTarget(*LoopyMonteCarloSampling self, str nodeName*) -> bool

Parameters

- **variable**(*int*) – a node Id
- **nodeName**(*str*) – a node name

Returns True if variable is a (marginal) target

Return type bool

Raises

- gum.IndexError – If the node does not belong to the Bayesian network
- gum.UndefinedElement – If node Id is not in the Bayesian network

makeInference(*LoopyMonteCarloSampling self*)

Perform the heavy computations needed to compute the targets' posteriors

In a Junction tree propagation scheme, for instance, the heavy computations are those of the messages sent in the JT. This is precisely what makeInference should compute. Later, the computations of the posteriors can be done ‘lightly’ by multiplying and projecting those messages.

maxIter(*LoopyMonteCarloSampling self*)

Returns the criterion on number of iterations

Return type int

maxTime(*LoopyMonteCarloSampling self*)

Returns the timeout(in seconds)

Return type double

messageApproximationScheme(*LoopyMonteCarloSampling self*)

Returns the approximation scheme message

Return type str

minEpsilonRate (*LoopyMonteCarloSampling self*)

Returns the value of the minimal epsilon rate

Return type double

nbrEvidence (*LoopyMonteCarloSampling self*)

Returns the number of evidence entered into the Bayesian network

Return type int

nbrHardEvidence (*LoopyMonteCarloSampling self*)

Returns the number of hard evidence entered into the Bayesian network

Return type int

nbrIterations (*LoopyMonteCarloSampling self*)

Returns the number of iterations

Return type int

nbrSoftEvidence (*LoopyMonteCarloSampling self*)

Returns the number of soft evidence entered into the Bayesian network

Return type int

nbrTargets (*LoopyMonteCarloSampling self*)

Returns the number of marginal targets

Return type int

periodSize (*LoopyMonteCarloSampling self*)

Returns the number of samples between 2 stopping

Return type int

Raises gum.OutOfLowerBound – If p<1

posterior (*LoopyMonteCarloSampling self, int var*)

posterior(*LoopyMonteCarloSampling self, str nodeName*) -> Potential

Computes and returns the posterior of a node.

Parameters

- **var** (*int*) – the node Id of the node for which we need a posterior probability
- **nodeName** (*str*) – the node name of the node for which we need a posterior probability

Returns a ref to the posterior probability of the node

Return type *pyAgrum.Potential* (page 37)

Raises gum.UndefinedElement – If an element of nodes is not in targets

setEpsilon (*LoopyMonteCarloSampling self, double eps*)

Parameters **eps** (*double*) – the epsilon we want to use

Raises gum.OutOfLowerBound – If eps<0

setEvidence (*evidces*)

Erase all the evidences and apply addEvidence(key,value) for every pairs in evidces.

Parameters **evidces** (*dict*) – a dict of evidences

Raises

- gum.InvalidArgument – If one value is not a value for the node
- gum.InvalidArgument – If the size of a value is different from the domain side of the node
- gum.FatalError – If one value is a vector of 0s
- gum.UndefinedElement – If one node does not belong to the Bayesian network

setMaxIter (*LoopyMonteCarloSampling self, int max*)

Parameters **max** (*int*) – the maximum number of iteration

Raises gum.OutOfLowerBound – If max <= 1

setMaxTime (*LoopyMonteCarloSampling self, double timeout*)

Parameters **timeout** (*double*) – stopping criterion on timeout (in seconds)

Raises gum.OutOfLowerBound – If timeout<=0.0

setMinEpsilonRate (*LoopyMonteCarloSampling self, double rate*)

Parameters **rate** (*double*) – the minimal epsilon rate

setPeriodSize (*LoopyMonteCarloSampling self, int p*)

Parameters **p** (*int*) – number of samples between 2 stopping

Raises gum.OutOfLowerBound – If p<1

setTargets (*targets*)

Remove all the targets and add the ones in parameter.

Parameters **targets** (*set*) – a set of targets

Raises gum.UndefinedElement – If one target is not in the Bayes net

setVerbosity (*LoopyMonteCarloSampling self, bool v*)

Parameters **v** (*bool*) – verbosity

setVirtualLBPSize (*LoopyMonteCarloSampling self, double vlbpsize*)

Parameters **vlbpsize** (*double*) – the size of the virtual LBP

softEvidenceNodes (*LoopyMonteCarloSampling self*)

Returns the set of nodes with soft evidence

Return type set

targets (*LoopyMonteCarloSampling self*)

Returns the list of marginal targets

Return type list

thisown

The membership flag

updateEvidence (*evidces*)

Apply chgEvidence(key,value) for every pairs in evidces (or addEvidence).

Parameters **evidces** (*dict*) – a dict of evidences

Raises

- gum.InvalidArgument – If one value is not a value for the node
- gum.InvalidArgument – If the size of a value is different from the domain side of the node
- gum.FatalError – If one value is a vector of 0s
- gum.UndefinedElement – If one node does not belong to the Bayesian network

verbosity (*LoopyMonteCarloSampling self*)

Returns True if the verbosity is enabled

Return type bool

1.5.3.3.3 Loopy Weighted Sampling

class pyAgrum.**LoopyWeightedSampling** (*bn: pyAgrum.pyAgrum.IBayesNet*)

Class used for inferences using a loopy version of weighted sampling.

Available ructors: LoopyWeightedSampling (*bn*) -> LoopyWeightedSampling

Parameters **bn** ([pyAgrum.BayesNet](#) (page 43)) – a Bayesian network

BN (*LoopyWeightedSampling self*)

Returns A ant reference over the IBayesNet referenced by this class.

Return type pyAgrum.IBayesNet

Raises gum.UndefinedElement – If no Bayes net has been assigned to the inference.

H (*LoopyWeightedSampling self, int X*)

H(*LoopyWeightedSampling self, str nodeName*) -> double

Parameters

- **x** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Returns the computed Shanon's entropy of a node given the observation

Return type double

addAllTargets (*LoopyWeightedSampling self*)

Add all the nodes as targets.

addEvidence (*LoopyWeightedSampling self, int id, int val*)

addEvidence(*LoopyWeightedSampling self, str nodeName, int val*) addEvidence(*LoopyWeightedSampling self, int id, str val*) addEvidence(*LoopyWeightedSampling self, str nodeName, str val*) addEvidence(*LoopyWeightedSampling self, int id, Vector vals*) addEvidence(*LoopyWeightedSampling self, str nodeName, Vector vals*)

Adds a new evidence on a node (might be soft or hard).

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*int*) – a node name
- **val** – (int) a node value
- **val** – (str) the label of the node value
- **vals** (*list*) – a list of values

Raises

- gum.InvalidArgument – If the node already has an evidence
- gum.InvalidArgument – If val is not a value for the node
- gum.InvalidArgument – If the size of vals is different from the domain side of the node
- gum.FatalError – If vals is a vector of 0s
- gum.UndefinedElement – If the node does not belong to the Bayesian network

addTarget (*LoopyWeightedSampling self, int target*)
 addTarget(LoopyWeightedSampling self, str nodeName)

Add a marginal target to the list of targets.

Parameters

- **target** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Raises `gum.UndefinedElement` – If target is not a NodeId in the Bayes net

chgEvidence (*LoopyWeightedSampling self, int id, int val*)

chgEvidence(LoopyWeightedSampling self, str nodeName, int val) chgEvidence(LoopyWeightedSampling self, str nodeName, int id, str val) chgEvidence(LoopyWeightedSampling self, str nodeName, str val) chgEvidence(LoopyWeightedSampling self, int id, Vector vals) chgEvidence(LoopyWeightedSampling self, str nodeName, Vector vals)

Change the value of an already existing evidence on a node (might be soft or hard).

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*int*) – a node name
- **val** – (int) a node value
- **val** – (str) the label of the node value
- **vals** (*list*) – a list of values

Raises

- `gum.InvalidArgument` – If the node does not already have an evidence
- `gum.InvalidArgument` – If val is not a value for the node
- `gum.InvalidArgument` – If the size of vals is different from the domain side of the node
- `gum.FatalError` – If vals is a vector of 0s
- `gum.UndefinedElement` – If the node does not belong to the Bayesian network

currentPosterior (*LoopyWeightedSampling self, int id*)

currentPosterior(LoopyWeightedSampling self, str name) -> Potential

Computes and returns the current posterior of a node.

Parameters

- **var** (*int*) – the node Id of the node for which we need a posterior probability
- **nodeName** (*str*) – the node name of the node for which we need a posterior probability

Returns a ref to the current posterior probability of the node

Return type `pyAgrum.Potential` (page 37)

Raises `UndefinedElement` (page 163) – If an element of nodes is not in targets

currentTime (*LoopyWeightedSampling self*)

Returns get the current running time in second (double)

Return type double

epsilon (*LoopyWeightedSampling self*)

Returns the value of epsilon

Return type double

eraseAllEvidence (*LoopyWeightedSampling self*)

Removes all the evidence entered into the network.

eraseAllTargets (*LoopyWeightedSampling self*)

Clear all previously defined targets (marginal and joint targets).

As a result, no posterior can be computed (since we can only compute the posteriors of the marginal or joint targets that have been added by the user).

eraseEvidence (*LoopyWeightedSampling self, int id*)

`eraseEvidence(LoopyWeightedSampling self, str nodeName)`

Remove the evidence, if any, corresponding to the node Id or name.

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*int*) – a node name

Raises `gum.IndexError` – If the node does not belong to the Bayesian network

eraseTarget (*LoopyWeightedSampling self, int target*)

`eraseTarget(LoopyWeightedSampling self, str nodeName)`

Remove, if existing, the marginal target.

Parameters

- **target** (*int*) – a node Id
- **nodeName** (*int*) – a node name

Raises

- `gum.IndexError` – If one of the node does not belong to the Bayesian network
- `gum.UndefinedElement` – If node Id is not in the Bayesian network

evidenceImpact (*LoopyWeightedSampling self, int target, PyObject * evs*)

`evidenceImpact(LoopyWeightedSampling self, str target, Vector_string evs)` -> Potential

Create a `pyAgrum.Potential` for $P(\text{target}|\text{levs})$ (for all instantiation of target and evs)

Parameters

- **target** (*set*) – a set of targets ids or names.
- **evs** (*set*) – a set of nodes ids or names.

Warning: if some evs are d-separated, they are not included in the Potential.

Returns a Potential for $P(\text{targets}|\text{levs})$

Return type `pyAgrum.Potential` (page 37)

hardEvidenceNodes (*LoopyWeightedSampling self*)

Returns the set of nodes with hard evidence

Return type set

hasEvidence (*LoopyWeightedSampling self, int id*)

`hasEvidence(LoopyWeightedSampling self, str nodeName)` -> bool

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Returns True if some node(s) (or the one in parameters) have received evidence

Return type bool

Raises gum.IndexError – If the node does not belong to the Bayesian network

hasHardEvidence (*LoopyWeightedSampling self, str nodeName*)

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Returns True if node has received a hard evidence

Return type bool

Raises gum.IndexError – If the node does not belong to the Bayesian network

hasSoftEvidence (*LoopyWeightedSampling self, int id*)

hasSoftEvidence(*LoopyWeightedSampling self, str nodeName*) -> bool

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Returns True if node has received a soft evidence

Return type bool

Raises gum.IndexError – If the node does not belong to the Bayesian network

history (*LoopyWeightedSampling self*)

Returns the scheme history

Return type tuple

Raises gum.OperationNotAllowed – If the scheme did not performed or if verbosity is set to false

isTarget (*LoopyWeightedSampling self, int variable*)

isTarget(*LoopyWeightedSampling self, str nodeName*) -> bool

Parameters

- **variable** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Returns True if variable is a (marginal) target

Return type bool

Raises

- gum.IndexError – If the node does not belong to the Bayesian network
- gum.UndefinedElement – If node Id is not in the Bayesian network

makeInference (*LoopyWeightedSampling self*)

Perform the heavy computations needed to compute the targets' posteriors

In a Junction tree propagation scheme, for instance, the heavy computations are those of the messages sent in the JT. This is precisely what makeInference should compute. Later, the computations of the posteriors can be done ‘lightly’ by multiplying and projecting those messages.

maxIter (*LoopyWeightedSampling self*)

Returns the criterion on number of iterations

Return type int

maxTime (*LoopyWeightedSampling self*)

Returns the timeout(in seconds)

Return type double

messageApproximationScheme (*LoopyWeightedSampling self*)

Returns the approximation scheme message

Return type str

minEpsilonRate (*LoopyWeightedSampling self*)

Returns the value of the minimal epsilon rate

Return type double

nbrEvidence (*LoopyWeightedSampling self*)

Returns the number of evidence entered into the Bayesian network

Return type int

nbrHardEvidence (*LoopyWeightedSampling self*)

Returns the number of hard evidence entered into the Bayesian network

Return type int

nbrIterations (*LoopyWeightedSampling self*)

Returns the number of iterations

Return type int

nbrSoftEvidence (*LoopyWeightedSampling self*)

Returns the number of soft evidence entered into the Bayesian network

Return type int

nbrTargets (*LoopyWeightedSampling self*)

Returns the number of marginal targets

Return type int

periodSize (*LoopyWeightedSampling self*)

Returns the number of samples between 2 stopping

Return type int

Raises gum.OutOfLowerBound – If p<1

posterior (*LoopyWeightedSampling self, int var*)

posterior(*LoopyWeightedSampling self, str nodeName*) -> Potential

Computes and returns the posterior of a node.

Parameters

- **var** (*int*) – the node Id of the node for which we need a posterior probability
- **nodeName** (*str*) – the node name of the node for which we need a posterior probability

Returns a ref to the posterior probability of the node

Return type *pyAgrum.Potential* (page 37)

Raises gum.UndefinedElement – If an element of nodes is not in targets

setEpsilon (*LoopyWeightedSampling self, double eps*)

Parameters **eps** (*double*) – the epsilon we want to use

Raises gum.OutOfLowerBound – If $\text{eps} < 0$

setEvidence (*evidces*)

Erase all the evidences and apply addEvidence(key,value) for every pairs in evidces.

Parameters *evidces* (*dict*) – a dict of evidences

Raises

- gum.InvalidArgument – If one value is not a value for the node
- gum.InvalidArgument – If the size of a value is different from the domain side of the node
- gum.FatalError – If one value is a vector of 0s
- gum.UndefinedElement – If one node does not belong to the Bayesian network

setMaxIter (*LoopyWeightedSampling self, int max*)

Parameters *max* (*int*) – the maximum number of iteration

Raises gum.OutOfLowerBound – If $\text{max} \leq 1$

setMaxTime (*LoopyWeightedSampling self, double timeout*)

Parameters *timeout* (*double*) – stopping criterion on timeout (in seconds)

Raises gum.OutOfLowerBound – If $\text{timeout} \leq 0.0$

setMinEpsilonRate (*LoopyWeightedSampling self, double rate*)

Parameters *rate* (*double*) – the minimal epsilon rate

setPeriodSize (*LoopyWeightedSampling self, int p*)

Parameters *p* (*int*) – number of samples between 2 stopping

Raises gum.OutOfLowerBound – If $\text{p} < 1$

setTargets (*targets*)

Remove all the targets and add the ones in parameter.

Parameters *targets* (*set*) – a set of targets

Raises gum.UndefinedElement – If one target is not in the Bayes net

setVerbosity (*LoopyWeightedSampling self, bool v*)

Parameters *v* (*bool*) – verbosity

setVirtualLBPSize (*LoopyWeightedSampling self, double vlpbsize*)

Parameters *vlpbsize* (*double*) – the size of the virtual LBP

softEvidenceNodes (*LoopyWeightedSampling self*)

Returns the set of nodes with soft evidence

Return type set

targets (*LoopyWeightedSampling self*)

Returns the list of marginal targets

Return type list

thisown

The membership flag

updateEvidence (*evidces*)

Apply chgEvidence(key,value) for every pairs in evidces (or addEvidence).

Parameters *evidces* (*dict*) – a dict of evidences

Raises

- gum.InvalidArgument – If one value is not a value for the node
- gum.InvalidArgument – If the size of a value is different from the domain side of the node
- gum.FatalError – If one value is a vector of 0s
- gum.UndefinedElement – If one node does not belong to the Bayesian network

verbosity (*LoopyWeightedSampling self*)

Returns True if the verbosity is enabled

Return type bool

1.5.3.3.4 Loopy Importance Sampling

class pyAgrum.**LoopyImportanceSampling** (*bn: pyAgrum.pyAgrum.IBayesNet*)

Class used for inferences using a loopy version of importance sampling.

Available ructors: LoopyImportanceSampling (*bn*) → LoopyImportanceSampling

Parameters **bn** ([pyAgrum.BayesNet](#) (page 43)) – a Bayesian network

BN (*LoopyImportanceSampling self*)

Returns A ant reference over the IBayesNet referenced by this class.

Return type pyAgrum.IBayesNet

Raises gum.UndefinedElement – If no Bayes net has been assigned to the inference.

H (*LoopyImportanceSampling self, int X*)

H(*LoopyImportanceSampling self, str nodeName*) -> double

Parameters

- **x** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Returns the computed Shanon's entropy of a node given the observation

Return type double

addAllTargets (*LoopyImportanceSampling self*)

Add all the nodes as targets.

addEvidence (*LoopyImportanceSampling self, int id, int val*)

addEvidence(*LoopyImportanceSampling self, str nodeName, int val*) addEvidence(*LoopyImportanceSampling self, int id, str val*) addEvidence(*LoopyImportanceSampling self, str nodeName, str val*) addEvidence(*LoopyImportanceSampling self, int id, Vector vals*) addEvidence(*LoopyImportanceSampling self, str nodeName, Vector vals*)

Adds a new evidence on a node (might be soft or hard).

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*int*) – a node name
- **val** – (*int*) a node value
- **val** – (*str*) the label of the node value
- **vals** (*list*) – a list of values

Raises

- gum.InvalidArgument – If the node already has an evidence

- `gum.InvalidArgument` – If val is not a value for the node
- `gum.InvalidArgument` – If the size of vals is different from the domain side of the node
- `gum.FatalError` – If vals is a vector of 0s
- `gum.UndefinedElement` – If the node does not belong to the Bayesian network

addTarget (*LoopyImportanceSampling self, int target*)

`addTarget(LoopyImportanceSampling self, str nodeName)`

Add a marginal target to the list of targets.

Parameters

- **target** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Raises `gum.UndefinedElement` – If target is not a NodeId in the Bayes net

chgEvidence (*LoopyImportanceSampling self, int id, int val*)

`chgEvidence(LoopyImportanceSampling self, str nodeName, int val)` `chgEvidence(LoopyImportanceSampling self, int id, str val)` `chgEvidence(LoopyImportanceSampling self, str nodeName, str val)` `chgEvidence(LoopyImportanceSampling self, int id, Vector vals)` `chgEvidence(LoopyImportanceSampling self, str nodeName, Vector vals)`

Change the value of an already existing evidence on a node (might be soft or hard).

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*int*) – a node name
- **val** – (*int*) a node value
- **val** – (*str*) the label of the node value
- **vals** (*list*) – a list of values

Raises

- `gum.InvalidArgument` – If the node does not already have an evidence
- `gum.InvalidArgument` – If val is not a value for the node
- `gum.InvalidArgument` – If the size of vals is different from the domain side of the node
- `gum.FatalError` – If vals is a vector of 0s
- `gum.UndefinedElement` – If the node does not belong to the Bayesian network

currentPosterior (*LoopyImportanceSampling self, int id*)

`currentPosterior(LoopyImportanceSampling self, str name) -> Potential`

Computes and returns the current posterior of a node.

Parameters

- **var** (*int*) – the node Id of the node for which we need a posterior probability
- **nodeName** (*str*) – the node name of the node for which we need a posterior probability

Returns a ref to the current posterior probability of the node

Return type `pyAgrum.Potential` (page 37)

Raises `UndefinedElement` (page 163) – If an element of nodes is not in targets

currentTime (*LoopyImportanceSampling self*)

Returns get the current running time in second (double)

Return type double

epsilon (*LoopyImportanceSampling self*)

Returns the value of epsilon

Return type double

eraseAllEvidence (*LoopyImportanceSampling self*)

Removes all the evidence entered into the network.

eraseAllTargets (*LoopyImportanceSampling self*)

Clear all previously defined targets (marginal and joint targets).

As a result, no posterior can be computed (since we can only compute the posteriors of the marginal or joint targets that have been added by the user).

eraseEvidence (*LoopyImportanceSampling self, int id*)

eraseEvidence(*LoopyImportanceSampling self, str nodeName*)

Remove the evidence, if any, corresponding to the node Id or name.

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*int*) – a node name

Raises `gum.IndexError` – If the node does not belong to the Bayesian network

eraseTarget (*LoopyImportanceSampling self, int target*)

eraseTarget(*LoopyImportanceSampling self, str nodeName*)

Remove, if existing, the marginal target.

Parameters

- **target** (*int*) – a node Id
- **nodeName** (*int*) – a node name

Raises

- `gum.IndexError` – If one of the node does not belong to the Bayesian network
- `gum.UndefinedElement` – If node Id is not in the Bayesian network

evidenceImpact (*LoopyImportanceSampling self, int target, PyObject * evs*)

evidenceImpact(*LoopyImportanceSampling self, str target, Vector_string evs*) -> Potential

Create a pyAgrum.Potential for P(targetlevs) (for all instantiation of target and evs)

Parameters

- **target** (*set*) – a set of targets ids or names.
- **evs** (*set*) – a set of nodes ids or names.

Warning: if some evs are d-separated, they are not included in the Potential.

Returns a Potential for P(targetslevs)

Return type `pyAgrum.Potential` (page 37)

hardEvidenceNodes (*LoopyImportanceSampling self*)

Returns the set of nodes with hard evidence

Return type set

hasEvidence (*LoopyImportanceSampling self, int id*)
hasEvidence(LoopyImportanceSampling self, str nodeName) -> bool

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Returns True if some node(s) (or the one in parameters) have received evidence

Return type bool

Raises gum.IndexError – If the node does not belong to the Bayesian network

hasHardEvidence (*LoopyImportanceSampling self, str nodeName*)

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Returns True if node has received a hard evidence

Return type bool

Raises gum.IndexError – If the node does not belong to the Bayesian network

hasSoftEvidence (*LoopyImportanceSampling self, int id*)

hasSoftEvidence(LoopyImportanceSampling self, str nodeName) -> bool

Parameters

- **id** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Returns True if node has received a soft evidence

Return type bool

Raises gum.IndexError – If the node does not belong to the Bayesian network

history (*LoopyImportanceSampling self*)

Returns the scheme history

Return type tuple

Raises gum.OperationNotAllowed – If the scheme did not performed or if verbosity is set to false

isTarget (*LoopyImportanceSampling self, int variable*)

isTarget(LoopyImportanceSampling self, str nodeName) -> bool

Parameters

- **variable** (*int*) – a node Id
- **nodeName** (*str*) – a node name

Returns True if variable is a (marginal) target

Return type bool

Raises

- gum.IndexError – If the node does not belong to the Bayesian network
- gum.UndefinedElement – If node Id is not in the Bayesian network

makeInference (*LoopyImportanceSampling self*)

Perform the heavy computations needed to compute the targets' posteriors

In a Junction tree propagation scheme, for instance, the heavy computations are those of the messages sent in the JT. This is precisely what makeInference should compute. Later, the computations of the posteriors can be done ‘lightly’ by multiplying and projecting those messages.

maxIter (*LoopyImportanceSampling self*)

Returns the criterion on number of iterations

Return type int

maxTime (*LoopyImportanceSampling self*)

Returns the timeout(in seconds)

Return type double

messageApproximationScheme (*LoopyImportanceSampling self*)

Returns the approximation scheme message

Return type str

minEpsilonRate (*LoopyImportanceSampling self*)

Returns the value of the minimal epsilon rate

Return type double

nbrEvidence (*LoopyImportanceSampling self*)

Returns the number of evidence entered into the Bayesian network

Return type int

nbrHardEvidence (*LoopyImportanceSampling self*)

Returns the number of hard evidence entered into the Bayesian network

Return type int

nbrIterations (*LoopyImportanceSampling self*)

Returns the number of iterations

Return type int

nbrSoftEvidence (*LoopyImportanceSampling self*)

Returns the number of soft evidence entered into the Bayesian network

Return type int

nbrTargets (*LoopyImportanceSampling self*)

Returns the number of marginal targets

Return type int

periodSize (*LoopyImportanceSampling self*)

Returns the number of samples between 2 stopping

Return type int

Raises gum.OutOfLowerBound – If p<1

posterior (*LoopyImportanceSampling self, int var*)

posterior(LoopyImportanceSampling self, str nodeName) -> Potential

Computes and returns the posterior of a node.

Parameters

- **var** (*int*) – the node Id of the node for which we need a posterior probability
- **nodeName** (*str*) – the node name of the node for which we need a posterior probability

Returns a ref to the posterior probability of the node

Return type *pyAgrum.Potential* (page 37)

Raises *gum.UndefinedElement* – If an element of nodes is not in targets

setEpsilon (*LoopyImportanceSampling self, double eps*)

Parameters **eps** (*double*) – the epsilon we want to use

Raises *gum.OutOfLowerBound* – If *eps*<0

setEvidence (*evidces*)

Erase all the evidences and apply addEvidence(key,value) for every pairs in evidces.

Parameters **evidces** (*dict*) – a dict of evidences

Raises

- *gum.InvalidArgument* – If one value is not a value for the node
- *gum.InvalidArgument* – If the size of a value is different from the domain side of the node
- *gum.FatalError* – If one value is a vector of 0s
- *gum.UndefinedElement* – If one node does not belong to the Bayesian network

setMaxIter (*LoopyImportanceSampling self, int max*)

Parameters **max** (*int*) – the maximum number of iteration

Raises *gum.OutOfLowerBound* – If *max* <= 1

setMaxTime (*LoopyImportanceSampling self, double timeout*)

Parameters **timeout** (*double*) – stopping criterion on timeout (in seconds)

Raises *gum.OutOfLowerBound* – If *timeout*<=0.0

setMinEpsilonRate (*LoopyImportanceSampling self, double rate*)

Parameters **rate** (*double*) – the minimal epsilon rate

setPeriodSize (*LoopyImportanceSampling self, int p*)

Parameters **p** (*int*) – number of samples between 2 stopping

Raises *gum.OutOfLowerBound* – If *p*<1

setTargets (*targets*)

Remove all the targets and add the ones in parameter.

Parameters **targets** (*set*) – a set of targets

Raises *gum.UndefinedElement* – If one target is not in the Bayes net

setVerbosity (*LoopyImportanceSampling self, bool v*)

Parameters **v** (*bool*) – verbosity

setVirtualLBPSize (*LoopyImportanceSampling self, double vlpbsize*)

Parameters **vlpbsize** (*double*) – the size of the virtual LBP

softEvidenceNodes (*LoopyImportanceSampling self*)

Returns the set of nodes with soft evidence

Return type set

targets (*LoopyImportanceSampling self*)

Returns the list of marginal targets

Return type list

thisown

The membership flag

updateEvidence (*evidces*)

Apply chgEvidence(key,value) for every pairs in evidces (or addEvidence).

Parameters **evidces** (*dict*) – a dict of evidences

Raises

- gum.InvalidArgument – If one value is not a value for the node
- gum.InvalidArgument – If the size of a value is different from the domain side of the node
- gum.FatalError – If one value is a vector of 0s
- gum.UndefinedElement – If one node does not belong to the Bayesian network

verbosity (*LoopyImportanceSampling self*)

Returns True if the verbosity is enabled

Return type bool

1.5.4 Learning

class pyAgrum.BNLearner (*args)

Available ructors: BNLearner(filename) -> BNLearner

BNLearner(filename,src,parse_database=false) -> BNLearner

BNLearner(learner) -> BNLearner

Parameters

- **filename** (*str*) – the file to learn from
- **src** ([pyAgrum.BayesNet](#) (page 43)) – the Bayesian network used to find those modalities
- **parse_database** (*bool*) – if true, the modalities specified by the user will be considered as a superset of the modalities of the variables.
- **learner** ([pyAgrum.BNLearner](#) (page 129)) – the BNLearner to copy

G2 (*BNLearner self, str var1, str var2, Vector_string knw={}*)

G2 computes the G2 statistic and pvalue for two columns, given a list of other columns.

Parameters

- **name1** (*str*) – the name of the first column
- **name2** (*str*) – the name of the second column
- **knowing** (*[str]*) – the list of names of conditioning columns

Returns the G2 statistic and the associated p-value as a Tuple

Return type statistic,pvalue

addForbiddenArc (*BNLearner self, Arc arc*)

addForbiddenArc(BNLearner self, int tail, int head) addForbiddenArc(BNLearner self, str tail, str head)

The arc in parameters won't be added.

Parameters

- **arc** ([pyAgrum.Arc](#) (page 5)) – an arc
- **head** – a variable's id (int)
- **tail** – a variable's id (int)
- **head** – a variable's name (str)
- **tail** – a variable's name (str)

addMandatoryArc (*BNLearner self, Arc arc*)

addMandatoryArc(BNLearner self, int tail, int head) addMandatoryArc(BNLearner self, str tail, str head)

Allow to add prior structural knowledge.

Parameters

- **arc** ([pyAgrum.Arc](#) (page 5)) – an arc
- **head** – a variable's id (int)
- **tail** – a variable's id (int)
- **head** – a variable's name (str)
- **tail** – a variable's name (str)

Raises `gum.InvalidDirectedCycle` – If the added arc creates a directed cycle in the DAG

addPossibleEdge (*BNLearner self, Edge edge*)

addPossibleEdge(BNLearner self, int tail, int head) addPossibleEdge(BNLearner self, str tail, str head)

chi2 (*BNLearner self, str var1, str var2, Vector_string knw={}*)

chi2 computes the chi2 statistic and pvalue for two columns, given a list of other columns.

Parameters

- **name1** (`str`) – the name of the first column
- **name2** (`str`) – the name of the second column
- **knowing** (`[str]`) – the list of names of conditioning columns

Returns the chi2 statistic and the associated p-value as a Tuple

Return type `statistic,pvalue`

currentTime (*BNLearner self*)

Returns get the current running time in second (double)

Return type double

databaseWeight (*BNLearner self*)

epsilon (*BNLearner self*)

Returns the value of epsilon

Return type double

`eraseForbiddenArc (BNLearner self, Arc arc)`

`eraseForbiddenArc(BNLearner self, int tail, int head)` `eraseForbiddenArc(BNLearner self, str tail, str head)`

Allow the arc to be added if necessary.

Parameters

- **arc** (*pyAgrum*) – an arc
- **head** – a variable's id (int)
- **tail** – a variable's id (int)
- **head** – a variable's name (str)
- **tail** – a variable's name (str)

`eraseMandatoryArc (BNLearner self, Arc arc)`

`eraseMandatoryArc(BNLearner self, int tail, int head)` `eraseMandatoryArc(BNLearner self, str tail, str head)`

Parameters

- **arc** (*pyAgrum*) – an arc
- **head** – a variable's id (int)
- **tail** – a variable's id (int)
- **head** – a variable's name (str)
- **tail** – a variable's name (str)

`erasePossibleEdge (BNLearner self, Edge edge)`

`erasePossibleEdge(BNLearner self, int tail, int head)` `erasePossibleEdge(BNLearner self, str tail, str head)`

Allow the 2 arcs to be added if necessary.

Parameters

- **arc** (*pyAgrum*) – an arc
- **head** – a variable's id (int)
- **tail** – a variable's id (int)
- **head** – a variable's name (str)
- **tail** – a variable's name (str)

`hasMissingValues (BNLearner self)`

Indicates whether there are missing values in the database.

Returns True if there are some missing values in the database.

Return type bool

`history (BNLearner self)`

Returns the scheme history

Return type tuple

Raises `gum.OperationNotAllowed` – If the scheme did not performed or if verbosity is set to false

`idFromName (BNLearner self, str var_name)`

Parameters `var_names` (str) – a variable's name

Returns the column id corresponding to a variable name

Return type int

Raises `gum.MissingVariableInDatabase` – If a variable of the BN is not found in the database.

latentVariables (*BNLearner self*)

`latentVariables(BNLearner self) -> vector<pyAgrum.Arc,allocator<pyAgrum.Arc>>`

Warning: learner must be using 3off2 or MIIC algorithm

Returns the list of latent variables

Return type list

learnBN (*BNLearner self*)

`learn a BayesNet from a file (must have read the db before)`

Returns the learned BayesNet

Return type `pyAgrum.BayesNet` (page 43)

learnDAG (*BNLearner self*)

`learn a structure from a file`

Returns the learned DAG

Return type `pyAgrum.DAG` (page 9)

learnMixedStructure (*BNLearner self*)

Warning: learner must be using 3off2 or MIIC algorithm

Returns the learned structure as an EssentialGraph

Return type `pyAgrum.EssentialGraph`

learnParameters (*BNLearner self, DAG dag, bool take_into_account_score=True*)

`learnParameters(BNLearner self, bool take_into_account_score=True) -> BayesNet`

`learns a BN (its parameters) when its structure is known.`

Parameters

- **dag** (`pyAgrum.DAG` (page 9)) –
- **bn** (`pyAgrum.BayesNet` (page 43)) –
- **take_into_account_score** (`bool`) – The dag passed in argument may have been learnt from a structure learning. In this case, if the score used to learn the structure has an implicit apriori (like K2 which has a 1-smoothing apriori), it is important to also take into account this implicit apriori for parameter learning. By default, if a score exists, we will learn parameters by taking into account the apriori specified by methods `useAprioriXXX()` + the implicit apriori of the score, else we just take into account the apriori specified by `useAprioriXXX()`

Returns the learned BayesNet

Return type `pyAgrum.BayesNet` (page 43)

Raises

- `gum.MissingVariableInDatabase` – If a variable of the BN is not found in the database
- `gum.UnknownLabelInDatabase` – If a label is found in the database that do not correspond to the variable

logLikelihood (*BNLearner self*, *vector< int, allocator< int > > vars*, *vector< int, allocator< int > > knowing={}*)
logLikelihood(BNLearner self, vector< int,allocator< int > > vars) -> double logLikelihood(BNLearner self, Vector_string vars, Vector_string knowing={{}}) -> double logLikelihood(BNLearner self, Vector_string vars) -> double

logLikelihood computes the log-likelihood for the columns in vars, given the columns in the list knowing (optional)

Parameters

- **vars** (*List [str]*) – the name of the columns of interest
- **knowing** (*List [str]*) – the (optional) list of names of conditioning columns

Returns the log-likelihood (base 2)

Return type double

maxIter (*BNLearner self*)

Returns the criterion on number of iterations

Return type int

maxTime (*BNLearner self*)

Returns the timeout(in seconds)

Return type double

messageApproximationScheme (*BNLearner self*)

Returns the approximation scheme message

Return type str

minEpsilonRate (*BNLearner self*)

Returns the value of the minimal epsilon rate

Return type double

nameFromId (*BNLearner self, int id*)

Parameters **id** – a node id

Returns the variable's name

Return type str

names (*BNLearner self*)

Returns the names of the variables in the database

Return type List[str]

nbCols (*BNLearner self*)

Return the nimber of columns in the database

Returns the number of columns in the database

Return type int

nbRows (*BNLearner self*)

Return the number of row in the database

Returns the number of rows in the database

Return type int

nbrIterations (*BNLearner self*)

Returns the number of iterations

Return type int

periodSize (*BNLearner self*)

Returns the number of samples between 2 stopping

Return type int

Raises gum.OutOfLowerBound – If p<1

recordWeight (*BNLearner self, size_t i*)

setAprioriWeight (*weight*)

Deprecated methods in BNLearner for pyAgrum>0.14.0

setDatabaseWeight (*BNLearner self, double new_weight*)

Set the database weight.

Parameters **weight** (*double*) – the database weight

setEpsilon (*BNLearner self, double eps*)

Parameters **eps** (*double*) – the epsilon we want to use

Raises gum.OutOfLowerBound – If eps<0

setInitialDAG (*BNLearner self, DAG g*)

Parameters **dag** ([pyAgrum.DAG](#) (page 9)) – an initial DAG structure

setMaxIndegree (*BNLearner self, int max_indegree*)

setMaxIter (*BNLearner self, int max*)

Parameters **max** (*int*) – the maximum number of iteration

Raises gum.OutOfLowerBound – If max <= 1

setMaxTime (*BNLearner self, double timeout*)

Parameters **timeout** (*double*) – stopping criterion on timeout (in seconds)

Raises gum.OutOfLowerBound – If timeout<=0.0

setMinEpsilonRate (*BNLearner self, double rate*)

Parameters **rate** (*double*) – the minimal epsilon rate

setPeriodSize (*BNLearner self, int p*)

Parameters **p** (*int*) – number of samples between 2 stopping

Raises gum.OutOfLowerBound – If p<1

setPossibleSkeleton (*BNLearner self, UndiGraph skeleton*)

setRecordWeight (*BNLearner self, size_t i, double weight*)

setSliceOrder (*BNLearner self, PyObject *l*)

setSliceOrder(BNLearner self, pyAgrum.NodeProperty< int > slice_order) setSliceOrder(BNLearner self, vector< vector< str,allocator< str > >,allocator< vector< str,allocator< str > > > > slices)

Set a partial order on the nodes.

Parameters **l** (*list*) – a list of sequences (composed of ids of rows or string)

setVerbosity (*BNLearner self, bool v*)

Parameters **v** (*bool*) – verbosity

thisown

The membership flag

use3off2 (*BNLearner self*)

Indicate that we wish to use 3off2.

useAprioriBDeu (*BNLearner self, double weight=1*)
useAprioriBDeu(*BNLearner self*)

The BDeu apriori adds weight to all the cells of the counting tables. In other words, it adds weight rows in the database with equally probable values.

Parameters **weight** (*double*) – the apriori weight

useAprioriDirichlet (*BNLearner self, str filename, double weight=1*)
useAprioriDirichlet(*BNLearner self, str filename*)

useAprioriSmoothing (*BNLearner self, double weight=1*)
useAprioriSmoothing(*BNLearner self*)

useEM (*BNLearner self, double epsilon*)
Indicates if we use EM for parameter learning.

Parameters **epsilon** (*double*) – if epsilon=0.0 then EM is not used if epsilon>0 then EM is used and stops when the sum of the cumulative squared error on parameters is less than epsilon.

useGreedyHillClimbing (*BNLearner self*)

useK2 (*BNLearner self, PyObject * l*)
useK2(*BNLearner self, pyAgrum.Sequence< int > order*) useK2(*BNLearner self, vector< int,allocator< int > order*)

Indicate that we wish to use K2.

Parameters **order** (*list*) – a list of ids

useLocalSearchWithTabuList (*BNLearner self, int tabu_size=100, int nb_decrease=2*)
useLocalSearchWithTabuList(*BNLearner self, int tabu_size=100*) useLocalSearchWithTabuList(*BNLearner self*)

Indicate that we wish to use a local search with tabu list

Parameters

- **tabu_size** (*int*) – The size of the tabu list
- **nb_decrease** (*int*) – The max number of changes decreasing the score consecutively that we allow to apply

useMDL (*BNLearner self*)

Indicate that we wish to use the MDL correction for 3off2 or MIIC

useMIIC (*BNLearner self*)

Indicate that we wish to use MIIC.

useNML (*BNLearner self*)

Indicate that we wish to use the NML correction for 3off2 or MIIC

useNoApriori (*BNLearner self*)

useNoCorr (*BNLearner self*)

Indicate that we wish to use the NoCorr correction for 3off2 or MIIC

useScoreAIC (*BNLearner self*)

useScoreBD (*BNLearner self*)

useScoreBDeu (*BNLearner self*)

useScoreBIC (*BNLearner self*)

useScoreK2 (*BNLearner self*)

useScoreLog2Likelihood (*BNLearner self*)

verbosity (*BNLearner self*)

Returns True if the verbosity is enabled

Return type bool

1.6 Probabilistic Relational Models

For now, pyAgrum only allows to explore Probabilistic Relational Models written with o3prm syntax.

class `pyAgrum.PRMexplorer`

PRMexplorer helps navigate through probabilistic relational models.

Available ructors: `PRMexplorer() -> PRMexplorer`

aggType

`a(9).str`

min/max/count/exists/forall/or/and/amplitude/median

Type aggType

classAggregates (`PRMexplorer self, str class_name`)

Parameters `class_name (str)` – a class name

Returns the list of aggregates in the class

Return type list

Raises `gum.IndexError` – If the class is not in the PRM

classAttributes (`PRMexplorer self, str class_name`)

Parameters `class_name (str)` – a class name

Returns the list of attributes

Return type list

Raises `gum.IndexError` – If the class is not in the PRM

classDag (`PRMexplorer self, str class_name`)

Parameters `class_name (str)` – a class name

Returns a description of the DAG

Return type tuple

Raises `gum.IndexError` – If the class is not in the PRM

classImplements (`PRMexplorer self, str class_name`)

Parameters `class_name (str)` – a class name

Returns the list of interfaces implemented by the class

Return type list

classParameters (`PRMexplorer self, str class_name`)

Parameters `class_name (str)` – a class name

Returns the list of parameters

Return type list

Raises `gum.IndexError` – If the class is not in the PRM

classReferences (`PRMexplorer self, str class_name`)

Parameters `class_name (str)` – a class name

Returns the list of references

Return type list

Raises `gum.IndexError` – If the class is not in the PRM

classSlotChains (*PRMexplorer self, str class_name*)

Parameters `class_name` (*str*) – a class name

Returns the list of class slot chains

Return type list

Raises `gum.IndexError` – if the class is not in the PRM

classes (*PRMexplorer self*)

Returns the list of classes

Return type list

cpf (*PRMexplorer self, str class_name, str attribute*)

Parameters

- `class_name` (*str*) – a class name
- `attribute` (*str*) – an attribute

Returns the potential of the attribute

Return type `pyAgrum.Potential` (page 37)

Raises

- `gum.OperationNotAllowed` – If the class element doesn't have any `pyAgrum.Potential` (like a `pyAgrum.PRMReferenceSlot`).
- `gum.IndexError` – If the class is not in the PRM
- `gum.IndexError` – If the attribute in parameters does not exist

getDirectSubClass (*PRMexplorer self, str class_name*)

Parameters `class_name` (*str*) – a class name

Returns the list of direct subclasses

Return type list

Raises `gum.IndexError` – If the class is not in the PRM

getDirectSubInterfaces (*PRMexplorer self, str interface_name*)

Parameters `interface_name` (*str*) – an interface name

Returns the list of direct subinterfaces

Return type list

Raises `gum.IndexError` – If the interface is not in the PRM

getDirectSubTypes (*PRMexplorer self, str type_name*)

Parameters `type_name` (*str*) – a type name

Returns the list of direct subtypes

Return type list

Raises `gum.IndexError` – If the type is not in the PRM

getImplementations (*PRMexplorer self, str interface_name*)

Parameters `interface_name` (*str*) – an interface name

Returns the list of classes implementing the interface

Return type str

Raises gum.IndexError – If the interface is not in the PRM

getLabelMap (*PRMexplorer self*, str *type_name*)

Parameters **type_name** (str) – a type name

Returns a dict containing pairs of label and their values

Return type dict

Raises gum.IndexError – If the type is not in the PRM

getLabels (*PRMexplorer self*, str *type_name*)

Parameters **type_name** (str) – a type name

Returns the list of type labels

Return type list

Raises gum.IndexError – If the type is not in the PRM

getSuperClass (*PRMexplorer self*, str *class_name*)

Parameters **class_name** (str) – a class name

Returns the class extended by class_name

Return type str

Raises gum.IndexError – If the class is not in the PRM

getSuperInterface (*PRMexplorer self*, str *interface_name*)

Parameters **interface_name** (str) – an interface name

Returns the interface extended by interface_name

Return type str

Raises gum.IndexError – If the interface is not in the PRM

getSuperType (*PRMexplorer self*, str *type_name*)

Parameters **type_name** (str) – a type name

Returns the type extended by type_name

Return type str

Raises gum.IndexError – If the type is not in the PRM

getAlltheSystems (*PRMexplorer self*)

Returns the list of all the systems and their components

Return type list

interAttributes (*PRMexplorer self*, str *interface_name*, bool *allAttributes=False*)

Parameters

- **interface_name** (str) – an interface
- **allAttributes** (bool) – True if supertypes of a custom type should be indicated

Returns the list of (<type>,<attribute_name>) for the given interface

Return type list

Raises gum.IndexError – If the type is not in the PRM

interReferences (*PRMexplorer self*, str *interface_name*)

Parameters **interface_name** (str) – an interface

Returns the list of (<reference_type>,<reference_name>,<True if the reference is an array>) for the given interface

Return type list

Raises gum.IndexError – If the type is not in the PRM

interfaces (PRMexplorer self)

Returns the list of interfaces in the PRM

Return type list

isAttribute (PRMexplorer self, str class_name, str att_name)

Parameters

- **class_name** (str) – a class name
- **att_name** (str) – the name of the attribute to be tested

Returns True if att_name is an attribute of class_name

Return type bool

Raises

- gum.IndexError – If the class is not in the PRM
- gum.IndexError – If att_name is not an element of class_name

isClass (PRMexplorer self, str name)

Parameters **name** (str) – an element name

Returns True if the parameter correspond to a class in the PRM

Return type bool

isInterface (PRMexplorer self, str name)

Parameters **name** (str) – an element name

Returns True if the parameter correspond to an interface in the PRM

Return type bool

isType (PRMexplorer self, str name)

Parameters **name** (str) – an element name

Returns True if the parameter correspond to a type in the PRM

Return type bool

load (PRMexplorer self, str filename, str classpath="", bool verbose=False)

Load a PRM into the explorer.

Parameters

- **filename** (str) – the name of the o3prm file
- **classpath** (str) – the classpath of the PRM

Raises gum.FatalError – If file not found

thisown

The membership flag

types (PRMexplorer self)

Returns the list of the custom types in the PRM

Return type list

1.7 Credal Networks

1.7.1 Model

```
class pyAgrum.CredalNet(*args)
    Constructor used to create a CredalNet (step by step or with two BayesNet)
```

Available constructors: CredalNet() -> CredalNet

```
CredalNet(src_min_num,src_max_den) -> CredalNet
```

```
CredalNet(src_min_num,src_max_den) -> CredalNet
```

Parameters

- **src_min_num** – (str) the path to a BayesNet which contains lower probabilities.
- **src_max_den** – (str) the (optional) path to a BayesNet which contains upper probabilities.
- **src_min_num** – (pyAgrum.BayesNet) the BayesNet which contains lower probabilities.
- **src_max_den** – (pyAgrum.BayesNet) the (optional) BayesNet which contains upper probabilities.

addArc (*CredalNet self, int tail, int head*)

Adds an arc between two nodes

Parameters

- **tail** – the id of the tail node
- **head** (*int*) – the id of the head node

Raises

- gum.InvalidDirectedCircle – If any (directed) cycle is created by this arc
- gum.InvalidNode – If head or tail does not belong to the graph nodes
- gum.DuplicateElement – If one of the arc already exists

addVariable (*CredalNet self, str name, int card*)

Parameters

- **name** (*str*) – the name of the new variable
- **card** (*int*) – the domainSize of the new variable

Returns the id of the new node

Return type int

approximatedBinarization (*CredalNet self*)

Approximate binarization.

Each bit has a lower and upper probability which is the lowest - resp. highest - over all vertices of the credal set. Enlarge the original credal sets and may induce huge imprecision.

Warning: Enlarge the original credal sets and therefor induce huge imprecision by propagation.
Not recommended, use MCSampling or something else instead

bnToCredal (*CredalNet self, double beta, bool oneNet, bool keepZeroes=False*)

Perturbates the BayesNet provided as input for this CredalNet by generating intervals instead of point probabilities and then computes each vertex of each credal set.

Parameters

- **beta** (*double*) – The beta used to perturbate the network
- **oneNet** (*bool*) – used as a flag. Set to True if one BayesNet if provided with counts, to False if two BayesNet are provided; one with probabilities (the lower net) and one with denominators over the first modalities (the upper net)
- **keepZeroes** (*bool*) – used as a flag as whether or not - respectively True or False - we keep zeroes as zeroes. Default is False, i.e. zeroes are not kept

computeCPTMinMax (*CredalNet self*)

Used with binary networks to speed-up L2U inference.

Store the lower and upper probabilities of each node X over the ‘True’ modality.

credalNet_currentCpt (*CredalNet self*)**Warning:** Experimental function - Return type to be wrapped**Returns** a ant reference to the (up-to-date) CredalNet CPTs.**Return type** tbw**credalNet_srcCpt** (*CredalNet self*)**Warning:** Experimental function - Return type to be wrapped**Returns** a ant reference to the (up-to-date) CredalNet CPTs.**Return type** tbw**currentNodeType** (*CredalNet self, int id*)**Parameters** **id** (*int*) – The ant reference to the choosen NodeId**Returns** the type of the choosen node in the (up-to-date) CredalNet __current_bn if any, __src_bn otherwise.**Return type** [pyAgrum.CredalNet](#) (page 140)**current_bn** (*CredalNet self*)**Returns** Returs a ant reference to the actual BayesNet (used as a DAG, it's CPTs does not matter).**Return type** [pyAgrum.BayesNet](#) (page 43)**domainSize** (*CredalNet self, int id*)**Parameters** **id** (*int*) – The id of the node**Returns** The cardinality of the node**Return type** int**epsilonMax** (*CredalNet self*)**Returns** a ant reference to the highest perturbation of the BayesNet provided as input for this CredalNet.**Return type** double**epsilonMean** (*CredalNet self*)

Returns a ant reference to the average perturbation of the BayesNet provided as input for this CredalNet.

Return type double

epsilonMin (*CredalNet self*)

Returns a ant reference to the lowest perturbation of the BayesNet provided as input for this CredalNet.

Return type double

fillConstraint (*CredalNet self, int id, int entry, Vector lower, Vector upper*)

fillConstraint(*CredalNet self, int id, Instantiation ins, Vector lower, Vector upper*)

Set the interval raints of a credal set of a given node (from an instantiation index)

Parameters

- **id** (*int*) – The id of the node
- **entry** (*int*) – The index of the instantiation excluding the given node (only the parents are used to compute the index of the credal set)
- **ins** ([pyAgrum.Instantiation](#) (page 32)) – The Instantiation
- **lower** (*list*) – The lower value for each probability in correct order
- **upper** (*list*) – The upper value for each probability in correct order

Warning: You need to call `intervalToCredal` when done filling all raints.

Warning: DOES change the BayesNet (s) associated to this credal net !

fillConstraints (*CredalNet self, int id, Vector lower, Vector upper*)

Set the interval raints of the credal sets of a given node (all instantiations)

Parameters

- **id** (*int*) – The id of the node
- **lower** (*list*) – The lower value for each probability in correct order
- **upper** (*list*) – The upper value for each probability in correct order

Warning: You need to call `intervalToCredal` when done filling all raints.

Warning: DOES change the BayesNet (s) associated to this credal net !

get_CPT_max (*CredalNet self*)

Warning: Experimental function - Return type to be wrapped

Returns a ant reference to the upper probabilities of each node X over the ‘True’ modality

Return type tbw

get_CPT_min (*CredalNet self*)

Warning: Experimental function - Return type to be wrapped

Returns a ant reference to the lower probabilities of each node X over the ‘True’ modality

Return type tbw

hasComputedCPTMinMax (*CredalNet self*)

Returns True this CredalNet has called computeCPTMinMax() to speed-up inference with binary networks and L2U.

Return type bool

idmLearning (*CredalNet self, int s=0, bool keepZeroes=False*)

Learns parameters from a BayesNet storing counts of events.

Use this method when using a single BayesNet storing counts of events. IDM model if *s* > 0, standard point probability if *s* = 0 (default value if none precised).

Parameters

- **s** (*int*) – the IDM parameter.
- **keepZeroes** (*bool*) – used as a flag as whether or not - respectively True or False
- we keep zeroes as zeroes. Default is False, i.e. zeroes are not kept.

instantiation (*CredalNet self, int id*)

Get an Instantiation from a node id, usefull to fill the raints of the network.

bnet accessors / shortcuts.

Parameters **id** (*int*) – the id of the node we want an instantiation from

Returns the instantiation

Return type *pyAgrum.Instantiation* (page 32)

intervalToCredal (*CredalNet self*)

Computes the vertices of each credal set according to their interval definition (uses lrs).

Use this method when using two BayesNet, one with lower probabilities and one with upper probabilities.

intervalToCredalWithFiles (*CredalNet self*)

Warning: Deprecated : use intervalToCredal (lrsWrapper with no input / output files needed).

Computes the vertices of each credal set according to their interval definition (uses lrs).

Use this method when using a single BayesNet storing counts of events.

isSeparatelySpecified (*CredalNet self*)

Returns True if this CredalNet is separately and interval specified, False otherwise.

Return type bool

lagrangeNormalization (*CredalNet self*)

Normalize counts of a BayesNet storing counts of each events such that no probability is 0.

Use this method when using a single BayesNet storing counts of events. Lagrange normalization. This call is irreversible and modify counts stored by __src_bn.

Doest not performs computations of the parameters but keeps normalized counts of events only. Call idmLearning to compute the probabilities (with any parameter value).

nodeType (*CredalNet self, int id*)

Parameters **id** (*int*) – the ant reference to the choosen NodeId

Returns the type of the choosen node in the (up-to-date) CredalNet in __src_bn.

Return type [pyAgrum.CredalNet](#) (page 140)

saveBNsMinMax (*CredalNet self, str min_path, str max_path*)

If this CredalNet was built over a perturbed BayesNet, one can save the intervals as two BayesNet.

to call after bnToCredal(GUM_SCALAR beta) save a BN with lower probabilities and a BN with upper ones

Parameters

- **min_path** (*str*) – the path to save the BayesNet which contains the lower probabilities of each node X.
- **max_path** (*str*) – the path to save the BayesNet which contains the upper probabilities of each node X.

setCPT (*CredalNet self, int id, int entry, vector<vector<double, allocator>, allocator<vector<double, allocator>>> cpt*)

setCPT(CredalNet self, int id, Instantiation ins, vector<vector<double, allocator>, allocator<vector<double, allocator>>> cpt)

Warning: (experimental function) - Parameters to be wrapped

Set the vertices of one credal set of a given node (any instantiation index)

Parameters

- **id** (*int*) – the Id of the node
- **entry** (*int*) – the index of the instantiation (from 0 to K - 1) excluding the given node (only the parents are used to compute the index of the credal set)
- **ins** ([pyAgrum.Instantiation](#) (page 32)) – the Instantiation (only the parents matter to find the credal set index)
- **cpt** (*tbw*) – the vertices of every credal set (for each instantiation of the parents)

Warning: DOES not change the BayesNet(s) associated to this credal net !

setCPTs (*CredalNet self, int id, vector<vector<vector<double, allocator>, allocator<vector<double, allocator>>>, allocator<vector<vector<double, allocator>, allocator<vector<double, allocator>>>> cpt*)

Warning: (experimental function) - Parameters to be wrapped

Set the vertices of the credal sets (all of the conditionals) of a given node

Parameters

- **id** (*int*) – the NodeId of the node
- **cpt** (*tbw*) – the vertices of every credal set (for each instantiation of the parents)

Warning: DOES not change the BayesNet (s) associated to this credal net !

src_bn (*CredalNet self*)

Returns Returns a ant reference to the original BayesNet (used as a DAG, it's CPTs does not matter).

Return type [pyAgrum.BayesNet](#) (page 43)

thisown

The membership flag

1.7.2 Inference

class [pyAgrum.CNMonteCarloSampling](#) (*credalNet: pyAgrum.pyAgrum.CredalNet*)

Class used for inferences in credal networks with Monte Carlo sampling algorithm.

Available ructors:

`CNMonteCarloSampling(cn) -> CNMonteCarloSampling`

Parameters `cn` ([pyAgrum.CredalNet](#) (page 140)) – a Credal network

currentTime (*CNMonteCarloSampling self*)

Returns get the current running time in second (double)

Return type double

dynamicExpMax (*CNMonteCarloSampling self, str varName*)

Get the upper dynamic expectation of a given variable prefix.

Parameters `varName` (`str`) – the variable name prefix which upper expectation we want.

Returns a ant reference to the variable upper expectation over all time steps.

Return type double

dynamicExpMin (*CNMonteCarloSampling self, str varName*)

Get the lower dynamic expectation of a given variable prefix.

Parameters `varName` (`str`) – the variable name prefix which lower expectation we want.

Returns a ant reference to the variable lower expectation over all time steps.

Return type double

epsilon (*CNMonteCarloSampling self*)

Returns the value of epsilon

Return type double

history (*CNMonteCarloSampling self*)

Returns the scheme history

Return type tuple

Raises `gum.OperationNotAllowed` – If the scheme did not performed or if verbosity is set to false

insertEvidenceFile (*CNMonteCarloSampling self, str path*)

Insert evidence from file.

Parameters `path` (`str`) – the path to the evidence file.

insertModalsFile (*CNMonteCarloSampling self, str path*)

Insert variables modalities from file to compute expectations.

Parameters **path** (*str*) – The path to the modalities file.

makeInference (*CNMonteCarloSampling self*)

Starts the inference.

marginalMax (*CNMonteCarloSampling self, int id*)

marginalMax(CNMonteCarloSampling self, str name) -> Vector

Get the upper marginals of a given node id.

Parameters

- **id** (*int*) – the node id which upper marginals we want.
- **varName** (*str*) – the variable name which upper marginals we want.

Returns a ant reference to this node upper marginals.

Return type list

Raises *gum.IndexError* – If the node does not belong to the Credal network

marginalMin (*CNMonteCarloSampling self, int id*)

marginalMin(CNMonteCarloSampling self, str name) -> Vector

Get the lower marginals of a given node id.

Parameters

- **id** (*int*) – the node id which lower marginals we want.
- **varName** (*str*) – the variable name which lower marginals we want.

Returns a ant reference to this node lower marginals.

Return type list

Raises *gum.IndexError* – If the node does not belong to the Credal network

maxIter (*CNMonteCarloSampling self*)

Returns the criterion on number of iterations

Return type int

maxTime (*CNMonteCarloSampling self*)

Returns the timeout(in seconds)

Return type double

messageApproximationScheme (*CNMonteCarloSampling self*)

Returns the approximation scheme message

Return type str

minEpsilonRate (*CNMonteCarloSampling self*)

Returns the value of the minimal epsilon rate

Return type double

nbrIterations (*CNMonteCarloSampling self*)

Returns the number of iterations

Return type int

periodSize (*CNMonteCarloSampling self*)

Returns the number of samples between 2 stopping

Return type int

Raises gum.OutOfLowerBound – If p<1

setEpsilon (*CNMonteCarloSampling self, double eps*)

Parameters **eps** (*double*) – the epsilon we want to use

Raises gum.OutOfLowerBound – If eps<0

setMaxIter (*CNMonteCarloSampling self, int max*)

Parameters **max** (*int*) – the maximum number of iteration

Raises gum.OutOfLowerBound – If max <= 1

setMaxTime (*CNMonteCarloSampling self, double timeout*)

Parameters **timeout** (*double*) – stopping criterion on timeout (in seconds)

Raises gum.OutOfLowerBound – If timeout<=0.0

setMinEpsilonRate (*CNMonteCarloSampling self, double rate*)

Parameters **rate** (*double*) – the minimal epsilon rate

setPeriodSize (*CNMonteCarloSampling self, int p*)

Parameters **p** (*int*) – number of samples between 2 stopping

Raises gum.OutOfLowerBound – If p<1

setRepetitiveInd (*CNMonteCarloSampling self, bool flag*)

Parameters **flag** (*bool*) – True if repetitive independence is to be used, false otherwise.
Only usefull with dynamic networks.

setVerbosity (*CNMonteCarloSampling self, bool v*)

Parameters **v** (*bool*) – verbosity

thisown

The membership flag

verbosity (*CNMonteCarloSampling self*)

Returns True if the verbosity is enabled

Return type bool

class pyAgrum.CNLoopyPropagation (*cnet: pyAgrum.pyAgrum.CredalNet*)

Class used for inferences in credal networks with Loopy Propagation algorithm.

Available ructors:

```
CNLoopyPropagation(cn) -> CNLoopyPropagation
```

Parameters **cn** ([pyAgrum.CredalNet](#) (page 140)) – a Credal network

currentTime (*CNLoopyPropagation self*)

Returns get the current running time in second (double)

Return type double

dynamicExpMax (*CNLoopyPropagation self, str varName*)

Get the upper dynamic expectation of a given variable prefix.

Parameters **varName** (*str*) – the variable name prefix which upper expectation we want.

Returns a ant reference to the variable upper expectation over all time steps.

Return type double

dynamicExpMin (*CNLoopyPropagation self, str varName*)

Get the lower dynamic expectation of a given variable prefix.

Parameters **varName** (*str*) – the variable name prefix which lower expectation we want.

Returns a ant reference to the variable lower expectation over all time steps.

Return type double

epsilon (*CNLoopyPropagation self*)

Returns the value of epsilon

Return type double

eraseAllEvidence (*CNLoopyPropagation self*)

Erase all inference related data to perform another one.

You need to insert evidence again if needed but modalities are kept. You can insert new ones by using the appropriate method which will delete the old ones.

history (*CNLoopyPropagation self*)

Returns the scheme history

Return type tuple

Raises `gum.OperationNotAllowed` – If the scheme did not performed or if verbosity is set to false

inferenceType (*CNLoopyPropagation self, pyAgrum.credal::CNLoopyPropagation ::InferenceType infi*)

`inferenceType(CNLoopyPropagation self) -> pyAgrum.credal::CNLoopyPropagation ::InferenceType`

Returns the inference type

Return type int

insertEvidenceFile (*CNLoopyPropagation self, str path*)

Insert evidence from file.

Parameters **path** (*str*) – the path to the evidence file.

insertModalsFile (*CNLoopyPropagation self, str path*)

Insert variables modalities from file to compute expectations.

Parameters **path** (*str*) – The path to the modalities file.

makeInference (*CNLoopyPropagation self*)

Starts the inference.

marginalMax (*CNLoopyPropagation self, int id*)

`marginalMax(CNLoopyPropagation self, str name) -> Vector`

Get the upper marginals of a given node id.

Parameters

- **id** (*int*) – the node id which upper marginals we want.

- **varName** (*str*) – the variable name which upper marginals we want.

Returns a ant reference to this node upper marginals.

Return type list

Raises `gum.IndexError` – If the node does not belong to the Credal network

marginalMin (*CNLoopyPropagation self, int id*)

`marginalMin(CNLoopyPropagation self, str name) -> Vector`

Get the lower marginals of a given node id.

Parameters

- **id** (*int*) – the node id which lower marginals we want.
 - **varName** (*str*) – the variable name which lower marginals we want.
- Returns** a ant reference to this node lower marginals.
- Return type** list
- Raises** gum.IndexError – If the node does not belong to the Credal network
- maxIter** (*CNLoopyPropagation self*)
- Returns** the criterion on number of iterations
- Return type** int
- maxTime** (*CNLoopyPropagation self*)
- Returns** the timeout(in seconds)
- Return type** double
- messageApproximationScheme** (*CNLoopyPropagation self*)
- Returns** the approximation scheme message
- Return type** str
- minEpsilonRate** (*CNLoopyPropagation self*)
- Returns** the value of the minimal epsilon rate
- Return type** double
- nbrIterations** (*CNLoopyPropagation self*)
- Returns** the number of iterations
- Return type** int
- periodSize** (*CNLoopyPropagation self*)
- Returns** the number of samples between 2 stopping
- Return type** int
- Raises** gum.OutOfLowerBound – If p<1
- saveInference** (*CNLoopyPropagation self, str path*)
- Saves marginals.
- Parameters** **path** (*str*) – The path to the file to save marginals.
- setEpsilon** (*CNLoopyPropagation self, double eps*)
- Parameters** **eps** (*double*) – the epsilon we want to use
- Raises** gum.OutOfLowerBound – If eps<0
- setMaxIter** (*CNLoopyPropagation self, int max*)
- Parameters** **max** (*int*) – the maximum number of iteration
- Raises** gum.OutOfLowerBound – If max <= 1
- setMaxTime** (*CNLoopyPropagation self, double timeout*)
- Parameters** **timeout** (*double*) – stopping criterion on timeout (in seconds)
- Raises** gum.OutOfLowerBound – If timeout<=0.0
- setMinEpsilonRate** (*CNLoopyPropagation self, double rate*)
- Parameters** **rate** (*double*) – the minimal epsilon rate
- setPeriodSize** (*CNLoopyPropagation self, int p*)

Parameters **p** (*int*) – number of samples between 2 stopping
Raises `gum.OutOfLowerBound` – If $p < 1$

setRepetitiveInd (*CNLoopyPropagation self, bool flag*)

Parameters **flag** (*bool*) – True if repetitive independence is to be used, false otherwise.
 Only usefull with dynamic networks.

setVerbosity (*CNLoopyPropagation self, bool v*)

Parameters **v** (*bool*) – verbosity

thisown
 The membership flag

verbosity (*CNLoopyPropagation self*)

Returns True if the verbosity is enabled

Return type *bool*

1.8 Influence Diagram

1.8.1 Model

```
class pyAgrum.InfluenceDiagram (*args)
InfluenceDiagram represents an Influence Diagram.
```

Available ructors: `InfluenceDiagram()` -> `InfluenceDiagram`
`InfluenceDiagram(source)` -> `InfluenceDiagram`

Parameters **source** ([pyAgrum.InfluenceDiagram](#) (page 150)) – the InfluenceDiagram to copy

add (*InfluenceDiagram self, DiscreteVariable variable, int id=0*)
 Add a chance variable, it's associate node and it's CPT.

The id of the new variable is automatically generated.

Parameters

- **variable** ([pyAgrum.DiscreteVariable](#) (page 21)) – The variable added by copy.
- **id** (*int*) – The chosen id. If 0, the NodeGraphPart will choose.

Warning: give an id (not 0) should be reserved for rare and specific situations !!!

Returns the id of the added variable.

Return type *int*

Raises `gum.DuplicateElement` – If id($<>0$) is already used

addArc (*InfluenceDiagram self, int tail, int head*)

Add an arc in the ID, and update diagram's potential nodes cpt if necessary.

Parameters

- **tail** (*int*) – the id of the tail node
- **head** (*int*) – the id of the head node

Raises

- gum.InvalidEdge – If arc.tail and/or arc.head are not in the ID.
- gum.InvalidEdge – If tail is a utility node

addChanceNode (*InfluenceDiagram self, DiscreteVariable variable, int id=0*)
 addChanceNode(*InfluenceDiagram self, DiscreteVariable variable, pyAgrum.MultiDimImplementation aContent, int id=0*) -> int

Add a chance variable, it's associate node and it's CPT.

The id of the new variable is automatically generated.

Parameters

- **variable** ([pyAgrum.DiscreteVariable](#) (page 21)) – the variable added by copy.
- **id** (*int*) – the chosen id. If 0, the NodeGraphPart will choose.

Warning: give an id (not 0) should be reserved for rare and specific situations !!!

Returns the id of the added variable.

Return type int

Raises gum.DuplicateElement – If id(<>0) is already used

addDecisionNode (*InfluenceDiagram self, DiscreteVariable variable, int id=0*)
 Add a decision variable.

The id of the new variable is automatically generated.

Parameters

- **variable** ([pyAgrum.DiscreteVariable](#) (page 21)) – the variable added by copy.
- **id** (*int*) – the chosen id. If 0, the NodeGraphPart will choose.

Warning: give an id (not 0) should be reserved for rare and specific situations !!!

Returns the id of the added variable.

Return type int

Raises gum.DuplicateElement – If id(<>0) is already used

addUtilityNode (*InfluenceDiagram self, DiscreteVariable variable, int id=0*)
 addUtilityNode(*InfluenceDiagram self, DiscreteVariable variable, pyAgrum.MultiDimImplementation aContent, int id=0*) -> int

Add a utility variable, it's associate node and it's UT.

The id of the new variable is automatically generated.

Parameters

- **variable** ([pyAgrum.DiscreteVariable](#) (page 21)) – the variable added by copy
- **id** (*int*) – the chosen id. If 0, the NodeGraphPart will choose

Warning: give an id (not 0) should be reserved for rare and specific situations !!!

Returns the id of the added variable.

Return type int

Raises

- gum.InvalidArgument – If variable has more than one label
- gum.DuplicateElement – If id(<>0) is already used

arcs (*InfluenceDiagram self*)

Returns the list of all the arcs in the Influence Diagram.

Return type list

chanceNodeSize (*InfluenceDiagram self*)

Returns the number of chance nodes.

Return type int

changeVariableName (*InfluenceDiagram self, int id, str new_name*)

Parameters

- **id** (int) – the node Id
- **new_name** (str) – the name of the variable

Raises

- gum.DuplicateLabel – If this name already exists
- gum.NotFound – If no nodes matches id.

children (*InfluenceDiagram self, int id*)

Parameters **id** (int) – the id of the parent

Returns the set of all the children

Return type Set

completeInstantiation (*DAGmodel self*)

Get an instantiation over all the variables of the model.

Returns the complete instantiation

Return type pyAgrum.instantiation

cpt (*InfluenceDiagram self, int varId*)

Returns the CPT of a variable.

Parameters **varId** (int) – A variable's id in the pyAgrum.BayesNet.

Returns The variable's CPT.

Return type [pyAgrum.Potential](#) (page 37)

Raises gum.NotFound – If no variable's id matches varId.

dag (*DAGmodel self*)

Returns a ant reference to the dag of this BayesNet.

Return type [pyAgrum.DAG](#) (page 9)

decisionNodeSize (*InfluenceDiagram self*)

Returns the number of decision nodes

Return type int

decisionOrderExists (*InfluenceDiagram self*)

Returns True if a directed path exist with all decision node

Return type bool

empty (*DAGmodel self*)

Returns True if the model is empty

Return type bool

erase (*InfluenceDiagram self, int id*)

erase(*InfluenceDiagram self, DiscreteVariable var*)

Erase a Variable from the network and remove the variable from all his childs.

If no variable matches the id, then nothing is done.

Parameters

- **id** (*int*) – The id of the variable to erase.
- **var** ([pyAgrum.DiscreteVariable](#) (page 21)) – The reference on the variable to remove.

eraseArc (*InfluenceDiagram self, Arc arc*)

eraseArc(*InfluenceDiagram self, int tail, int head*)

Removes an arc in the ID, and update diagram's potential nodes cpt if necessary.

If (tail, head) doesn't exist, the nothing happens.

Parameters

- **arc** ([pyAgrum.Arc](#) (page 5)) – The arc to be removed.
- **tail** (*int*) – the id of the tail node
- **head** (*int*) – the id of the head node

existsPathBetween (*InfluenceDiagram self, int src, int dest*)

Returns true if a path exists between two nodes.

Return type bool

getDecisionGraph (*InfluenceDiagram self*)

Returns the temporal Graph.

Return type [pyAgrum.DAG](#) (page 9)

getDecisionOrder (*InfluenceDiagram self*)

Returns the sequence of decision nodes in the directed path.

Return type list

Raises [NotFound](#) (page 162) – If such a path does not exist

hasSameStructure (*DAGmodel self, DAGmodel other*)

Parameters [pyAgrum.DAGmodel](#) – a direct acyclic model

Returns True if all the named node are the same and all the named arcs are the same

Return type bool

idFromName (*InfluenceDiagram self, str name*)

Returns a variable's id given its name.

Parameters **name** (*str*) – the variable's name from which the id is returned.

Returns the variable's node id.

Return type int

Raises gum.NotFound – If no such name exists in the graph.

ids (*InfluenceDiagram self*)

Note: Deprecated in pyAgrum>0.13.0 Please use nodes() instead

isChanceNode (*InfluenceDiagram self, int varId*)

Parameters **varId** (int) – the tested node id.

Returns true if node is a chance node

Return type bool

isDecisionNode (*InfluenceDiagram self, int varId*)

Parameters **varId** (int) – the tested node id.

Returns true if node is a decision node

Return type bool

isUtilityNode (*InfluenceDiagram self, int varId*)

Parameters **varId** (int) – the tested node id.

Returns true if node is an utility node

Return type bool

loadBIFXML (*InfluenceDiagram self, str name, PyObject * l=(PyObject *) 0*)

Load a BIFXML file.

Parameters **name** (str) – the name's file

Raises

- gum.IOError – If file not found
- gum.FatalError – If file is not valid

log10DomainSize (*DAGmodel self*)

Returns The log10 domain size of the joint probability for the model.

Return type double

moralGraph (*DAGmodel self, bool clear=True*)

Returns the moral graph of the BayesNet, formed by adding edges between all pairs of nodes that have a common child, and then making all edges in the graph undirected.

Returns The moral graph

Return type [pyAgrum.UndiGraph](#) (page 11)

names (*InfluenceDiagram self*)

Returns The names of the InfluenceDiagram variables

Return type list

nodeId (*InfluenceDiagram self, DiscreteVariable var*)

Parameters **var** ([pyAgrum.DiscreteVariable](#) (page 21)) – a variable

Returns the id of the variable

Return type int

Raises `gum.IndexError` – If the InfluenceDiagram does not contain the variable

nodes (*DAGmodel self*)

Returns the set of ids

Return type set

parents (*InfluenceDiagram self, int id*)

Parameters `id` – The id of the child node

Returns the set of the parents ids.

Return type set

saveBIFXML (*InfluenceDiagram self, str name*)

Save the BayesNet in a BIFXML file.

Parameters `name` (`str`) – the file's name

size (*DAGmodel self*)

Returns the number of nodes in the graph

Return type int

sizeArcs (*DAGmodel self*)

Returns the number of arcs in the graph

Return type int

thisown

The membership flag

toDot (*InfluenceDiagram self*)

Returns a friendly display of the graph in DOT format

Return type str

topologicalOrder (*DAGmodel self, bool clear=True*)

Returns the list of the nodes Ids in a topological order

Return type List

Raises `gum.InvalidDirectedCycle` – If this graph contains cycles

utility (*InfluenceDiagram self, int varId*)

Parameters `varId` (`int`) – the tested node id.

Returns the utility table of the node

Return type `pyAgrum.Potential` (page 37)

Raises `gum.IndexError` – If the InfluenceDiagram does not contain the variable

utilityNodeSize (*InfluenceDiagram self*)

Returns the number of utility nodes

Return type int

variable (*InfluenceDiagram self, int id*)

Parameters `id` (`int`) – the node id

Returns a ant reference over a variabe given it's node id

Return type `pyAgrum.DiscreteVariable` (page 21)

Raises `gum.NotFound` – If no variable's id matches the parameter

variableFromName (*InfluenceDiagram self, str name*)

Parameters `name (str)` – a variable's name
Returns the variable
Return type `pyAgrum.DiscreteVariable` (page 21)
Raises `gum.IndexError` – If the InfluenceDiagram does not contain the variable

variableNodeMap (DAGmodel self)
Returns the variable node map
Return type `pyAgrum.variableNodeMap`

1.8.2 Inference

```
class pyAgrum.InfluenceDiagramInference (infDiag:  
                                         pyA-  
                                         grum.pyAgrum.InfluenceDiagram)  
Proxy of C++ pyAgrum.InfluenceDiagramInference class. Proxy of C++ pyA-  
grum.InfluenceDiagramInference class.
```

displayResult (InfluenceDiagramInference self)
 Displays the result of an inference.

displayStrongJunctionTree (InfluenceDiagramInference self, ostream stream=cout)
 Displays on terminal the result of strong junction tree computation for test purpose only.

Parameters `args (TBW)` –

eraseAllEvidence (InfluenceDiagramInference self)
 Removes all the evidence entered into the diagram.

eraseEvidence (InfluenceDiagramInference self, Potential evidence)
Parameters `evidence (pyAgrum.Potential` (page 37)) – the evidence to remove
Raises `gum.IndexError` – If the evidence does not belong to the influence diagram

getBestDecisionChoice (InfluenceDiagramInference self, int decisionId)
 Returns best choice for decision variable given in parameter (based upon MEU criteria)

Parameters `decisionId (int)` – the id of the decision variable
Raises

- `gum.OperationNotAllowed` – If no inference have yet been made
- `gum.InvalidNode` – If node given in parmaeter is not a decision node

getMEU (InfluenceDiagramInference self)
 Returns maximum expected utility obtained from inference.

Raises `gum.OperationNotAllowed` – If no inference have yet been made

influenceDiagram (InfluenceDiagramInference self)
 Returns a ant reference over the InfluenceDiagram on which this class work.

Returns the InfluenceDiagram on which this class work

Return type `pyAgrum.InfluenceDiagram` (page 150)

insertEvidence (InfluenceDiagramInference self, pyAgrum.List< pyAgrum.Potential * > evidenceList)
 Insert new evidence in the graph.

Parameters `evidenceList (list)` – a list of potentials as evidences

Warning: If an evidence already w.r.t. a given node and a new evidence w.r.t. this node is onserted, the old evidence is removed

Raises `gum.OperationNotAllowed` – If an evidence is over more than one variable

junctionTreeToDot (*InfluenceDiagramInference self*)

Returns the result of strong junction tree computation for test purpose only.

Return type str

makeInference (*InfluenceDiagramInference self*)

Makes the inference.

setEvidence (*evidces*)

Erase all the evidences and apply `addEvidence(key,value)` for every pairs in evidces.

Parameters `evidces (dict)` – a dict of evidences

Raises

- `gum.InvalidArgument` – If one value is not a value for the node
- `gum.InvalidArgument` – If the size of a value is different from the domain side of the node
- `gum.FatalError` – If one value is a vector of 0s
- `gum.UndefinedElement` – If one node does not belong to the Bayesian network

thisown

The membership flag

1.9 Other functions from aGrUM

1.9.1 Listeners

aGrUM includes a mechanism for listening to actions (close to QT signal/slot). Some of them have been ported to pyAgrum :

1.9.1.1 LoadListener

Listeners could be added in order to monitor the progress when loading a `pyAgrum.BayesNet`

```
>>> import pyAgrum as gum
>>>
>>> # creating a new listeners
>>> def foo(progress):
>>>     if progress==200:
>>>         print(' BN loaded ')
>>>         return
>>>     elif progress==100:
>>>         car='%'
>>>     elif progress%10==0:
>>>         car='#'
>>>     else:
>>>         car='.'
>>>     print(car,end='',flush=True)
>>>
>>> def bar(progress):
>>>     if progress==50:
>>>         print('50%')
>>>
>>> gum.loadBN('./bn.bif',listeners=[foo,bar])
```

(continues on next page)

(continued from previous page)

```
>>> # .....#.....#.....#..50%
>>> # .....#.....#.....#.....#.....% / bn loaded
```

1.9.1.2 StructuralListener

Listeners could also be added when structural modification are made in a pyAgrum.BayesNet:

```
>>> import pyAgrum as gum
>>>
>>> ## creating a BayesNet
>>> bn=gum.BayesNet()
>>>
>>> ## adding structural listeners
>>> bn.addStructureListener(whenNodeAdded=lambda n,s:print('adding {}:{}'.format(n,
->s)),
->>>                                     whenArcAdded=lambda i,j: print('adding {}->{}'.
->format(i,j)),
->>>                                     whenNodeDeleted=lambda n:print('deleting {}'.
->format(n)),
->>>                                     whenArcDeleted=lambda i,j: print('deleting {}->{}'.
->format(i,j)))
>>>
>>> ## adding another listener for when a node is deleted
>>> bn.addStructureListener(whenNodeDeleted=lambda n: print('yes, really deleting
->'+str(n)))
>>>
>>> ## adding nodes to the BN
>>> l=[bn.add(item,3) for item in 'ABCDE']
>>> # adding 0:A
>>> # adding 1:B
>>> # adding 2:C
>>> # adding 3:D
>>> # adding 4:E
>>>
>>> ## adding arc to the BN
>>> bn.addArc(1,3)
>>> # adding 1->3
>>>
>>> ## removing a node from the BN
>>> bn.erase('C')
>>> # deleting 2
>>> # yes, really deleting 2
```

1.9.1.3 ApproximationSchemeListener

1.9.1.4 DatabaseGenerationListener

1.9.2 Random functions

pyAgrum.**initRandom** (*unsigned int seed=0*)

Initialize random generator seed.

Parameters **seed** (*int*) – the seed used to initialize the random generator

pyAgrum.**randomProba** ()

Returns a random number between 0 and 1 included (i.e. a proba).

Return type double

`pyAgrum.randomDistribution (int n)`

Parameters `n` (`int`) – The number of modalities for the ditribution.

Returns

Return type a random discrete distribution.

1.9.3 OMP functions

`pyAgrum.isOMP ()`

Returns True if OMP has been set at compilation, False otherwise

Return type bool

`pyAgrum.setNumberOfThreads (unsigned int number)`

To avoid spare cycles (less then 100% CPU occupied), use more threads than logical processors (x2 is a good all-around value).

Returns `number` – the number of threads to be used

Return type int

`pyAgrum.getNumberOfLogicalProcessors ()`

Returns the number of logical processors

Return type int

`pyAgrum.getMaxNumberOfThreads ()`

Returns the max number of threads

Return type int

1.10 Exceptions from aGrUM

All the classes inherit GumException's functions `errorType`, `errorCallStack` and `errorContent`.

exception `pyAgrum.DefaultInLabel (*args)`

Proxy of C++ `pyAgrum.DefaultInLabel` class.

thisown

The membership flag

what (`GumException self`)

exception `pyAgrum.DuplicateElement (*args)`

Proxy of C++ `pyAgrum.DuplicateElement` class.

thisown

The membership flag

what (`GumException self`)

exception `pyAgrum.DuplicateLabel (*args)`

Proxy of C++ `pyAgrum.DuplicateLabel` class.

thisown

The membership flag

what (`GumException self`)

exception `pyAgrum.EmptyBSTree (*args)`

Proxy of C++ `pyAgrum.EmptyBSTree` class.

```
thisown
    The membership flag

what (GumException self)

exception pyAgrum.EmptySet (*args)
    Proxy of C++ pyAgrum.EmptySet class.

thisown
    The membership flag

what (GumException self)

exception pyAgrum.GumException (*args)
    Proxy of C++ pyAgrum.Exception class.

errorCallStack (GumException self)
    Returns the error call stack
    Return type str

errorContent (GumException self)
    Returns the error content
    Return type str

errorType (GumException self)
    Returns the error type
    Return type str

thisown
    The membership flag

what (GumException self)

exception pyAgrum.FatalError (*args)
    Proxy of C++ pyAgrum.FatalError class.

thisown
    The membership flag

what (GumException self)

exception pyAgrum.FormatNotFound (*args)
    Proxy of C++ pyAgrum.FormatNotFound class.

thisown
    The membership flag

what (GumException self)

exception pyAgrum.GraphError (*args)
    Proxy of C++ pyAgrum.GraphError class.

thisown
    The membership flag

what (GumException self)

exception pyAgrum.IOError (*args)
    Proxy of C++ pyAgrum.IOError class.

thisown
    The membership flag

what (GumException self)

exception pyAgrum.IdError (*args)
    Proxy of C++ pyAgrum.IdError class.
```

```

thisown
    The membership flag

what (GumException self)

exception pyAgrum.InvalidArc (*args)
    Proxy of C++ pyAgrum.InvalidArc class.

thisown
    The membership flag

what (GumException self)

exception pyAgrum.InvalidArgument (*args)
    Proxy of C++ pyAgrum.InvalidArgument class.

thisown
    The membership flag

what (GumException self)

exception pyAgrum.InvalidArgumentsNumber (*args)
    Proxy of C++ pyAgrum.InvalidArgumentsNumber class.

thisown
    The membership flag

what (GumException self)

exception pyAgrum.InvalidDirectedCycle (*args)
    Proxy of C++ pyAgrum.InvalidDirectedCycle class.

thisown
    The membership flag

what (GumException self)

exception pyAgrum.InvalidEdge (*args)
    Proxy of C++ pyAgrum.InvalidEdge class.

thisown
    The membership flag

what (GumException self)

exception pyAgrum.InvalidNode (*args)
    Proxy of C++ pyAgrum.InvalidNode class.

thisown
    The membership flag

what (GumException self)

exception pyAgrum.NoChild (*args)
    Proxy of C++ pyAgrum.NoChild class.

thisown
    The membership flag

what (GumException self)

exception pyAgrum.NoNeighbour (*args)
    Proxy of C++ pyAgrum.NoNeighbour class.

thisown
    The membership flag

what (GumException self)

exception pyAgrum.NoParent (*args)
    Proxy of C++ pyAgrum.NoParent class.

```

```
thisown
    The membership flag
what (GumException self)
```

exception pyAgrum.**NotFound**(*args)
 Proxy of C++ pyAgrum.NotFound class.

```
thisown
    The membership flag
what (GumException self)
```

exception pyAgrum.**NullElement**(*args)
 Proxy of C++ pyAgrum.NullElement class.

```
thisown
    The membership flag
what (GumException self)
```

exception pyAgrum.**OperationNotAllowed**(*args)
 Proxy of C++ pyAgrum.OperationNotAllowed class.

```
thisown
    The membership flag
what (GumException self)
```

exception pyAgrum.**OutOfBounds**(*args)
 Proxy of C++ pyAgrum.OutOfBounds class.

```
thisown
    The membership flag
what (GumException self)
```

exception pyAgrum.**OutOfLowerBound**(*args)
 Proxy of C++ pyAgrum.OutOfLowerBound class.

```
thisown
    The membership flag
what (GumException self)
```

exception pyAgrum.**OutOfUpperBound**(*args)
 Proxy of C++ pyAgrum.OutOfUpperBound class.

```
thisown
    The membership flag
what (GumException self)
```

exception pyAgrum.**ReferenceError**(*args)
 Proxy of C++ pyAgrum.ReferenceError class.

```
thisown
    The membership flag
what (GumException self)
```

exception pyAgrum.**SizeError**(*args)
 Proxy of C++ intError class.

```
thisown
    The membership flag
what (GumException self)
```

exception pyAgrum.**SyntaxError**(*args)
 Proxy of C++ pyAgrum.SyntaxError class.

```
col (SyntaxError self)
    Returns the indice of the colonne of the error
    Return type int

line (SyntaxError self)
    Returns the indice of the line of the error
    Return type int

thisown
    The membership flag

what (GumException self)
exception pyAgrum.UndefinedElement (*args)
    Proxy of C++ pyAgrum.UndefinedElement class.

thisown
    The membership flag

what (GumException self)
exception pyAgrum.UndefinedIteratorKey (*args)
    Proxy of C++ pyAgrum.UndefinedIteratorKey class.

thisown
    The membership flag

what (GumException self)
exception pyAgrum.UndefinedIteratorValue (*args)
    Proxy of C++ pyAgrum.UndefinedIteratorValue class.

thisown
    The membership flag


what (GumException self)
exception pyAgrum.UnknownLabelInDatabase (*args)
    Proxy of C++ pyAgrum.UnknownLabelInDatabase class.
```


CHAPTER 2

Python helpers : pyAgrum.lib

`pyAgrum.lib` is a set of python tools.

2.1 Module notebook



2.1.1 Helpers

2.1.2 Visualization of Potentials

2.1.3 Visualization of graphs

2.1.4 Visualization of graphical models

2.1.5 Visualization of approximation algorithm

2.2 Module bn2graph

```
pyAgrum.lib.bn2graph.BN2dot (bn,    size='4',    nodeColor=None,    arcWidth=None,    ar-
                             cColor=None,      cmapNode=None,      cmapArc=None,
                             showMsg=None)
```

create a pydotplus representation of the BN

Parameters

- **bn** ([pyAgrum.BayesNet](#) (page 43)) –
- **size** (*string*) – size of the rendered graph
- **nodeColor** – a nodeMap of values (between 0 and 1) to be shown as color of nodes (with special colors for 0 and 1)

:param arcWidth: a arcMap of values to be shown as width of arcs :param arcColor: a arcMap of values (between 0 and 1) to be shown as color of arcs :param cmapNode: color map to show the vals of Nodes :param cmapArc: color map to show the vals of Arcs. :param showMsg: a nodeMap of values to be shown as tooltip

Returns the desired representation of the BN as a dot graph

```
pyAgrum.lib.bn2graph.BNinference2dot (bn,    size='4',    engine=None,    evs={},    targets={},
                                         format='png',    nodeColor=None,    arcWidth=None,
                                         cmap=None)
```

create a pydotplus representation of an inference in a BN

Parameters

- **bn** ([pyAgrum.BayesNet](#) (page 43)) –
- **size** (*string*) – size of the rendered graph
- **Inference engine** (*pyAgrum*) – inference algorithm used. If None, LazyPropagation will be used
- **evs** (*dict*) – map of evidence
- **targets** (*set*) – set of targets. If targets={} then each node is a target
- **format** (*string*) – render as “png” or “svg”
- **nodeColor** – a nodeMap of values to be shown as color nodes (with special color for 0 and 1)
- **arcWidth** – a arcMap of values to be shown as bold arcs
- **cmap** – color map to show the vals

Returns the desired representation of the inference

```
pyAgrum.lib.bn2graph.dotize (aBN, name, format='pdf')
```

From a bn, creates an image of the BN

Parameters

- **bn** ([pyAgrum.BayesNet](#) (page 43)) – the bayes net to show
- **name** (*string*) – the filename (without extension) for the image
- **format** (*string*) – format in ['pdf','png','fig','jpg','svg']

`pyAgrum.lib.bn2graph.pdfize(aBN, name)`

From a bn, creates a pdf of the BN

Parameters

- **bn** ([pyAgrum.BayesNet](#) (page 43)) – the bayes net to show
- **name** (*string*) – the filename (without extension) for the image

`pyAgrum.lib.bn2graph.pngize(aBN, name)`

From a bn, creates a png of the BN

Parameters

- **bn** ([pyAgrum.BayesNet](#) (page 43)) – the bayes net to show
- **name** (*string*) – the filename (without extension) for the image

`pyAgrum.lib.bn2graph.proba2histo(p, scale=1.0)`

compute the representation of an histogram for a mono-dim Potential

Parameters **p** ([pyAgrum.Potential](#) (page 37)) – the mono-dim Potential

Returns a matplotlib histogram for a Potential p.

```

1 bn = gum.fastBN("a->b->d; a->c->d->e; f->b")
2 g = BNinference2dot(bn,
3                         targets=['f', 'd'],
4                         vals={'a': 1,
5                               'b': 0.3,
6                               'c': 0.3,
7                               'd': 0.1,
8                               'e': 0.1,
9                               'f': 0.3},
10                        arcvals={(0, 1): 2,
11                               (0, 2): 0.5})
12 g.write("test.png", format='png')
```

2.2.1 Visualization of Potentials

`pyAgrum.lib.bn2graph.proba2histo(p, scale=1.0)`
compute the representation of an histogram for a mono-dim Potential

Parameters **p** ([pyAgrum.Potential](#) (page 37)) – the mono-dim Potential

Returns a matplotlib histogram for a Potential p.

2.2.2 Visualization of Bayesian Networks

`pyAgrum.lib.bn2graph.BN2dot(bn, size='4', nodeColor=None, arcWidth=None, arcColor=None, cmapNode=None, cmapArc=None, showMsg=None)`
create a pydotplus representation of the BN

Parameters

- **bn** ([pyAgrum.BayesNet](#) (page 43)) –

- **size** (*string*) – size of the rendered graph
- **nodeColor** – a nodeMap of values (between 0 and 1) to be shown as color of nodes (with special colors for 0 and 1) :param arcWidth: a arcMap of values to be shown as width of arcs :param arcColor: a arcMap of values (between 0 and 1) to be shown as color of arcs :param cmapNode: color map to show the vals of Nodes :param cmapArc: color map to show the vals of Arcs. :param showMsg: a nodeMap of values to be shown as tooltip

Returns the desired representation of the BN as a dot graph

```
pyAgrum.lib.bn2graph.BNinference2dot (bn, size='4', engine=None, evs={}, targets={}, format='png', nodeColor=None, arcWidth=None, cmap=None)
```

create a pydotplus representation of an inference in a BN

Parameters

- **bn** ([pyAgrum.BayesNet](#) (page 43)) –
- **size** (*string*) – size of the rendered graph
- **Inference engine** ([pyAgrum](#)) – inference algorithm used. If None, LazyPropagation will be used
- **evs** (*dictioinary*) – map of evidence
- **targets** (*set*) – set of targets. If targets={} then each node is a target
- **format** (*string*) – render as “png” or “svg”
- **nodeColor** – a nodeMap of values to be shown as color nodes (with special color for 0 and 1)
- **arcWidth** – a arcMap of values to be shown as bold arcs
- **cmap** – color map to show the vals

Returns the desired representation of the inference

2.2.3 Hi-level functions

```
pyAgrum.lib.bn2graph.dotize (aBN, name, format='pdf')
```

From a bn, creates an image of the BN

Parameters

- **bn** ([pyAgrum.BayesNet](#) (page 43)) – the bayes net to show
- **name** (*string*) – the filename (without extension) for the image
- **format** (*string*) – format in [‘pdf’, ‘png’, ‘fig’, ‘jpg’, ‘svg’]

```
pyAgrum.lib.bn2graph.pngize (aBN, name)
```

From a bn, creates a png of the BN

Parameters

- **bn** ([pyAgrum.BayesNet](#) (page 43)) – the bayes net to show
- **name** (*string*) – the filename (without extension) for the image


`pyAgrum.lib.bn2graph.pdfize(aBN, name)`

From a bn, creates a pdf of the BN

Parameters

- `bn` (`pyAgrum.BayesNet` (page 43)) – the bayes net to show
- `name` (`string`) – the filename (without extension) for the image

2.3 Module dynamic bayesian network



2.4 other pyAgrum.lib modules

2.4.1 bn2roc

`pyAgrum.lib.bn2roc.module_help(exit_value=1, message="")`

defines help viewed if args are not OK on command line, and
exit with `exit_value`

`pyAgrum.lib.bn2roc.showROC(bn, csv_name, variable, label, visible=True, show_fig=False, with_labels=True)`

Compute the ROC curve and save the result in the folder of the

csv file.

Parameters

- **bn** (`pyAgrum.BayesNet` (page 43)) – a bayesian network
- **csv_name** (`str`) – a csv filename
- **target** (`str`) – the target
- **label** (`str`) – the target label
- **visible** (`bool`) – indicates if the resulting curve must be printed

2.4.2 bn2csv

Samples generation w.r.t to a probability distribution represented by a Bayesian network.

class `pyAgrum.lib.bn2csv.CSVGenerator`
Bases: `object`

Class for samples generation w.r.t to a probability distribution represented by a Bayesian network.

caching_probas (`bn, node_id, n, par`)

Parameters

- **bn** (`pyAgrum.BayesNet` (page 43)) – a Bayesian network
- **node_id** (`int`) – a node id
- **n** (`int`) – a node id
- **par** (`list`) – the node's parents

Returns the node's probabilities

Return type list

cachingnameAndParents (`bn, n`)

Compute a list of parents for node n in BN bn.

Parameters

- **bn** (`pyAgrum.BayesNet` (page 43)) – a Bayesian network
- **n** – (int) a node id
- **n** – (str) a node name

Returns a couple of name of n and list of parents names

Return type tuple

static draw (`tab`)

draw a value using tab as probability table.

Parameters `tab` (`list`) – a probability table

Returns the couple (i,proba)

Return type tuple

static nameAndParents (`bn, n`)

Compute a list of parents for node n in BN bn.

Parameters

- **bn** (`pyAgrum.BayesNet` (page 43)) – a Bayesian network
- **n** – (int) a node id
- **n** – (str) a node name

Returns a couple of name of n and list of parents names

Return type tuple

Raises `gum.IndexError` – If the node is not in the Bayesian network

`newSample(bn, seq)`

Generate a sample w.r.t to the bn using the variable sequence seq (topological order)

Parameters

- **bn** (`pyAgrum.BayesNet` (page 43)) – a Bayesian network
- **seq** (*list*) – a variable sequence

Returns the couple (sample,log2-likelihood)

Return type tuple

`proceed(name_in, name_out, n, visible, with_labels)`

From the file name_in (BN file), generate n samples and save them in name_out

Parameters

- **name_in** (*str*) – a file name
- **name_out** (*str*) – the output file
- **n** (*int*) – the number of samples
- **visible** (*bool*) – indicate if a progress bar should be displayed
- **with_labels** (*bool*) – indicate if values should be labelled or not

Returns the log2-likelihood of the n samples database

Return type double

`pyAgrum.lib.bn2csv.generateCSV(name_in, name_out, n, visible=False, with_labels=True)`

From the file name_in (BN file), generate n samples and save them in name_out

Parameters

- **name_in** (*str*) – a file name
- **name_out** (*str*) – the output file
- **n** (*int*) – the number of samples
- **visible** (*bool*) – indicate if a progress bar should be displayed
- **with_labels** (*bool*) – indicate if values should be labelled or not

Returns the log2-likelihood of the n samples database

Return type double

```
pyAgrum.lib.bn2csv.module_help(exit_value=1)
    defines help viewed if args are not OK on command line, and
    exit with exit_value
```

2.4.3 bn2scores

```
pyAgrum.lib.bn2scores.checkCompatibility(bn, fields, csv_name)
    check if variables of the bn are in the fields

    if not : return None if compatibility : return a list of position for
    variables in fields

pyAgrum.lib.bn2scores.computeScores(bn_name, csv_name, visible=False, transforme_label=None)

pyAgrum.lib.bn2scores.getNumLabel(inst, i, label, transforme_label)

pyAgrum.lib.bn2scores.lines_count(filename)
    count lines in a file

pyAgrum.lib.bn2scores.module_help(exit_value=1)
    defines help viewed if args are not OK on command line, and
    exit with exit_value

pyAgrum.lib.bn2scores.stringify(s)
```

2.4.4 bn_vs_bn

```
class pyAgrum.lib.bn_vs_bn.GraphicalBNComparator(name1, name2, delta=1e-06)
Bases: object
```

BNGraphicalComparator allows to compare in multiple way 2 BNs... The smallest assumption is that the names of the variables are the same in the 2 BNs. But some comparisons will have also to check the type and domainSize of the variables. The bns have not exactly the same role : _bn1 is rather the referent model for the comparison whereas _bn2 is the compared one to the referent model

Parameters

- **name1** (*str or pyAgrum.BayesNet* (page 43)) – a BN or a filename for reference
- **name2** (*str or pyAgrum.BayesNet* (page 43)) – another BN or another filename for comparison

dotDiff()

Return a pydotplus graph that compares the arcs of _bn1 (reference) with those of self._bn2. full black line: the arc is common for both full red line: the arc is common but inverted in _bn2 dotted black line: the arc is added in _bn2 dotted red line: the arc is removed in _bn2

Returns the result dot graph

Return type pydotplus.Dot

equivalentBNs()

Check if the 2 BNs are equivalent :

- same variables

- same graphical structure
- same parameters

Returns “OK” if bn are the same, a description of the error otherwise

Return type str

scores()

Compute Precision, Recall, F-score for self._bn2 compared to self._bn1

precision and recall are computed considering BN1 as the reference

Fscore is $2 * (\text{recall} * \text{precision}) / (\text{recall} + \text{precision})$ and is the weighted average of Precision and Recall.

dist2opt=square root of $(1 - \text{precision})^2 + (1 - \text{recall})^2$ and represents the euclidian distance to the ideal point (precision=1, recall=1)

Returns A dictionary containing ‘precision’, ‘recall’, ‘fscore’, ‘dist2opt’ and so on.

Return type dict[str,double]

`pyAgrum.lib.bn_vs_bn.module_help(exit_value=1)`
defines help viewed if args are not OK on command line, and exit with exit_value

2.4.5 pretty_print

`pyAgrum.lib.pretty_print.bn2txt(aBN)`
Representation of all CPTs of a gum.BayesNet

Parameters `aBN` – the bayes net or the name of the file

Returns

`pyAgrum.lib.pretty_print.cpt2txt(cpt, digits=4)`
string representation of a gum.Potential

Parameters `cpt` – the Potential to represent

Returns the string representation

`pyAgrum.lib.pretty_print.max_length(v)`

`pyAgrum.lib.pretty_print.module_help(exit_value=1)`
defines help viewed if args are not OK on command line, and exit with exit_value

CHAPTER 3

Indices and tables

- genindex
- modindex
- search

CHAPTER 4

Documentation tools

4.1 Read me/To do

4.1.1 Read me

The following command is used in order to check the completion of the documentation :

```
python act guideline
```

OPTIONS –correction to display the undocumented methods

Lists of methods and classes to skip are defined in the missingDocs python script (in acttools).

4.1.2 To do

4.1.2.1 Type issues

CredalNet.credalNet_currentCpt (issue with return type)

CredalNet.credalNet_srcCPt (issue with return type)

CredalNet.get_CPT_max (issue with return type)

CredalNet.get_CPT_min (issue with return type)

CredalNet.setCPT (issue with parameter type)

CredalNet.setCPTs (issue with parameter type)

InfluenceDiagramInference.displayStrongJunctionTree (issue with parameter type)

LazyPropagation.setTriangulation (issue with parameter type, Triangulation is not a wrapped object)

BayesNet.variableNodeMap (issue with return type, VariableNodeMap is not a wrapped object)

4.1.2.2 Exception issues

RangeVar.setMinVal(new_minval) (resp. setMaxVal(new_maxval)) should raise an exception if new_minval>maxval (resp. new_maxval<minval)

Potential.add should raise an exception when a DiscretizedVariable is added without any tick.

4.1.2.3 Methods to add

- gum::LabelizedVariable::addLabels
- gum::DiscretizedVariable::addTicks

4.1.2.4 Methods to overload

hasHardEvidence with a node id in parameter (instead of a node name)

4.1.2.5 Other issues

gum.CredalNet.dynamicExceptions needed in order to make dynamicExpMax and dynamicExpMin work.

Can't document MarkovBlanket and EssentialGraph for unknown reason.

Version of addChanceNode and addUtilityNode with a multiDimImplementation as parameter should be disabled as the object isn't wrapped.

Python Module Index

p

`pyAgrum.lib.bn2graph`, 166

A

about () (*in module pyAgrum*), 3
abs () (*pyAgrum.Potential method*), 37
add () (*pyAgrum.BayesNet method*), 43
add () (*pyAgrum.InfluenceDiagram method*), 150
add () (*pyAgrum.Instantiation method*), 32
add () (*pyAgrum.Potential method*), 37
addAllTargets () (*pyAgrum.GibbsSampling method*), 79
addAllTargets () (*pyAgrum.ImportanceSampling method*), 98
addAllTargets () (*pyAgrum.LazyPropagation method*), 55
addAllTargets () (*pyAgrum.LoopyBeliefPropagation method*), 73
addAllTargets () (*pyAgrum.LoopyGibbsSampling method*), 104
addAllTargets () (*pyAgrum.LoopyImportanceSampling method*), 123
addAllTargets () (*pyAgrum.LoopyMonteCarloSampling method*), 111
addAllTargets () (*pyAgrum.LoopyWeightedSampling method*), 117
addAllTargets () (*pyAgrum.MonteCarloSampling method*), 86
addAllTargets () (*pyAgrum.ShaferShenoyInference method*), 61
addAllTargets () (*pyAgrum.VariableElimination method*), 68
addAllTargets () (*pyAgrum.WeightedSampling method*), 92
addAMPLITUDE () (*pyAgrum.BayesNet method*), 43
addAND () (*pyAgrum.BayesNet method*), 43
addArc () (*pyAgrum.BayesNet method*), 43
addArc () (*pyAgrum.CredalNet method*), 140
addArc () (*pyAgrum.DAG method*), 9
addArc () (*pyAgrum.DiGraph method*), 6
addArc () (*pyAgrum.InfluenceDiagram method*), 150
addArc () (*pyAgrum.MixedGraph method*), 17
addChanceNode () (*pyAgrum.InfluenceDiagram method*), 151
addCOUNT () (*pyAgrum.BayesNet method*), 44
addDecisionNode () (*pyAgrum.InfluenceDiagram method*), 151
addEdge () (*pyAgrum.CliqueGraph method*), 13
addEdge () (*pyAgrum.MixedGraph method*), 17
addEdge () (*pyAgrum.UndiGraph method*), 11
addEvidence () (*pyAgrum.GibbsSampling method*), 79
addEvidence () (*pyAgrum.ImportanceSampling method*), 98
addEvidence () (*pyAgrum.LazyPropagation method*), 55
addEvidence () (*pyAgrum.LoopyBeliefPropagation method*), 73
addEvidence () (*pyAgrum.LoopyGibbsSampling method*), 104
addEvidence () (*pyAgrum.LoopyImportanceSampling method*), 123
addEvidence () (*pyAgrum.LoopyMonteCarloSampling method*), 111
addEvidence () (*pyAgrum.LoopyWeightedSampling method*), 117
addEvidence () (*pyAgrum.MonteCarloSampling method*), 86
addEvidence () (*pyAgrum.ShaferShenoyInference method*), 61
addEvidence () (*pyAgrum.VariableElimination method*), 68
addEvidence () (*pyAgrum.WeightedSampling method*), 92
addEXISTS () (*pyAgrum.BayesNet method*), 44
addFORALL () (*pyAgrum.BayesNet method*), 44
addForbiddenArc () (*pyAgrum.BNLearnert method*), 129
addJointTarget () (*pyAgrum.LazyPropagation method*), 56
addJointTarget () (*pyAgrum.ShaferShenoyInference method*),

62
 addJointTarget() (pyAgrum.VariableElimination method), 68
 addLabel() (pyAgrum.LabelizedVariable method), 23
 addLogit() (pyAgrum.BayesNet method), 44
 addMandatoryArc() (pyAgrum.BNLearnert method), 130
 addMAX() (pyAgrum.BayesNet method), 44
 addMEDIAN() (pyAgrum.BayesNet method), 45
 addMIN() (pyAgrum.BayesNet method), 45
 addNode() (pyAgrum.CliqueGraph method), 13
 addNode() (pyAgrum.DAG method), 9
 addNode() (pyAgrum.DiGraph method), 6
 addNode() (pyAgrum.MixedGraph method), 17
 addNode() (pyAgrum.UndiGraph method), 11
 addNodes() (pyAgrum.CliqueGraph method), 13
 addNodes() (pyAgrum.DAG method), 9
 addNodes() (pyAgrum.DiGraph method), 7
 addNodes() (pyAgrum.MixedGraph method), 17
 addNodes() (pyAgrum.UndiGraph method), 11
 addNodeWithId() (pyAgrum.CliqueGraph method), 13
 addNodeWithId() (pyAgrum.DAG method), 9
 addNodeWithId() (pyAgrum.DiGraph method), 7
 addNodeWithId() (pyAgrum.MixedGraph method), 17
 addNodeWithId() (pyAgrum.UndiGraph method), 11
 addNoisyAND() (pyAgrum.BayesNet method), 45
 addNoisyOR() (pyAgrum.BayesNet method), 45
 addNoisyORCompound() (pyAgrum.BayesNet method), 45
 addNoisyORNet() (pyAgrum.BayesNet method), 46
 addOR() (pyAgrum.BayesNet method), 46
 addPossibleEdge() (pyAgrum.BNLearnert method), 130
 addStructureListener() (pyAgrum.BayesNet method), 46
 addTarget() (pyAgrum.GibbsSampling method), 80
 addTarget() (pyAgrum.ImportanceSampling method), 99
 addTarget() (pyAgrum.LazyPropagation method), 56
 addTarget() (pyAgrum.LoopyBeliefPropagation method), 74
 addTarget() (pyAgrum.LoopyGibbsSampling method), 105
 addTarget() (pyAgrum.LoopyImportanceSampling method), 124
 addTarget() (pyAgrum.LoopyMonteCarloSampling method), 111
 addTarget() (pyAgrum.LoopyWeightedSampling method), 118
 addTarget() (pyAgrum.MonteCarloSampling method), 86
 addTarget() (pyAgrum.ShaferShenoyInference method), 62
 addTarget() (pyAgrum.VariableElimination method), 68
 addTarget() (pyAgrum.WeightedSampling method), 92
 addTick() (pyAgrum.DiscretizedVariable method), 26
 addToClique() (pyAgrum.CliqueGraph method), 14
 addUtilityNode() (pyAgrum.InfluenceDiagram method), 151
 addVariable() (pyAgrum.CredalNet method), 140
 addWeightedArc() (pyAgrum.BayesNet method), 47
 aggType (pyAgrum.PRMexplorer attribute), 136
 approximatedBinarization() (pyAgrum.CredalNet method), 140
 Arc (class in pyAgrum), 5
 arcs() (pyAgrum.BayesNet method), 47
 arcs() (pyAgrum.DAG method), 9
 arcs() (pyAgrum.DiGraph method), 7
 arcs() (pyAgrum.InfluenceDiagram method), 152
 arcs() (pyAgrum.MixedGraph method), 17
 argmax() (pyAgrum.Potential method), 37
 argmin() (pyAgrum.Potential method), 37
 availableBNExts() (in module pyAgrum), 4

B

BayesNet (class in pyAgrum), 43
 beginTopologyTransformation() (pyAgrum.BayesNet method), 47
 belongs() (pyAgrum.RangeVariable method), 29
 BN() (pyAgrum.GibbsSampling method), 79
 BN() (pyAgrum.ImportanceSampling method), 98
 BN() (pyAgrum.LazyPropagation method), 55
 BN() (pyAgrum.LoopyBeliefPropagation method), 73
 BN() (pyAgrum.LoopyGibbsSampling method), 104
 BN() (pyAgrum.LoopyImportanceSampling method), 123
 BN() (pyAgrum.LoopyMonteCarloSampling method), 111
 BN() (pyAgrum.LoopyWeightedSampling method), 117
 BN() (pyAgrum.MonteCarloSampling method), 86
 BN() (pyAgrum.ShaferShenoyInference method), 61
 BN() (pyAgrum.VariableElimination method), 67
 BN() (pyAgrum.WeightedSampling method), 92
 BN2dot() (in module pyAgrum.lib.bn2graph), 166, 167
 BNinference2dot() (in module pyAgrum.lib.bn2graph), 166, 168
 BNLearnert (class in pyAgrum), 129
 bnToCredal() (pyAgrum.CredalNet method), 140
 burnIn() (pyAgrum.GibbsSampling method), 80
 burnIn() (pyAgrum.LoopyGibbsSampling method), 105

C

chanceNodeSize() (*pyAgrum.InfluenceDiagram method*), 152
 changeLabel() (*pyAgrum.LabelizedVariable method*), 24
 changePotential() (*pyAgrum.BayesNet method*), 47
 changeVariableLabel() (*pyAgrum.BayesNet method*), 47
 changeVariableName() (*pyAgrum.BayesNet method*), 48
 changeVariableName() (*pyAgrum.InfluenceDiagram method*), 152
 chgEvidence() (*pyAgrum.GibbsSampling method*), 80
 chgEvidence() (*pyAgrum.ImportanceSampling method*), 99
 chgEvidence() (*pyAgrum.LazyPropagation method*), 56
 chgEvidence() (*pyAgrum.LoopyBeliefPropagation method*), 74
 chgEvidence() (*pyAgrum.LoopyGibbsSampling method*), 105
 chgEvidence() (*pyAgrum.LoopyImportanceSampling method*), 124
 chgEvidence() (*pyAgrum.LoopyMonteCarloSampling method*), 112
 chgEvidence() (*pyAgrum.LoopyWeightedSampling method*), 118
 chgEvidence() (*pyAgrum.MonteCarloSampling method*), 86
 chgEvidence() (*pyAgrum.ShaferShenoyInference method*), 62
 chgEvidence() (*pyAgrum.VariableElimination method*), 68
 chgEvidence() (*pyAgrum.WeightedSampling method*), 93
 chgVal() (*pyAgrum.Instantiation method*), 32
 chi2() (*pyAgrum.BNLearner method*), 130
 children() (*pyAgrum.BayesNet method*), 48
 children() (*pyAgrum.DAG method*), 9
 children() (*pyAgrum.DiGraph method*), 7
 children() (*pyAgrum.InfluenceDiagram method*), 152
 children() (*pyAgrum.MixedGraph method*), 18
 classAggregates() (*pyAgrum.PRMexplorer method*), 136
 classAttributes() (*pyAgrum.PRMexplorer method*), 136
 classDag() (*pyAgrum.PRMexplorer method*), 136
 classes() (*pyAgrum.PRMexplorer method*), 137
 classImplements() (*pyAgrum.PRMexplorer method*), 136
 classParameters() (*pyAgrum.PRMexplorer method*), 136
 classReferences() (*pyAgrum.PRMexplorer method*), 136
 classSlotChains() (*pyAgrum.PRMexplorer method*), 137
 clear() (*pyAgrum.CliqueGraph method*), 14
 clear() (*pyAgrum.DAG method*), 9
 clear() (*pyAgrum.DiGraph method*), 7
 clear() (*pyAgrum.Instantiation method*), 33
 clear() (*pyAgrum.MixedGraph method*), 18
 clear() (*pyAgrum.UndiGraph method*), 11
 clearEdges() (*pyAgrum.CliqueGraph method*), 14
 clique() (*pyAgrum.CliqueGraph method*), 14
 CliqueGraph (*class in pyAgrum*), 13
 CNLoopyPropagation (*class in pyAgrum*), 147
 CNMonteCarloSampling (*class in pyAgrum*), 145
 col() (*pyAgrum.SyntaxError method*), 162
 completeInstantiation() (*pyAgrum.BayesNet method*), 48
 completeInstantiation() (*pyAgrum.InfluenceDiagram method*), 152
 computeCPTMinMax() (*pyAgrum.CredalNet method*), 141
 container() (*pyAgrum.CliqueGraph method*), 14
 containerPath() (*pyAgrum.CliqueGraph method*), 14
 contains() (*pyAgrum.Instantiation method*), 33
 contains() (*pyAgrum.Potential method*), 37
 cpt() (*pyAgrum.PRMexplorer method*), 137
 cpt() (*pyAgrum.BayesNet method*), 48
 cpt() (*pyAgrum.InfluenceDiagram method*), 152
 CredalNet (*class in pyAgrum*), 140
 credalNet_currentCpt() (*pyAgrum.CredalNet method*), 141
 credalNet_srcCpt() (*pyAgrum.CredalNet method*), 141
 current.bn() (*pyAgrum.CredalNet method*), 141
 currentNodeType() (*pyAgrum.CredalNet method*), 141
 currentPosterior() (*pyAgrum.GibbsSampling method*), 80
 currentPosterior() (*pyAgrum.ImportanceSampling method*), 99
 currentPosterior() (*pyAgrum.LoopyGibbsSampling method*), 106
 currentPosterior() (*pyAgrum.LoopyImportanceSampling method*), 124
 currentPosterior() (*pyAgrum.LoopyMonteCarloSampling method*), 112
 currentPosterior() (*pyAgrum.LoopyWeightedSampling method*), 118
 currentPosterior() (*pyAgrum.MonteCarloSampling method*), 87
 currentPosterior() (*pyAgrum.WeightedSampling method*), 93
 currentTime() (*pyAgrum.BNLearner method*),

<p>130 currentTime() (<i>pyAgrum.CNLoopyPropagation method</i>), 147 currentTime() (<i>pyAgrum.CNMonteCarloSampling method</i>), 145 currentTime() (<i>pyAgrum.GibbsSampling method</i>), 81 currentTime() (<i>pyAgrum.ImportanceSampling method</i>), 99 currentTime() (<i>pyAgrum.LoopyBeliefPropagation method</i>), 74 currentTime() (<i>pyAgrum.LoopyGibbsSampling method</i>), 106 currentTime() (<i>pyAgrum.LoopyImportanceSampling method</i>), 124 currentTime() (<i>pyAgrum.LoopyMonteCarloSampling method</i>), 112 currentTime() (<i>pyAgrum.LoopyWeightedSampling method</i>), 118 currentTime() (<i>pyAgrum.MonteCarloSampling method</i>), 87 currentTime() (<i>pyAgrum.WeightedSampling method</i>), 93</p>	<p>156 displayStrongJunctionTree() (<i>pyAgrum.InfluenceDiagramInference method</i>), 156 domain() (<i>pyAgrum.DiscreteVariable method</i>), 21 domain() (<i>pyAgrum.DiscretizedVariable method</i>), 26 domain() (<i>pyAgrum.LabelizedVariable method</i>), 24 domain() (<i>pyAgrum.RangeVariable method</i>), 29 domainSize() (<i>pyAgrum.CredalNet method</i>), 141 domainSize() (<i>pyAgrum.DiscreteVariable method</i>), 21 domainSize() (<i>pyAgrum.DiscretizedVariable method</i>), 26 domainSize() (<i>pyAgrum.Instantiation method</i>), 33 domainSize() (<i>pyAgrum.LabelizedVariable method</i>), 24 domainSize() (<i>pyAgrum.RangeVariable method</i>), 29 dotize() (<i>in module pyAgrum.lib.bn2graph</i>), 166, 168 draw() (<i>pyAgrum.Potential method</i>), 37 DuplicateElement, 159 DuplicateLabel, 159 dynamicExpMax() (<i>pyAgrum.CNLoopyPropagation method</i>), 147 dynamicExpMax() (<i>pyAgrum.CNMonteCarloSampling method</i>), 145 dynamicExpMin() (<i>pyAgrum.CNLoopyPropagation method</i>), 147 dynamicExpMin() (<i>pyAgrum.CNMonteCarloSampling method</i>), 145</p>
<p>D</p> <p>DAG (<i>class in pyAgrum</i>), 9 dag() (<i>pyAgrum.BayesNet method</i>), 48 dag() (<i>pyAgrum.InfluenceDiagram method</i>), 152 databaseWeight() (<i>pyAgrum.BNLearnert method</i>), 130 dec() (<i>pyAgrum.Instantiation method</i>), 33 decIn() (<i>pyAgrum.Instantiation method</i>), 33 decisionNodeSize() (<i>pyAgrum.InfluenceDiagram method</i>), 152 decisionOrderExists() (<i>pyAgrum.InfluenceDiagram method</i>), 153 decNotVar() (<i>pyAgrum.Instantiation method</i>), 33 decOut() (<i>pyAgrum.Instantiation method</i>), 33 decVar() (<i>pyAgrum.Instantiation method</i>), 33 DefaultInLabel, 159 description() (<i>pyAgrum.DiscreteVariable method</i>), 21 description() (<i>pyAgrum.DiscretizedVariable method</i>), 26 description() (<i>pyAgrum.LabelizedVariable method</i>), 24 description() (<i>pyAgrum.RangeVariable method</i>), 29 DiGraph (<i>class in pyAgrum</i>), 6 dim() (<i>pyAgrum.BayesNet method</i>), 48 DiscreteVariable (<i>class in pyAgrum</i>), 21 DiscretizedVariable (<i>class in pyAgrum</i>), 26 displayResult() (<i>pyAgrum.InfluenceDiagramInference method</i>),</p>	<p>Edge (<i>class in pyAgrum</i>), 6 edges() (<i>pyAgrum.CliqueGraph method</i>), 14 edges() (<i>pyAgrum.MixedGraph method</i>), 18 edges() (<i>pyAgrum.UndiGraph method</i>), 11 empty() (<i>pyAgrum.BayesNet method</i>), 48 empty() (<i>pyAgrum.CliqueGraph method</i>), 14 empty() (<i>pyAgrum.DAG method</i>), 9 empty() (<i>pyAgrum.DiGraph method</i>), 7 empty() (<i>pyAgrum.DiscreteVariable method</i>), 21 empty() (<i>pyAgrum.DiscretizedVariable method</i>), 26 empty() (<i>pyAgrum.InfluenceDiagram method</i>), 153 empty() (<i>pyAgrum.Instantiation method</i>), 34 empty() (<i>pyAgrum.LabelizedVariable method</i>), 24 empty() (<i>pyAgrum.MixedGraph method</i>), 18 empty() (<i>pyAgrum.Potential method</i>), 38 empty() (<i>pyAgrum.RangeVariable method</i>), 29 empty() (<i>pyAgrum.UndiGraph method</i>), 12 emptyArcs() (<i>pyAgrum.DAG method</i>), 9 emptyArcs() (<i>pyAgrum.DiGraph method</i>), 7 emptyArcs() (<i>pyAgrum.MixedGraph method</i>), 18 EmptyBSTree, 159</p>

emptyEdges () (*pyAgrum.CliqueGraph method*), 15
 emptyEdges () (*pyAgrum.MixedGraph method*), 18
 emptyEdges () (*pyAgrum.UndiGraph method*), 12
 EmptySet, 160
 end () (*pyAgrum.Instantiation method*), 34
 endTopologyTransformation () (*pyAgrum.BayesNet method*), 48
 entropy () (*pyAgrum.Potential method*), 38
 epsilon () (*pyAgrum.BNLearned method*), 130
 epsilon () (*pyAgrum.CNLoopyPropagation method*), 148
 epsilon () (*pyAgrum.CNMonteCarloSampling method*), 145
 epsilon () (*pyAgrum.GibbsSampling method*), 81
 epsilon () (*pyAgrum.ImportanceSampling method*), 100
 epsilon () (*pyAgrum.LoopyBeliefPropagation method*), 75
 epsilon () (*pyAgrum.LoopyGibbsSampling method*), 106
 epsilon () (*pyAgrum.LoopyImportanceSampling method*), 125
 epsilon () (*pyAgrum.LoopyMonteCarloSampling method*), 112
 epsilon () (*pyAgrum.LoopyWeightedSampling method*), 118
 epsilon () (*pyAgrum.MonteCarloSampling method*), 87
 epsilon () (*pyAgrum.WeightedSampling method*), 93
 epsilonMax () (*pyAgrum.CredalNet method*), 141
 epsilonMean () (*pyAgrum.CredalNet method*), 141
 epsilonMin () (*pyAgrum.CredalNet method*), 142
 erase () (*pyAgrum.BayesNet method*), 49
 erase () (*pyAgrum.InfluenceDiagram method*), 153
 erase () (*pyAgrum.Instantiation method*), 34
 eraseAllEvidence () (*pyAgrum.CNLoopyPropagation method*), 148
 eraseAllEvidence () (*pyAgrum.GibbsSampling method*), 81
 eraseAllEvidence () (*pyAgrum.ImportanceSampling method*), 100
 eraseAllEvidence () (*pyAgrum.InfluenceDiagramInference method*), 156
 eraseAllEvidence () (*pyAgrum.LazyPropagation method*), 56
 eraseAllEvidence () (*pyAgrum.LoopyBeliefPropagation method*), 75
 eraseAllEvidence () (*pyAgrum.LoopyGibbsSampling method*), 106
 eraseAllEvidence () (*pyAgrum.LoopyImportanceSampling method*), 125
 eraseAllEvidence () (*pyAgrum.LoopyMonteCarloSampling method*), 112
 112
 eraseAllEvidence () (*pyAgrum.LoopyWeightedSampling method*), 119
 eraseAllEvidence () (*pyAgrum.MonteCarloSampling method*), 87
 eraseAllEvidence () (*pyAgrum.ShaferShenoyInference method*), 63
 eraseAllEvidence () (*pyAgrum.VariableElimination method*), 69
 eraseAllEvidence () (*pyAgrum.WeightedSampling method*), 94
 eraseAllJointTargets () (*pyAgrum.LazyPropagation method*), 56
 eraseAllJointTargets () (*pyAgrum.ShaferShenoyInference method*), 63
 eraseAllMarginalTargets () (*pyAgrum.LazyPropagation method*), 56
 eraseAllMarginalTargets () (*pyAgrum.ShaferShenoyInference method*), 63
 eraseAllTargets () (*pyAgrum.GibbsSampling method*), 81
 eraseAllTargets () (*pyAgrum.ImportanceSampling method*), 100
 eraseAllTargets () (*pyAgrum.LazyPropagation method*), 56
 eraseAllTargets () (*pyAgrum.LoopyBeliefPropagation method*), 75
 eraseAllTargets () (*pyAgrum.LoopyGibbsSampling method*), 106
 eraseAllTargets () (*pyAgrum.LoopyImportanceSampling method*), 125
 eraseAllTargets () (*pyAgrum.LoopyMonteCarloSampling method*), 112
 eraseAllTargets () (*pyAgrum.LoopyWeightedSampling method*), 119
 eraseAllTargets () (*pyAgrum.MonteCarloSampling method*), 87
 eraseAllTargets () (*pyAgrum.ShaferShenoyInference method*), 63
 eraseAllTargets () (*pyAgrum.VariableElimination method*), 69
 eraseAllTargets () (*pyAgrum.WeightedSampling method*), 94
 eraseArc () (*pyAgrum.BayesNet method*), 49
 eraseArc () (*pyAgrum.DAG method*), 9
 eraseArc () (*pyAgrum.DiGraph method*), 7
 eraseArc () (*pyAgrum.InfluenceDiagram method*), 153
 eraseArc () (*pyAgrum.MixedGraph method*), 18

```

eraseChildren() (pyAgrum.DAG method), 10
eraseChildren() (pyAgrum.DiGraph method), 7
eraseChildren() (pyAgrum.MixedGraph
    method), 18
eraseEdge() (pyAgrum.CliqueGraph method), 15
eraseEdge() (pyAgrum.MixedGraph method), 18
eraseEdge() (pyAgrum.UndiGraph method), 12
eraseEvidence() (pyAgrum.GibbsSampling
    method), 81
eraseEvidence() (pyAgrum.ImportanceSampling
    method), 100
eraseEvidence() (pyA-
    grum.InfluenceDiagramInference method), 156
eraseEvidence() (pyAgrum.LazyPropagation
    method), 56
eraseEvidence() (pyA-
    grum.LoopyBeliefPropagation method), 75
eraseEvidence() (pyAgrum.LoopyGibbsSampling
    method), 106
eraseEvidence() (pyA-
    grum.LoopyImportanceSampling method), 125
eraseEvidence() (pyA-
    grum.LoopyMonteCarloSampling method), 112
eraseEvidence() (pyA-
    grum.LoopyWeightedSampling method), 119
eraseEvidence() (pyAgrum.MonteCarloSampling
    method), 87
eraseEvidence() (pyAgrum.ShaferShenoyInference
    method), 63
eraseEvidence() (pyAgrum.VariableElimination
    method), 69
eraseEvidence() (pyAgrum.WeightedSampling
    method), 94
eraseForbiddenArc() (pyAgrum.BNLearnert
    method), 130
eraseFromClique() (pyAgrum.CliqueGraph
    method), 15
eraseJointTarget() (pyAgrum.LazyPropagation
    method), 57
eraseJointTarget() (pyA-
    grum.ShaferShenoyInference method), 63
eraseJointTarget() (pyA-
    grum.VariableElimination method), 69
eraseLabels() (pyAgrum.LabelizedVariable
    method), 24
eraseMandatoryArc() (pyAgrum.BNLearnert
    method), 131
eraseNeighbours() (pyAgrum.CliqueGraph
    method), 15
eraseNeighbours() (pyAgrum.MixedGraph
    method), 18
eraseNeighbours() (pyAgrum.UndiGraph
    method), 12
eraseNode() (pyAgrum.CliqueGraph method), 15
eraseNode() (pyAgrum.DAG method), 10
eraseNode() (pyAgrum.DiGraph method), 7
eraseNode() (pyAgrum.MixedGraph method), 18
eraseNode() (pyAgrum.UndiGraph method), 12
eraseParents() (pyAgrum.DAG method), 10
eraseParents() (pyAgrum.DiGraph method), 7
eraseParents() (pyAgrum.MixedGraph method),
    18
erasePossibleEdge() (pyAgrum.BNLearnert
    method), 131
eraseTarget() (pyAgrum.GibbsSampling
    method), 81
eraseTarget() (pyAgrum.ImportanceSampling
    method), 100
eraseTarget() (pyAgrum.LazyPropagation
    method), 57
eraseTarget() (pyAgrum.LoopyBeliefPropagation
    method), 75
eraseTarget() (pyAgrum.LoopyGibbsSampling
    method), 106
eraseTarget() (pyA-
    grum.LoopyImportanceSampling method), 125
eraseTarget() (pyA-
    grum.LoopyMonteCarloSampling method), 113
eraseTarget() (pyA-
    grum.LoopyWeightedSampling method), 119
eraseTarget() (pyAgrum.MonteCarloSampling
    method), 88
eraseTarget() (pyAgrum.ShaferShenoyInference
    method), 63
eraseTarget() (pyAgrum.VariableElimination
    method), 69
eraseTarget() (pyAgrum.WeightedSampling
    method), 94
eraseTicks() (pyAgrum.DiscretizedVariable
    method), 27
errorCallStack() (pyAgrum.GumException
    method), 160
errorContent() (pyAgrum.GumException
    method), 160
errorType() (pyAgrum.GumException method), 160
evidenceImpact() (pyAgrum.GibbsSampling
    method), 81
evidenceImpact() (pyA-
    grum.ImportanceSampling method), 100
evidenceImpact() (pyAgrum.LazyPropagation
    method), 57
evidenceImpact() (pyA-
    grum.LoopyBeliefPropagation method), 75
evidenceImpact() (pyA-

```

grum.LoopyGibbsSampling method), 106
evidenceImpact () (pyA-
grum.LoopyImportanceSampling method), 125
evidenceImpact () (pyA-
grum.LoopyMonteCarloSampling method), 113
evidenceImpact () (pyA-
grum.LoopyWeightedSampling method), 119
evidenceImpact () (pyA-
grum.MonteCarloSampling method), 88
evidenceImpact () (pyA-
grum.ShaferShenoyInference method), 63
evidenceImpact () (pyA-
grum.VariableElimination method), 69
evidenceImpact () (pyAgrum.WeightedSampling method), 94
evidenceJointImpact () (pyA-
grum.LazyPropagation method), 57
evidenceJointImpact () (pyA-
grum.ShaferShenoyInference method), 64
evidenceJointImpact () (pyA-
grum.VariableElimination method), 70
evidenceProbability () (pyA-
grum.LazyPropagation method), 58
evidenceProbability () (pyA-
grum.ShaferShenoyInference method), 64
existsArc () (pyAgrum.DAG method), 10
existsArc () (pyAgrum.DiGraph method), 7
existsArc () (pyAgrum.MixedGraph method), 19
existsEdge () (pyAgrum.CliqueGraph method), 15
existsEdge () (pyAgrum.MixedGraph method), 19
existsEdge () (pyAgrum.UndiGraph method), 12
existsNode () (pyAgrum.CliqueGraph method), 15
existsNode () (pyAgrum.DAG method), 10
existsNode () (pyAgrum.DiGraph method), 8
existsNode () (pyAgrum.MixedGraph method), 19
existsNode () (pyAgrum.UndiGraph method), 12
existsPathBetween () (pyA-
grum.InfluenceDiagram method), 153
extract () (pyAgrum.Potential method), 38

F

fastBN () (in module pyAgrum), 3
fastPrototype () (pyAgrum.BayesNet static method), 49
FatalError, 160
fill () (pyAgrum.Potential method), 38
fillConstraint () (pyAgrum.CredalNet method), 142
fillConstraints () (pyAgrum.CredalNet method), 142
fillWith () (pyAgrum.Potential method), 38
findAll () (pyAgrum.Potential method), 38

first () (pyAgrum.Arc method), 5
first () (pyAgrum.Edge method), 6
FormatNotFound, 160
fromdict () (pyAgrum.Instantiation method), 34

G

G2 () (pyAgrum.BNLearner method), 129
generateCPT () (pyAgrum.BayesNet method), 49
generateCPTs () (pyAgrum.BayesNet method), 49
get () (pyAgrum.Potential method), 38
get_CPT_max () (pyAgrum.CredalNet method), 142
get_CPT_min () (pyAgrum.CredalNet method), 142
getalltheSystems () (pyAgrum.PRMexplorer method), 138
getBestDecisionChoice () (pyA-
grum.InfluenceDiagramInference method), 156
getDecisionGraph () (pyA-
grum.InfluenceDiagram method), 153
getDecisionOrder () (pyA-
grum.InfluenceDiagram method), 153
getDirectSubClass () (pyAgrum.PRMexplorer method), 137
getDirectSubInterfaces () (pyA-
grum.PRMexplorer method), 137
getDirectSubTypes () (pyAgrum.PRMexplorer method), 137
getImplementations () (pyAgrum.PRMexplorer method), 137
getLabelMap () (pyAgrum.PRMexplorer method), 138
getLabels () (pyAgrum.PRMexplorer method), 138
getMaxNumberOfThreads () (in module pyA-
grum), 159
getMEU () (pyAgrum.InfluenceDiagramInference method), 156
getNumberOfLogicalProcessors () (in mod-
ule pyAgrum), 159
getPosterior () (in module pyAgrum), 3
getSuperClass () (pyAgrum.PRMexplorer method), 138
getSuperInterface () (pyAgrum.PRMexplorer method), 138
getSuperType () (pyAgrum.PRMexplorer method), 138
GibbsSampling (class in pyAgrum), 79
GraphError, 160
GumException, 160

H

H () (pyAgrum.GibbsSampling method), 79
H () (pyAgrum.ImportanceSampling method), 98
H () (pyAgrum.LazyPropagation method), 55
H () (pyAgrum.LoopyBeliefPropagation method), 73
H () (pyAgrum.LoopyGibbsSampling method), 104
H () (pyAgrum.LoopyImportanceSampling method), 123

H()	(<i>pyAgrum.LoopyMonteCarloSampling</i> method),		hasEvidence()	(<i>pyAgrum.MonteCarloSampling</i> method),	88
	111				
H()	(<i>pyAgrum.LoopyWeightedSampling</i> method),	117	hasEvidence()	(<i>pyAgrum.ShaferShenoyInference</i> method),	64
H()	(<i>pyAgrum.MonteCarloSampling</i> method),	86	hasEvidence()	(<i>pyAgrum.VariableElimination</i> method),	70
H()	(<i>pyAgrum.ShaferShenoyInference</i> method),	61	hasEvidence()	(<i>pyAgrum.WeightedSampling</i> method),	94
H()	(<i>pyAgrum.VariableElimination</i> method),	67	hasEvidence()	(<i>pyAgrum.GibbsSampling</i> method),	82
H()	(<i>pyAgrum.WeightedSampling</i> method),	92	hasHardEvidence()	(<i>pyAgrum.GibbsSampling</i> method),	82
hamming()	(<i>pyAgrum.Instantiation</i> method),	34	hasHardEvidence()	(<i>pyAgrum.ImportanceSampling</i> method),	101
hardEvidenceNodes()	(<i>pyAgrum.GibbsSampling</i> method),	82	hasHardEvidence()	(<i>pyAgrum.LazyPropagation</i> method),	58
hardEvidenceNodes()	(<i>pyAgrum.ImportanceSampling</i> method),	100	hasHardEvidence()	(<i>pyAgrum.LoopyBeliefPropagation</i> method),	76
hardEvidenceNodes()	(<i>pyAgrum.LazyPropagation</i> method),	58	hasHardEvidence()	(<i>pyAgrum.LoopyGibbsSampling</i> method),	107
hardEvidenceNodes()	(<i>pyAgrum.LoopyBeliefPropagation</i> method),	75	hasHardEvidence()	(<i>pyAgrum.LoopyImportanceSampling</i> method),	126
hardEvidenceNodes()	(<i>pyAgrum.LoopyGibbsSampling</i> method),	107	hasHardEvidence()	(<i>pyAgrum.LoopyMonteCarloSampling</i> method),	113
hardEvidenceNodes()	(<i>pyAgrum.LoopyImportanceSampling</i> method),	125	hasHardEvidence()	(<i>pyAgrum.LoopyWeightedSampling</i> method),	120
hardEvidenceNodes()	(<i>pyAgrum.LoopyMonteCarloSampling</i> method),	113	hasHardEvidence()	(<i>pyAgrum.MonteCarloSampling</i> method),	88
hardEvidenceNodes()	(<i>pyAgrum.LoopyWeightedSampling</i> method),	119	hasHardEvidence()	(<i>pyAgrum.ShaferShenoyInference</i> method),	64
hardEvidenceNodes()	(<i>pyAgrum.MonteCarloSampling</i> method),	88	hardEvidenceNodes()	(<i>pyAgrum.VariableElimination</i> method),	70
hardEvidenceNodes()	(<i>pyAgrum.ShaferShenoyInference</i> method),	64	hardEvidenceNodes()	(<i>pyAgrum.WeightedSampling</i> method),	94
hardEvidenceNodes()	(<i>pyAgrum.VariableElimination</i> method),	70	hasComputedCPTMinMax()	(<i>pyAgrum.CredalNet</i> method),	143
hardEvidenceNodes()	(<i>pyAgrum.WeightedSampling</i> method),	94	hasMissingValues()	(<i>pyAgrum.BN Learner</i> method),	131
hasComputedCPTMinMax()	(<i>pyAgrum.CredalNet</i> method),	143	hasRunningIntersection()	(<i>pyAgrum.CliqueGraph</i> method),	15
hasEvidence()	(<i>pyAgrum.GibbsSampling</i> method),	82	hasSameStructure()	(<i>pyAgrum.BayesNet</i> method),	50
hasEvidence()	(<i>pyAgrum.ImportanceSampling</i> method),	100	hasSameStructure()	(<i>pyAgrum.InfluenceDiagram</i> method),	153
hasEvidence()	(<i>pyAgrum.LazyPropagation</i> method),	58	hasSoftEvidence()	(<i>pyAgrum.GibbsSampling</i> method),	82
hasEvidence()	(<i>pyAgrum.LoopyBeliefPropagation</i> method),	75	hasSoftEvidence()	(<i>pyAgrum.ImportanceSampling</i> method),	101
hasEvidence()	(<i>pyAgrum.LoopyGibbsSampling</i> method),	107	hasSoftEvidence()	(<i>pyAgrum.LazyPropagation</i> method),	58
hasEvidence()	(<i>pyAgrum.LoopyImportanceSampling</i> method),	125	hasSoftEvidence()	(<i>pyAgrum.LoopyBeliefPropagation</i> method),	76
hasEvidence()	(<i>pyAgrum.LoopyMonteCarloSampling</i> method),	113	hasSoftEvidence()	(<i>pyAgrum.LoopyGibbsSampling</i> method),	107
hasEvidence()	(<i>pyAgrum.LoopyWeightedSampling</i> method),	119	hasSoftEvidence()	(<i>pyAgrum.LoopyImportanceSampling</i> method),	126

126
 hasSoftEvidence() (pyAgrum.*LoopyMonteCarloSampling* method), 114
 hasSoftEvidence() (pyAgrum.*LoopyWeightedSampling* method), 120
 hasSoftEvidence() (pyAgrum.*MonteCarloSampling* method), 89
 hasSoftEvidence() (pyAgrum.*ShaferShenoyInference* method), 65
 hasSoftEvidence() (pyAgrum.*VariableElimination* method), 70
 hasSoftEvidence() (pyAgrum.*WeightedSampling* method), 95
 hasUndirectedCycle() (pyAgrum.*CliqueGraph* method), 15
 hasUndirectedCycle() (pyAgrum.*MixedGraph* method), 19
 hasUndirectedCycle() (pyAgrum.*UndiGraph* method), 12
 head() (pyAgrum.*Arc* method), 5
 history() (pyAgrum.*BNLearner* method), 131
 history() (pyAgrum.*CNLoopyPropagation* method), 148
 history() (pyAgrum.*CNMonteCarloSampling* method), 145
 history() (pyAgrum.*GibbsSampling* method), 82
 history() (pyAgrum.*ImportanceSampling* method), 101
 history() (pyAgrum.*LoopyBeliefPropagation* method), 76
 history() (pyAgrum.*LoopyGibbsSampling* method), 107
 history() (pyAgrum.*LoopyImportanceSampling* method), 126
 history() (pyAgrum.*LoopyMonteCarloSampling* method), 114
 history() (pyAgrum.*LoopyWeightedSampling* method), 120
 history() (pyAgrum.*MonteCarloSampling* method), 89
 history() (pyAgrum.*WeightedSampling* method), 95

|

I() (pyAgrum.*LazyPropagation* method), 55
 I() (pyAgrum.*ShaferShenoyInference* method), 61
 IdError, 160
 idFromName() (pyAgrum.*BayesNet* method), 50
 idFromName() (pyAgrum.*BNLearner* method), 131
 idFromName() (pyAgrum.*InfluenceDiagram* method), 153
 idmLearning() (pyAgrum.*CredalNet* method), 143
 ids() (pyAgrum.*BayesNet* method), 50
 ids() (pyAgrum.*CliqueGraph* method), 15
 ids() (pyAgrum.*DAG* method), 10

ids() (pyAgrum.*DiGraph* method), 8
 ids() (pyAgrum.*InfluenceDiagram* method), 154
 ids() (pyAgrum.*MixedGraph* method), 19
 ids() (pyAgrum.*UndiGraph* method), 12
 ImportanceSampling (class in pyAgrum), 98
 inc() (pyAgrum.*Instantiation* method), 34
 incIn() (pyAgrum.*Instantiation* method), 34
 incNotVar() (pyAgrum.*Instantiation* method), 34
 incOut() (pyAgrum.*Instantiation* method), 34
 incVar() (pyAgrum.*Instantiation* method), 34
 index() (pyAgrum.*DiscreteVariable* method), 21
 index() (pyAgrum.*DiscretizedVariable* method), 27
 index() (pyAgrum.*LabelizedVariable* method), 24
 index() (pyAgrum.*RangeVariable* method), 29
 inferenceType() (pyAgrum.*CNLoopyPropagation* method), 148
 InfluenceDiagram (class in pyAgrum), 150
 influenceDiagram() (pyAgrum.*InfluenceDiagramInference* method), 156
 InfluenceDiagramInference (class in pyAgrum), 156
 initRandom() (in module pyAgrum), 158
 inOverflow() (pyAgrum.*Instantiation* method), 34
 insertEvidence() (pyAgrum.*InfluenceDiagramInference* method), 156
 insertEvidenceFile() (pyAgrum.*CNLoopyPropagation* method), 148
 insertEvidenceFile() (pyAgrum.*CNMonteCarloSampling* method), 145
 insertModalsFile() (pyAgrum.*CNLoopyPropagation* method), 148
 insertModalsFile() (pyAgrum.*CNMonteCarloSampling* method), 145
 Instantiation (class in pyAgrum), 32
 instantiation() (pyAgrum.*CredalNet* method), 143
 interAttributes() (pyAgrum.*PRMexplorer* method), 138
 interfaces() (pyAgrum.*PRMexplorer* method), 139
 interReferences() (pyAgrum.*PRMexplorer* method), 138
 intervalToCredal() (pyAgrum.*CredalNet* method), 143
 intervalToCredalWithFiles() (pyAgrum.*CredalNet* method), 143
 InvalidArc, 161
 InvalidArgument, 161
 InvalidArgumentsNumber, 161
 InvalidDirectedCycle, 161
 InvalidEdge, 161

InvalidNode, 161
 IOError, 160
 isAttribute() (*pyAgrum.PRMexplorer method*), 139
 isChanceNode() (*pyAgrum.InfluenceDiagram method*), 154
 isClass() (*pyAgrum.PRMexplorer method*), 139
 isDecisionNode() (*pyAgrum.InfluenceDiagram method*), 154
 isDrawnAtRandom() (*pyAgrum.GibbsSampling method*), 82
 isDrawnAtRandom() (*pyAgrum.LoopyGibbsSampling method*), 107
 isInterface() (*pyAgrum.PRMexplorer method*), 139
 isJoinTree() (*pyAgrum.CliqueGraph method*), 15
 isJointTarget() (*pyAgrum.LazyPropagation method*), 58
 isJointTarget() (*pyAgrum.ShaferShenoyInference method*), 65
 isJointTarget() (*pyAgrum.VariableElimination method*), 71
 isLabel() (*pyAgrum.LabelizedVariable method*), 24
 isNonZeroMap() (*pyAgrum.Potential method*), 38
 isOMP() (*in module pyAgrum*), 159
 isSeparatelySpecified() (*pyAgrum.CredalNet method*), 143
 isTarget() (*pyAgrum.GibbsSampling method*), 83
 isTarget() (*pyAgrum.ImportanceSampling method*), 101
 isTarget() (*pyAgrum.LazyPropagation method*), 58
 isTarget() (*pyAgrum.LoopyBeliefPropagation method*), 76
 isTarget() (*pyAgrum.LoopyGibbsSampling method*), 108
 isTarget() (*pyAgrum.LoopyImportanceSampling method*), 126
 isTarget() (*pyAgrum.LoopyMonteCarloSampling method*), 114
 isTarget() (*pyAgrum.LoopyWeightedSampling method*), 120
 isTarget() (*pyAgrum.MonteCarloSampling method*), 89
 isTarget() (*pyAgrum.ShaferShenoyInference method*), 65
 isTarget() (*pyAgrum.VariableElimination method*), 71
 isTarget() (*pyAgrum.WeightedSampling method*), 95
 isTick() (*pyAgrum.DiscretizedVariable method*), 27
 isType() (*pyAgrum.PRMexplorer method*), 139
 isUtilityNode() (*pyAgrum.InfluenceDiagram method*), 154

J

jointMutualInformation() (*pyAgrum.LazyPropagation method*), 59
 jointMutualInformation() (*pyAgrum.ShaferShenoyInference method*), 65
 jointMutualInformation() (*pyAgrum.VariableElimination method*), 71
 jointPosterior() (*pyAgrum.LazyPropagation method*), 59
 jointPosterior() (*pyAgrum.ShaferShenoyInference method*), 65
 jointPosterior() (*pyAgrum.VariableElimination method*), 71
 jointProbability() (*pyAgrum.BayesNet method*), 50
 joinTree() (*pyAgrum.LazyPropagation method*), 59
 joinTree() (*pyAgrum.ShaferShenoyInference method*), 65
 jointTargets() (*pyAgrum.LazyPropagation method*), 59
 jointTargets() (*pyAgrum.ShaferShenoyInference method*), 66
 jointTargets() (*pyAgrum.VariableElimination method*), 71
 junctionTree() (*pyAgrum.LazyPropagation method*), 59
 junctionTree() (*pyAgrum.ShaferShenoyInference method*), 66
 junctionTree() (*pyAgrum.VariableElimination method*), 71
 junctionTreeToDot() (*pyAgrum.InfluenceDiagramInference method*), 157

K

KL() (*pyAgrum.Potential method*), 37

L

label() (*pyAgrum.DiscreteVariable method*), 21
 label() (*pyAgrum.DiscretizedVariable method*), 27
 label() (*pyAgrum.LabelizedVariable method*), 24
 label() (*pyAgrum.RangeVariable method*), 29
 LabelizedVariable (*class in pyAgrum*), 23
 labels() (*pyAgrum.DiscreteVariable method*), 21
 labels() (*pyAgrum.DiscretizedVariable method*), 27
 labels() (*pyAgrum.LabelizedVariable method*), 24
 labels() (*pyAgrum.RangeVariable method*), 30
 lagrangeNormalization() (*pyAgrum.CredalNet method*), 143
 latentVariables() (*pyAgrum.BNLearner method*), 132
 LazyPropagation (*class in pyAgrum*), 54
 learnBN() (*pyAgrum.BNLearner method*), 132
 learnDAG() (*pyAgrum.BNLearner method*), 132
 learnMixedStructure() (*pyAgrum.BNLearner method*), 132

learnParameters() (*pyAgrum.BNLearnert
method*), 132

line() (*pyAgrum.SyntacticError method*), 163

load() (*pyAgrum.PRMExplorer method*), 139

loadBIF() (*pyAgrum.BayesNet method*), 50

loadBIFXML() (*pyAgrum.BayesNet method*), 50

loadBIFXML() (*pyAgrum.InfluenceDiagram
method*), 154

loadBN() (*in module pyAgrum*), 4

loadDSL() (*pyAgrum.BayesNet method*), 50

loadID() (*in module pyAgrum*), 4

loadNET() (*pyAgrum.BayesNet method*), 51

loadO3PRM() (*pyAgrum.BayesNet method*), 51

loadUAI() (*pyAgrum.BayesNet method*), 51

log10DomainSize() (*pyAgrum.BayesNet
method*), 51

log10DomainSize() (*pyAgrum.InfluenceDiagram
method*), 154

log2JointProbability() (*pyAgrum.BayesNet
method*), 51

logLikelihood() (*pyAgrum.BNLearnert
method*), 133

LoopyBeliefPropagation (*class in pyAgrum*),
73

LoopyGibbsSampling (*class in pyAgrum*), 104

LoopyImportanceSampling (*class in pyAgrum*),
123

LoopyMonteCarloSampling (*class in pyAgrum*),
111

LoopyWeightedSampling (*class in pyAgrum*),
117

M

makeInference() (*pyA-
grum.CNLoopyPropagation
method*), 148

makeInference() (*pyA-
grum.CNMonteCarloSampling
method*), 146

makeInference() (*pyAgrum.GibbsSampling
method*), 83

makeInference() (*pyAgrum.ImportanceSampling
method*), 101

makeInference() (*pyA-
grum.InfluenceDiagramInference
method*), 157

makeInference() (*pyAgrum.LazyPropagation
method*), 59

makeInference() (*pyA-
grum.LoopyBeliefPropagation
method*), 76

makeInference() (*pyAgrum.LoopyGibbsSampling
method*), 108

makeInference() (*pyA-
grum.LoopyImportanceSampling
method*), 126

makeInference() (*pyA-
grum.LoopyMonteCarloSampling
method*), 114

makeInference() (*pyA-
grum.LoopyWeightedSampling
method*), 120

makeInference() (*pyAgrum.MonteCarloSampling
method*), 89

makeInference() (*pyAgrum.WeightedSampling
method*), 95

marginalMax() (*pyAgrum.CNLoopyPropagation
method*), 148

marginalMax() (*pyA-
grum.CNMonteCarloSampling
method*), 146

margMaxIn() (*pyAgrum.Potential method*), 39

margMaxOut() (*pyAgrum.Potential method*), 39

margMinIn() (*pyAgrum.Potential method*), 39

margMinOut() (*pyAgrum.Potential method*), 39

margProdIn() (*pyAgrum.Potential method*), 39

margProdOut() (*pyAgrum.Potential method*), 39

margSumIn() (*pyAgrum.Potential method*), 39

margSumOut() (*pyAgrum.Potential method*), 39

max() (*pyAgrum.Potential method*), 40

maxIter() (*pyAgrum.BNLearnert
method*), 133

maxIter() (*pyAgrum.CNLoopyPropagation
method*), 149

maxIter() (*pyAgrum.CNMonteCarloSampling
method*), 146

maxIter() (*pyAgrum.GibbsSampling method*), 83

maxIter() (*pyAgrum.ImportanceSampling method*),
102

maxIter() (*pyAgrum.LoopyBeliefPropagation
method*), 77

maxIter() (*pyAgrum.LoopyGibbsSampling
method*), 108

maxIter() (*pyAgrum.LoopyImportanceSampling
method*), 127

maxIter() (*pyAgrum.LoopyMonteCarloSampling
method*), 114

maxIter() (*pyAgrum.LoopyWeightedSampling
method*), 120

maxIter() (*pyAgrum.MonteCarloSampling
method*), 89

maxIter() (*pyAgrum.WeightedSampling method*),
95

maxNonOne() (*pyAgrum.Potential method*), 40

maxNonOneParam() (*pyAgrum.BayesNet method*),
52

maxParam() (*pyAgrum.BayesNet method*), 52

```

maxTime () (pyAgrum.BNLearn method), 133
maxTime () (pyAgrum.CNLoopyPropagation
    method), 149
maxTime () (pyAgrum.CNMonteCarloSampling
    method), 146
maxTime () (pyAgrum.GibbsSampling method), 83
maxTime () (pyAgrum.ImportanceSampling method),
    102
maxTime () (pyAgrum.LoopyBeliefPropagation
    method), 77
maxTime () (pyAgrum.LoopyGibbsSampling
    method), 108
maxTime () (pyAgrum.LoopyImportanceSampling
    method), 127
maxTime () (pyAgrum.LoopyMonteCarloSampling
    method), 114
maxTime () (pyAgrum.LoopyWeightedSampling
    method), 120
maxTime () (pyAgrum.MonteCarloSampling
    method), 89
maxTime () (pyAgrum.WeightedSampling method),
    95
maxVal () (pyAgrum.RangeVariable method), 30
maxVarDomainSize () (pyAgrum.BayesNet
    method), 52
messageApproximationScheme () (pyA-
    grum.BNLearn method), 133
messageApproximationScheme () (pyA-
    grum.CNLoopyPropagation method), 149
messageApproximationScheme () (pyA-
    grum.CNMonteCarloSampling method),
    146
messageApproximationScheme () (pyA-
    grum.GibbsSampling method), 83
messageApproximationScheme () (pyA-
    grum.ImportanceSampling method), 102
messageApproximationScheme () (pyA-
    grum.LoopyBeliefPropagation
    method), 77
messageApproximationScheme () (pyA-
    grum.LoopyGibbsSampling method), 108
messageApproximationScheme () (pyA-
    grum.LoopyImportanceSampling
    method), 127
messageApproximationScheme () (pyA-
    grum.LoopyMonteCarloSampling
    method), 114
messageApproximationScheme () (pyA-
    grum.LoopyWeightedSampling
    method), 121
messageApproximationScheme () (pyA-
    grum.MonteCarloSampling method), 89
messageApproximationScheme () (pyA-
    grum.WeightedSampling method), 96
min () (pyAgrum.Potential method), 40
minEpsilonRate () (pyAgrum.BNLearn
    method), 133
minEpsilonRate () (pyA-
    grum.CNLoopyPropagation
    method), 149
minEpsilonRate () (pyAgrum.CNMonteCarloSampling
    method), 146
minEpsilonRate () (pyAgrum.GibbsSampling
    method), 83
minEpsilonRate () (pyAgrum.ImportanceSampling
    method), 102
minEpsilonRate () (pyA-
    grum.LoopyBeliefPropagation
    method), 77
minEpsilonRate () (pyA-
    grum.LoopyGibbsSampling method), 108
minEpsilonRate () (pyA-
    grum.LoopyImportanceSampling
    method), 127
minEpsilonRate () (pyA-
    grum.LoopyMonteCarloSampling
    method), 115
minEpsilonRate () (pyA-
    grum.LoopyWeightedSampling
    method), 121
minEpsilonRate () (pyA-
    grum.MonteCarloSampling method), 90
minEpsilonRate () (pyAgrum.WeightedSampling
    method), 96
minimalCondSet () (pyAgrum.BayesNet method),
    52
minNonZero () (pyAgrum.Potential method), 40
minNonZeroParam () (pyAgrum.BayesNet
    method), 52
minParam () (pyAgrum.BayesNet method), 52
minVal () (pyAgrum.RangeVariable method), 30
MixedGraph (class in pyAgrum), 17
mixedOrientedPath () (pyAgrum.MixedGraph
    method), 19
mixedUnorientedPath () (pyAgrum.MixedGraph
    method), 19
MonteCarloSampling (class in pyAgrum), 85
moralGraph () (pyAgrum.BayesNet method), 52
moralGraph () (pyAgrum.DAG method), 10
moralGraph () (pyAgrum.InfluenceDiagram
    method), 154

```

N

```

name () (pyAgrum.DiscreteVariable method), 22
name () (pyAgrum.DiscretizedVariable method), 27
name () (pyAgrum.LabelizedVariable method), 25
name () (pyAgrum.RangeVariable method), 30
nameFromId () (pyAgrum.BNLearn method), 133
names () (pyAgrum.BayesNet method), 52
names () (pyAgrum.BNLearn method), 133
names () (pyAgrum.InfluenceDiagram method), 154
nbCols () (pyAgrum.BNLearn method), 133
nbrDim () (pyAgrum.Instantiation method), 35
nbrDim () (pyAgrum.Potential method), 40

```

<code>nbrDrawnVar()</code>	<i>(pyAgrum.GibbsSampling method)</i> , 83	<code>nbrHardEvidence()</code>	<i>(pyAgrum.WeightedSampling method)</i> , 96
<code>nbrDrawnVar()</code>	<i>(pyAgrum.LoopyGibbsSampling method)</i> , 108	<code>nbrIterations()</code>	<i>(pyAgrum.BNLearn method)</i> , 133
<code>nbrEvidence()</code>	<i>(pyAgrum.GibbsSampling method)</i> , 83	<code>nbrIterations()</code>	<i>(pyAgrum.CNLoopyPropagation method)</i> , 149
<code>nbrEvidence()</code>	<i>(pyAgrum.ImportanceSampling method)</i> , 102	<code>nbrIterations()</code>	<i>(pyAgrum.CNMonteCarloSampling method)</i> , 146
<code>nbrEvidence()</code>	<i>(pyAgrum.LazyPropagation method)</i> , 59	<code>nbrIterations()</code>	<i>(pyAgrum.GibbsSampling method)</i> , 83
<code>nbrEvidence()</code>	<i>(pyAgrum.LoopyBeliefPropagation method)</i> , 77	<code>nbrIterations()</code>	<i>(pyAgrum.ImportanceSampling method)</i> , 102
<code>nbrEvidence()</code>	<i>(pyAgrum.LoopyGibbsSampling method)</i> , 108	<code>nbrIterations()</code>	<i>(pyAgrum.LoopyBeliefPropagation method)</i> , 77
<code>nbrEvidence()</code>	<i>(pyAgrum.LoopyImportanceSampling method)</i> , 127	<code>nbrIterations()</code>	<i>(pyAgrum.LoopyGibbsSampling method)</i> , 108
<code>nbrEvidence()</code>	<i>(pyAgrum.LoopyMonteCarloSampling method)</i> , 115	<code>nbrIterations()</code>	<i>(pyAgrum.LoopyImportanceSampling method)</i> , 127
<code>nbrEvidence()</code>	<i>(pyAgrum.LoopyWeightedSampling method)</i> , 121	<code>nbrIterations()</code>	<i>(pyAgrum.LoopyMonteCarloSampling method)</i> , 115
<code>nbrEvidence()</code>	<i>(pyAgrum.MonteCarloSampling method)</i> , 90	<code>nbrIterations()</code>	<i>(pyAgrum.LoopyWeightedSampling method)</i> , 121
<code>nbrEvidence()</code>	<i>(pyAgrum.ShaferShenoyInference method)</i> , 66	<code>nbrIterations()</code>	<i>(pyAgrum.MonteCarloSampling method)</i> , 90
<code>nbrEvidence()</code>	<i>(pyAgrum.VariableElimination method)</i> , 72	<code>nbrIterations()</code>	<i>(pyAgrum.WeightedSampling method)</i> , 96
<code>nbrEvidence()</code>	<i>(pyAgrum.WeightedSampling method)</i> , 96	<code>nbrJointTargets()</code>	<i>(pyAgrum.LazyPropagation method)</i> , 59
<code>nbrHardEvidence()</code>	<i>(pyAgrum.GibbsSampling method)</i> , 83	<code>nbrJointTargets()</code>	<i>(pyAgrum.ShaferShenoyInference method)</i> , 66
<code>nbrHardEvidence()</code>	<i>(pyAgrum.ImportanceSampling method)</i> , 102	<code>nbRows()</code>	<i>(pyAgrum.BNLearn method)</i> , 133
<code>nbrHardEvidence()</code>	<i>(pyAgrum.LazyPropagation method)</i> , 59	<code>nbrSoftEvidence()</code>	<i>(pyAgrum.GibbsSampling method)</i> , 83
<code>nbrHardEvidence()</code>	<i>(pyAgrum.LoopyBeliefPropagation method)</i> , 77	<code>nbrSoftEvidence()</code>	<i>(pyAgrum.ImportanceSampling method)</i> , 102
<code>nbrHardEvidence()</code>	<i>(pyAgrum.LoopyGibbsSampling method)</i> , 108	<code>nbrSoftEvidence()</code>	<i>(pyAgrum.LazyPropagation method)</i> , 60
<code>nbrHardEvidence()</code>	<i>(pyAgrum.LoopyImportanceSampling method)</i> , 127	<code>nbrSoftEvidence()</code>	<i>(pyAgrum.LoopyBeliefPropagation method)</i> , 77
<code>nbrHardEvidence()</code>	<i>(pyAgrum.LoopyMonteCarloSampling method)</i> , 115	<code>nbrSoftEvidence()</code>	<i>(pyAgrum.LoopyGibbsSampling method)</i> , 109
<code>nbrHardEvidence()</code>	<i>(pyAgrum.LoopyWeightedSampling method)</i> , 121	<code>nbrSoftEvidence()</code>	<i>(pyAgrum.LoopyImportanceSampling method)</i> , 127
<code>nbrHardEvidence()</code>	<i>(pyAgrum.MonteCarloSampling method)</i> , 90	<code>nbrSoftEvidence()</code>	<i>(pyAgrum.LoopyMonteCarloSampling method)</i> , 115
<code>nbrHardEvidence()</code>	<i>(pyAgrum.ShaferShenoyInference method)</i> , 66	<code>nbrSoftEvidence()</code>	<i>(pyAgrum.LoopyWeightedSampling method)</i> , 121
<code>nbrHardEvidence()</code>	<i>(pyAgrum.VariableElimination method)</i> , 72		

```

nbrSoftEvidence() (pyA-
    grum.MonteCarloSampling method), 90
nbrSoftEvidence() (pyA-
    grum.ShaferShenoyInference method),
    66
nbrSoftEvidence() (pyA-
    grum.VariableElimination method), 72
nbrSoftEvidence() (pyAgrum.WeightedSampling
    method), 96
nbrTargets() (pyAgrum.GibbsSampling method),
    84
nbrTargets() (pyAgrum.ImportanceSampling
    method), 102
nbrTargets() (pyAgrum.LazyPropagation
    method), 60
nbrTargets() (pyAgrum.LoopyBeliefPropagation
    method), 77
nbrTargets() (pyAgrum.LoopyGibbsSampling
    method), 109
nbrTargets() (pyAgrum.LoopyImportanceSampling
    method), 127
nbrTargets() (pyA-
    grum.LoopyMonteCarloSampling method),
    115
nbrTargets() (pyAgrum.LoopyWeightedSampling
    method), 121
nbrTargets() (pyAgrum.MonteCarloSampling
    method), 90
nbrTargets() (pyAgrum.ShaferShenoyInference
    method), 66
nbrTargets() (pyAgrum.VariableElimination
    method), 72
nbrTargets() (pyAgrum.WeightedSampling
    method), 96
neighbours() (pyAgrum.CliqueGraph method), 16
neighbours() (pyAgrum.MixedGraph method), 20
neighbours() (pyAgrum.UndiGraph method), 12
newFactory() (pyAgrum.Potential method), 40
NoChild, 161
nodeId() (pyAgrum.BayesNet method), 52
nodeId() (pyAgrum.InfluenceDiagram method), 154
nodes() (pyAgrum.BayesNet method), 53
nodes() (pyAgrum.CliqueGraph method), 16
nodes() (pyAgrum.DAG method), 10
nodes() (pyAgrum.DiGraph method), 8
nodes() (pyAgrum.InfluenceDiagram method), 155
nodes() (pyAgrum.MixedGraph method), 20
nodes() (pyAgrum.UndiGraph method), 12
nodeType() (pyAgrum.CredalNet method), 144
NoNeighbour, 161
NoParent, 161
normalize() (pyAgrum.Potential method), 40
normalizeAsCPT() (pyAgrum.Potential method),
    40
NotFound, 162
NullElement, 162
numerical() (pyAgrum.DiscreteVariable method),
    22
numerical() (pyAgrum.DiscretizedVariable
    method), 27
numerical() (pyAgrum.LabelizedVariable method),
    25
numerical() (pyAgrum.RangeVariable method), 30

```

O

OperationNotAllowed, 162
other() (pyAgrum.Arc method), 5
other() (pyAgrum.Edge method), 6
OutOfBounds, 162
OutOfLowerBound, 162
OutOfUpperBound, 162

P

parents() (pyAgrum.BayesNet method), 53
parents() (pyAgrum.DAG method), 10
parents() (pyAgrum.DiGraph method), 8
parents() (pyAgrum.InfluenceDiagram method),
 155
parents() (pyAgrum.MixedGraph method), 20
partialUndiGraph() (pyAgrum.CliqueGraph
 method), 16
partialUndiGraph() (pyAgrum.MixedGraph
 method), 20
partialUndiGraph() (pyAgrum.UndiGraph
 method), 13
pdfize() (in module pyAgrum.lib.bn2graph), 167,
 168
periodSize() (pyAgrum.BNLearn method), 134
periodSize() (pyAgrum.CNLoopyPropagation
 method), 149
periodSize() (pyAgrum.CNMonteCarloSampling
 method), 146
periodSize() (pyAgrum.GibbsSampling method),
 84
periodSize() (pyAgrum.ImportanceSampling
 method), 102
periodSize() (pyAgrum.LoopyBeliefPropagation
 method), 77
periodSize() (pyAgrum.LoopyGibbsSampling
 method), 109
periodSize() (pyAgrum.LoopyImportanceSampling
 method), 127
periodSize() (pyA-
 grum.LoopyMonteCarloSampling method),
 115
periodSize() (pyAgrum.LoopyWeightedSampling
 method), 121
periodSize() (pyAgrum.MonteCarloSampling
 method), 90
periodSize() (pyAgrum.WeightedSampling
 method), 96
pngize() (in module pyAgrum.lib.bn2graph), 167,
 168
pos() (pyAgrum.Instantiation method), 35

pos() (*pyAgrum.Potential method*), 40
posLabel() (*pyAgrum.LabelizedVariable method*), 25
posterior() (*pyAgrum.GibbsSampling method*), 84
posterior() (*pyAgrum.ImportanceSampling method*), 102
posterior() (*pyAgrum.LazyPropagation method*), 60
posterior() (*pyAgrum.LoopyBeliefPropagation method*), 77
posterior() (*pyAgrum.LoopyGibbsSampling method*), 109
posterior() (*pyAgrum.LoopyImportanceSampling method*), 127
posterior() (*pyAgrum.LoopyMonteCarloSampling method*), 115
posterior() (*pyAgrum.LoopyWeightedSampling method*), 121
posterior() (*pyAgrum.MonteCarloSampling method*), 90
posterior() (*pyAgrum.ShaferShenoyInference method*), 66
posterior() (*pyAgrum.VariableElimination method*), 72
posterior() (*pyAgrum.WeightedSampling method*), 96
Potential (*class in pyAgrum*), 37
PRMexplorer (*class in pyAgrum*), 136
proba2histo() (*in module pyAgrum.lib.bn2graph*), 167
product() (*pyAgrum.Potential method*), 41
putFirst() (*pyAgrum.Potential method*), 41
pyAgrum.lib.bn2graph (*module*), 166

R

randomDistribution() (*in module pyAgrum*), 158
randomProba() (*in module pyAgrum*), 158
RangeVariable (*class in pyAgrum*), 28
recordWeight() (*pyAgrum.BN Learner method*), 134
ReferenceError, 162
remove() (*pyAgrum.Potential method*), 41
rend() (*pyAgrum.Instantiation method*), 35
reorder() (*pyAgrum.Instantiation method*), 35
reorganize() (*pyAgrum.Potential method*), 41
reverseArc() (*pyAgrum.BayesNet method*), 53

S

saveBIF() (*pyAgrum.BayesNet method*), 53
saveBIFXML() (*pyAgrum.BayesNet method*), 53
saveBIFXML() (*pyAgrum.InfluenceDiagram method*), 155
saveBN() (*in module pyAgrum*), 4
saveBNsMinMax() (*pyAgrum.CredalNet method*), 144
saveDSL() (*pyAgrum.BayesNet method*), 53
saveInference() (*pyAgrum.CNLoopyPropagation method*), 149
saveNET() (*pyAgrum.BayesNet method*), 53
saveO3PRM() (*pyAgrum.BayesNet method*), 53
saveUAI() (*pyAgrum.BayesNet method*), 53
scale() (*pyAgrum.Potential method*), 41
second() (*pyAgrum.Arc method*), 5
second() (*pyAgrum.Edge method*), 6
separator() (*pyAgrum.CliqueGraph method*), 16
set() (*pyAgrum.Potential method*), 41
setAprioriWeight() (*pyAgrum.BN Learner method*), 134
setBurnIn() (*pyAgrum.GibbsSampling method*), 84
setBurnIn() (*pyAgrum.LoopyGibbsSampling method*), 109
setClique() (*pyAgrum.CliqueGraph method*), 16
setCPT() (*pyAgrum.CredalNet method*), 144
setCPTs() (*pyAgrum.CredalNet method*), 144
setDatabaseWeight() (*pyAgrum.BN Learner method*), 134
setDescription() (*pyAgrum.DiscreteVariable method*), 22
setDescription() (*pyAgrum.DiscretizedVariable method*), 27
setDescription() (*pyAgrum.LabelizedVariable method*), 25
setDescription() (*pyAgrum.RangeVariable method*), 30
setDrawnAtRandom() (*pyAgrum.GibbsSampling method*), 84
setDrawnAtRandom() (*pyAgrum.LoopyGibbsSampling method*), 109
setEpsilon() (*pyAgrum.BN Learner method*), 134
setEpsilon() (*pyAgrum.CNLoopyPropagation method*), 149
setEpsilon() (*pyAgrum.CNMonteCarloSampling method*), 147
setEpsilon() (*pyAgrum.GibbsSampling method*), 84
setEpsilon() (*pyAgrum.ImportanceSampling method*), 103
setEpsilon() (*pyAgrum.LoopyBeliefPropagation method*), 78
setEpsilon() (*pyAgrum.LoopyGibbsSampling method*), 109
setEpsilon() (*pyAgrum.LoopyImportanceSampling method*), 128
setEpsilon() (*pyAgrum.LoopyMonteCarloSampling method*), 115
setEpsilon() (*pyAgrum.LoopyWeightedSampling method*), 121
setEpsilon() (*pyAgrum.MonteCarloSampling method*), 90

```

setEpsilon()           (pyAgrum.WeightedSampling
                     method), 96
setEvidence()          (pyAgrum.GibbsSampling
                     method), 84
setEvidence()          (pyAgrum.ImportanceSampling
                     method), 103
setEvidence()          (pyAgrum.InfluenceDiagramInference
                     method), 157
setEvidence()          (pyAgrum.LazyPropagation
                     method), 60
setEvidence()          (pyAgrum.LoopyBeliefPropagation
                     method), 78
setEvidence()          (pyAgrum.LoopyGibbsSampling
                     method), 109
setEvidence()          (pyAgrum.LoopyImportanceSampling
                     method), 128
setEvidence()          (pyAgrum.LoopyMonteCarloSampling
                     method), 115
setEvidence()          (pyAgrum.LoopyWeightedSampling
                     method), 122
setEvidence()          (pyAgrum.MonteCarloSampling
                     method), 90
setEvidence()          (pyAgrum.ShaferShenoyInference
                     method), 66
setEvidence()          (pyAgrum.VariableElimination
                     method), 72
setEvidence()          (pyAgrum.WeightedSampling
                     method), 97
setFirst()             (pyAgrum.Instantiation
                     method), 35
setFirstIn()            (pyAgrum.Instantiation
                     method), 35
setFirstNotVar()        (pyAgrum.Instantiation
                     method), 35
setFirstOut()            (pyAgrum.Instantiation
                     method), 35
setFirstVar()            (pyAgrum.Instantiation
                     method), 35
setInitialDAG()         (pyAgrum.BN Learner
                     method), 134
setLast()               (pyAgrum.Instantiation
                     method), 35
setLastIn()              (pyAgrum.Instantiation
                     method), 35
setLastNotVar()          (pyAgrum.Instantiation
                     method), 35
setLastOut()              (pyAgrum.Instantiation
                     method), 36
setLastVar()              (pyAgrum.Instantiation
                     method), 36
setMaxIndegree()         (pyAgrum.BN Learner
                     method), 134
setMaxIter()             (pyAgrum.BN Learner
                     method), 134
setMaxIter()             (pyAgrum.CNLoopyPropagation
                     method), 149
setMaxIter()             (pyAgrum.CNMonteCarloSampling
                     method), 147
setMaxIter()             (pyAgrum.GibbsSampling
                     method), 84
setMaxIter()             (pyAgrum.ImportanceSampling
                     method), 103
setMaxIter()             (pyAgrum.LoopyBeliefPropagation
                     method), 78
setMaxIter()             (pyAgrum.LoopyGibbsSampling
                     method), 109
setMaxIter()             (pyAgrum.LoopyImportanceSampling
                     method), 128
setMaxIter()             (pyAgrum.LoopyMonteCarloSampling
                     method), 116
setMaxIter()             (pyAgrum.LoopyWeightedSampling
                     method), 122
setMaxIter()             (pyAgrum.MonteCarloSampling
                     method), 91
setMaxIter()             (pyAgrum.WeightedSampling
                     method), 97
setMaxTime()             (pyAgrum.BN Learner
                     method), 134
setMaxTime()             (pyAgrum.CNLoopyPropagation
                     method), 149
setMaxTime()             (pyAgrum.CNMonteCarloSampling
                     method), 147
setMaxTime()             (pyAgrum.GibbsSampling
                     method), 84
setMaxTime()             (pyAgrum.ImportanceSampling
                     method), 103
setMaxTime()             (pyAgrum.LoopyBeliefPropagation
                     method), 78
setMaxTime()             (pyAgrum.LoopyGibbsSampling
                     method), 109
setMaxTime()             (pyAgrum.LoopyImportanceSampling
                     method), 128
setMaxTime()             (pyAgrum.LoopyMonteCarloSampling
                     method), 116
setMaxTime()             (pyAgrum.LoopyWeightedSampling
                     method), 122
setMaxTime()             (pyAgrum.MonteCarloSampling
                     method), 91
setMaxTime()             (pyAgrum.WeightedSampling
                     method), 97
setMaxVal()              (pyAgrum.RangeVariable
                     method), 30
setMinEpsilonRate()       (pyAgrum.BN Learner
                     method), 134
setMinEpsilonRate()       (pyAgrum.CNLoopyPropagation
                     method), 149
setMinEpsilonRate()       (pyAgrum.CNMonteCarloSampling
                     method), 147
setMinEpsilonRate()       (pyAgrum.GibbsSampling
                     method), 85
setMinEpsilonRate()       (pyAgrum.ImportanceSampling
                     method), 103
setMinEpsilonRate()       (pyAgrum.LoopyBeliefPropagation
                     method), 78

```

setMinEpsilonRate()	(<i>pyAgrum.LoopyGibbsSampling method</i>), 110	<i>method</i>), 134
setMinEpsilonRate()	(<i>pyAgrum.LoopyImportanceSampling method</i>), 128	<i>setRecordWeight ()</i> (<i>pyAgrum.BNLearn</i>
setMinEpsilonRate()	(<i>pyAgrum.LoopyMonteCarloSampling method</i>), 116	<i>method</i>), 134
setMinEpsilonRate()	(<i>pyAgrum.LoopyWeightedSampling method</i>), 122	<i>setRepetitiveInd ()</i> (<i>pyAgrum.CNLoopyPropagation method</i>),
setMinEpsilonRate()	(<i>pyAgrum.MonteCarloSampling method</i>), 91	150
setMinEpsilonRate()	(<i>pyAgrum.WeightedSampling method</i>), 97	<i>setRepetitiveInd ()</i> (<i>pyAgrum.CNMonteCarloSampling method</i>),
setMinVal()	(<i>pyAgrum.RangeVariable method</i>), 30	147
setName()	(<i>pyAgrum.DiscreteVariable method</i>), 22	<i>setSliceOrder ()</i> (<i>pyAgrum.BNLearn</i>
setName()	(<i>pyAgrum.DiscretizedVariable method</i>), 27	<i>method</i>), 134
setName()	(<i>pyAgrum.LabelizedVariable method</i>), 25	<i>setTargets ()</i> (<i>pyAgrum.GibbsSampling method</i>),
setName()	(<i>pyAgrum.RangeVariable method</i>), 30	85
setNbrDrawnVar()	(<i>pyAgrum.GibbsSampling method</i>), 85	<i>setTargets ()</i> (<i>pyAgrum.ImportanceSampling method</i>), 103
setNbrDrawnVar()	(<i>pyAgrum.LoopyGibbsSampling method</i>), 110	<i>setTargets ()</i> (<i>pyAgrum.LazyPropagation method</i>), 60
setNumberOfThreads()	(in module <i>pyAgrum</i>), 159	<i>setTargets ()</i> (<i>pyAgrum.LoopyBeliefPropagation method</i>), 78
setPeriodSize()	(<i>pyAgrum.BNLearn</i> method), 134	<i>setTargets ()</i> (<i>pyAgrum.LoopyGibbsSampling method</i>), 110
setPeriodSize()	(<i>pyAgrum.CNLoopyPropagation method</i>), 149	<i>setTargets ()</i> (<i>pyAgrum.LoopyImportanceSampling method</i>),
setPeriodSize()	(<i>pyAgrum.CNMonteCarloSampling method</i>), 147	128
setPeriodSize()	(<i>pyAgrum.GibbsSampling method</i>), 85	<i>setTargets ()</i> (<i>pyAgrum.LoopyMonteCarloSampling method</i>), 116
setPeriodSize()	(<i>pyAgrum.ImportanceSampling method</i>), 103	<i>setTargets ()</i> (<i>pyAgrum.LoopyWeightedSampling method</i>), 122
setPeriodSize()	(<i>pyAgrum.LoopyBeliefPropagation method</i>), 78	<i>setTargets ()</i> (<i>pyAgrum.MonteCarloSampling method</i>), 91
setPeriodSize()	(<i>pyAgrum.LoopyGibbsSampling method</i>), 110	<i>setTargets ()</i> (<i>pyAgrum.ShaferShenoyInference method</i>), 67
setPeriodSize()	(<i>pyAgrum.LoopyImportanceSampling method</i>), 128	<i>setTargets ()</i> (<i>pyAgrum.VariableElimination method</i>), 72
setPeriodSize()	(<i>pyAgrum.LoopyMonteCarloSampling method</i>), 116	<i>setTargets ()</i> (<i>pyAgrum.WeightedSampling method</i>), 97
setPeriodSize()	(<i>pyAgrum.LoopyWeightedSampling method</i>), 122	<i>setVals ()</i> (<i>pyAgrum.Instantiation method</i>), 36
setPeriodSize()	(<i>pyAgrum.MonteCarloSampling method</i>), 91	<i>setVerbosity ()</i> (<i>pyAgrum.BNLearn</i> method),
setPeriodSize()	(<i>pyAgrum.WeightedSampling method</i>), 97	134
setPossibleSkeleton()	(<i>pyAgrum.BNLearn</i>	<i>setVerbosity ()</i> (<i>pyAgrum.CNLoopyPropagation method</i>), 150
		<i>method</i>), 147
		<i>setVerbosity ()</i> (<i>pyAgrum.GibbsSampling method</i>), 85
		<i>setVerbosity ()</i> (<i>pyAgrum.ImportanceSampling method</i>), 103
		<i>setVerbosity ()</i> (<i>pyAgrum.LoopyBeliefPropagation method</i>), 78
		<i>setVerbosity ()</i> (<i>pyAgrum.LoopyGibbsSampling method</i>), 110
		<i>setVerbosity ()</i> (<i>pyAgrum.LoopyImportanceSampling method</i>), 128
		<i>setVerbosity ()</i> (<i>pyAgrum.BNLearn</i>

grum.LoopyMonteCarloSampling method), 116
setVerbosity() grum.LoopyWeightedSampling method), 122
setVerbosity() (pyAgrum.MonteCarloSampling method), 91
setVerbosity() (pyAgrum.WeightedSampling method), 97
setVirtualLBPSize() grum.LoopyGibbsSampling method), 110
setVirtualLBPSize() grum.LoopyImportanceSampling method), 128
setVirtualLBPSize() grum.LoopyMonteCarloSampling method), 116
setVirtualLBPSize() grum.LoopyWeightedSampling method), 122
ShaferShenoyInference (class in pyAgrum), 61
size() (pyAgrum.BayesNet method), 54
size() (pyAgrum.CliqueGraph method), 16
size() (pyAgrum.DAG method), 10
size() (pyAgrum.DiGraph method), 8
size() (pyAgrum.InfluenceDiagram method), 155
size() (pyAgrum.MixedGraph method), 20
size() (pyAgrum.UndiGraph method), 13
sizeArcs() (pyAgrum.BayesNet method), 54
sizeArcs() (pyAgrum.DAG method), 10
sizeArcs() (pyAgrum.DiGraph method), 8
sizeArcs() (pyAgrum.InfluenceDiagram method), 155
sizeArcs() (pyAgrum.MixedGraph method), 20
sizeEdges() (pyAgrum.CliqueGraph method), 16
sizeEdges() (pyAgrum.MixedGraph method), 20
sizeEdges() (pyAgrum.UndiGraph method), 13
SizeError, 162
softEvidenceNodes() (pyAgrum.GibbsSampling method), 85
softEvidenceNodes() (pyAgrum.ImportanceSampling method), 103
softEvidenceNodes() (pyAgrum.LazyPropagation method), 60
softEvidenceNodes() (pyAgrum.LoopyBeliefPropagation method), 78
softEvidenceNodes() (pyAgrum.LoopyGibbsSampling method), 110
softEvidenceNodes() (pyAgrum.LoopyImportanceSampling method), 128
softEvidenceNodes() (pyAgrum.LoopyMonteCarloSampling method), 116
softEvidenceNodes() (pyAgrum.LoopyWeightedSampling method), 122
softEvidenceNodes() (pyAgrum.MonteCarloSampling method), 91
softEvidenceNodes() (pyAgrum.ShafersShenoyInference method), 67
softEvidenceNodes() (pyAgrum.VariableElimination method), 72
softEvidenceNodes() (pyAgrum.WeightedSampling method), 97
sq() (pyAgrum.Potential method), 41
src_bn() (pyAgrum.CredalNet method), 145
sum() (pyAgrum.Potential method), 41
SyntaxError, 162

T

tail() (pyAgrum.Arc method), 5
targets() (pyAgrum.GibbsSampling method), 85
targets() (pyAgrum.ImportanceSampling method), 103
targets() (pyAgrum.LazyPropagation method), 60
targets() (pyAgrum.LoopyBeliefPropagation method), 78
targets() (pyAgrum.LoopyGibbsSampling method), 110
targets() (pyAgrum.LoopyImportanceSampling method), 128
targets() (pyAgrum.LoopyMonteCarloSampling method), 116
targets() (pyAgrum.LoopyWeightedSampling method), 122
targets() (pyAgrum.MonteCarloSampling method), 91
targets() (pyAgrum.ShafersShenoyInference method), 67
targets() (pyAgrum.VariableElimination method), 73
targets() (pyAgrum.WeightedSampling method), 97
thisown (pyAgrum.Arc attribute), 5
thisown (pyAgrum.BayesNet attribute), 54
thisown (pyAgrum.BNLearner attribute), 134
thisown (pyAgrum.CliqueGraph attribute), 16
thisown (pyAgrum.CNLoopyPropagation attribute), 150
thisown (pyAgrum.CNMonteCarloSampling attribute), 147
thisown (pyAgrum.CredalNet attribute), 145
thisown (pyAgrum.DAG attribute), 11
thisown (pyAgrum.DefaultInLabel attribute), 159
thisown (pyAgrum.DiGraph attribute), 8
thisown (pyAgrum.DiscreteVariable attribute), 22
thisown (pyAgrum.DiscretizedVariable attribute), 27
thisown (pyAgrum.DuplicateElement attribute), 159
thisown (pyAgrum.DuplicateLabel attribute), 159
thisown (pyAgrum.Edge attribute), 6
thisown (pyAgrum.EmptyBSTree attribute), 159
thisown (pyAgrum.EmptySet attribute), 160
thisown (pyAgrum.FatalError attribute), 160

thisown (`pyAgrum.FormatNotFound` attribute), 160
 thisown (`pyAgrum.GibbsSampling` attribute), 85
 thisown (`pyAgrum.GraphError` attribute), 160
 thisown (`pyAgrum.GumException` attribute), 160
 thisown (`pyAgrum.IdError` attribute), 160
 thisown (`pyAgrum.ImportanceSampling` attribute), 104
 thisown (`pyAgrum.InfluenceDiagram` attribute), 155
 thisown (`pyAgrum.InfluenceDiagramInference` attribute), 157
 thisown (`pyAgrum.Instantiation` attribute), 36
 thisown (`pyAgrum.InvalidArc` attribute), 161
 thisown (`pyAgrum.InvalidArgument` attribute), 161
 thisown (`pyAgrum.InvalidArgumentsNumber` attribute), 161
 thisown (`pyAgrum.InvalidDirectedCycle` attribute), 161
 thisown (`pyAgrum.InvalidEdge` attribute), 161
 thisown (`pyAgrum.InvalidNode` attribute), 161
 thisown (`pyAgrum.IOError` attribute), 160
 thisown (`pyAgrum.LabelizedVariable` attribute), 25
 thisown (`pyAgrum.LazyPropagation` attribute), 60
 thisown (`pyAgrum.LoopyBeliefPropagation` attribute), 79
 thisown (`pyAgrum.LoopyGibbsSampling` attribute), 110
 thisown (`pyAgrum.LoopyImportanceSampling` attribute), 129
 thisown (`pyAgrum.LoopyMonteCarloSampling` attribute), 116
 thisown (`pyAgrum.LoopyWeightedSampling` attribute), 122
 thisown (`pyAgrum.MixedGraph` attribute), 20
 thisown (`pyAgrum.MonteCarloSampling` attribute), 91
 thisown (`pyAgrum.NoChild` attribute), 161
 thisown (`pyAgrum.NoNeighbour` attribute), 161
 thisown (`pyAgrum.NoParent` attribute), 161
 thisown (`pyAgrum.NotFound` attribute), 162
 thisown (`pyAgrum.NullElement` attribute), 162
 thisown (`pyAgrum.OperationNotAllowed` attribute), 162
 thisown (`pyAgrum.OutOfBounds` attribute), 162
 thisown (`pyAgrum.OutOfLowerBound` attribute), 162
 thisown (`pyAgrum.OutOfUpperBound` attribute), 162
 thisown (`pyAgrum.Potential` attribute), 41
 thisown (`pyAgrum.PRMexplorer` attribute), 139
 thisown (`pyAgrum.RangeVariable` attribute), 30
 thisown (`pyAgrum.ReferenceError` attribute), 162
 thisown (`pyAgrum.ShaferShenoyInference` attribute), 67
 thisown (`pyAgrum.SizeError` attribute), 162
 thisown (`pyAgrum.SyntaxError` attribute), 163
 thisown (`pyAgrum.UndefinedElement` attribute), 163
 thisown (`pyAgrum.UndefinedIteratorKey` attribute), 163
 thisown (`pyAgrum.UndefinedIteratorValue` attribute), 163
 thisown (`pyAgrum.UndiGraph` attribute), 13
 thisown (`pyAgrum.UnknownLabelInDatabase` attribute), 163
 thisown (`pyAgrum.VariableElimination` attribute), 73
 thisown (`pyAgrum.WeightedSampling` attribute), 97
 tick () (`pyAgrum.DiscretizedVariable` method), 27
 ticks () (`pyAgrum.DiscretizedVariable` method), 28
 toArray () (`pyAgrum.Potential` method), 42
 todict () (`pyAgrum.Instantiation` method), 36
 toDiscretizedVar () (`pyAgrum.DiscreteVariable` method), 22
 toDiscretizedVar () (`pyAgrum.DiscretizedVariable` method), 28
 toDiscretizedVar () (`pyAgrum.LabelizedVariable` method), 25
 toDiscretizedVar () (`pyAgrum.RangeVariable` method), 30
 toDot () (`pyAgrum.BayesNet` method), 54
 toDot () (`pyAgrum.CliqueGraph` method), 16
 toDot () (`pyAgrum.DAG` method), 11
 toDot () (`pyAgrum.DiGraph` method), 8
 toDot () (`pyAgrum.InfluenceDiagram` method), 155
 toDot () (`pyAgrum.MixedGraph` method), 20
 toDot () (`pyAgrum.UndiGraph` method), 13
 toDotWithNames () (`pyAgrum.CliqueGraph` method), 16
 toLabelizedVar () (`pyAgrum.DiscreteVariable` method), 22
 toLabelizedVar () (`pyAgrum.DiscretizedVariable` method), 28
 toLabelizedVar () (`pyAgrum.LabelizedVariable` method), 25
 toLabelizedVar () (`pyAgrum.RangeVariable` method), 31
 tolist () (`pyAgrum.Potential` method), 42
 topologicalOrder () (`pyAgrum.BayesNet` method), 54
 topologicalOrder () (`pyAgrum.DAG` method), 11
 topologicalOrder () (`pyAgrum.DiGraph` method), 8
 topologicalOrder () (`pyAgrum.InfluenceDiagram` method), 155
 topologicalOrder () (`pyAgrum.MixedGraph` method), 20
 toRangeVar () (`pyAgrum.DiscreteVariable` method), 22
 toRangeVar () (`pyAgrum.DiscretizedVariable` method), 28
 toRangeVar () (`pyAgrum.LabelizedVariable` method), 25
 toRangeVar () (`pyAgrum.RangeVariable` method), 31
 toStringWithDescription () (`pyAgrum.DiscreteVariable` method), 22

```

toStringWithDescription()           (pyA-
    grum.DiscretizedVariable method), 28
toStringWithDescription()           (pyA-
    grum.LabelizedVariable method), 25
toStringWithDescription()           (pyA-
    grum.RangeVariable method), 31
translate() (pyAgrum.Potential method), 42
types() (pyAgrum.PRMexplorer method), 139

U
UndefinedElement, 163
UndefinedIteratorKey, 163
UndefinedIteratorValue, 163
UndiGraph (class in pyAgrum), 11
UnknownLabelInDatabase, 163
unsetEnd() (pyAgrum.Instantiation method), 36
unsetOverflow() (pyAgrum.Instantiation
    method), 36
updateEvidence() (pyAgrum.GibbsSampling
    method), 85
updateEvidence() (pyA-
    grum.ImportanceSampling method), 104
updateEvidence() (pyAgrum.LazyPropagation
    method), 60
updateEvidence() (pyA-
    grum.LoopyBeliefPropagation
    method), 79
updateEvidence() (pyA-
    grum.LoopyGibbsSampling method), 110
updateEvidence() (pyA-
    grum.LoopyImportanceSampling
    method), 129
updateEvidence() (pyA-
    grum.LoopyMonteCarloSampling
    method), 116
updateEvidence() (pyA-
    grum.LoopyWeightedSampling
    method), 122
updateEvidence() (pyA-
    grum.MonteCarloSampling method), 91
updateEvidence() (pyA-
    grum.ShaferShenoyInference
    method), 67
updateEvidence() (pyA-
    grum.VariableElimination method), 73
updateEvidence() (pyAgrum.WeightedSampling
    method), 97
use3off2() (pyAgrum.BNLearnert method), 134
useAprioriBDeu() (pyAgrum.BNLearnert
    method), 134
useAprioriDirichlet() (pyAgrum.BNLearnert
    method), 135
useAprioriSmoothing() (pyAgrum.BNLearnert
    method), 135
useEM() (pyAgrum.BNLearnert method), 135
useGreedyHillClimbing() (pyA-
    grum.BNLearnert method), 135
useK2() (pyAgrum.BNLearnert method), 135

U
useLocalSearchWithTabuList() (pyA-
    grum.BNLearnert method), 135
useMDL() (pyAgrum.BNLearnert method), 135
useMIC() (pyAgrum.BNLearnert method), 135
useNML() (pyAgrum.BNLearnert method), 135
useNoApriori() (pyAgrum.BNLearnert method),
    135
useNoCorr() (pyAgrum.BNLearnert method), 135
useScoreAIC() (pyAgrum.BNLearnert method),
    135
useScoreBD() (pyAgrum.BNLearnert method), 135
useScoreBDeu() (pyAgrum.BNLearnert method),
    135
useScoreBIC() (pyAgrum.BNLearnert method),
    135
useScoreK2() (pyAgrum.BNLearnert method), 135
useScoreLog2Likelihood() (pyA-
    grum.BNLearnert method), 135
utility() (pyAgrum.InfluenceDiagram
    method), 155
utilityNodeSize() (pyAgrum.InfluenceDiagram
    method), 155

V
val() (pyAgrum.Instantiation method), 36
var_dims (pyAgrum.Potential attribute), 42
var_names (pyAgrum.Potential attribute), 42
variable() (pyAgrum.BayesNet method), 54
variable() (pyAgrum.InfluenceDiagram method),
    155
variable() (pyAgrum.Instantiation method), 36
variable() (pyAgrum.Potential method), 42
VariableElimination (class in pyAgrum), 67
variableFromName() (pyAgrum.BayesNet
    method), 54
variableFromName() (pyA-
    grum.InfluenceDiagram method), 155
variableNodeMap() (pyAgrum.BayesNet
    method), 54
variableNodeMap() (pyAgrum.InfluenceDiagram
    method), 156
variablesSequence() (pyAgrum.Instantiation
    method), 37
variablesSequence() (pyAgrum.Potential
    method), 42
varType() (pyAgrum.DiscreteVariable method), 22
varType() (pyAgrum.DiscretizedVariable method),
    28
varType() (pyAgrum.LabelizedVariable method), 25
varType() (pyAgrum.RangeVariable method), 31
verbosity() (pyAgrum.BNLearnert method), 135
verbosity() (pyAgrum.CNLoopyPropagation
    method), 150
verbosity() (pyAgrum.CNMonteCarloSampling
    method), 147
verbosity() (pyAgrum.GibbsSampling method),
    85

```

```

verbosity()      (pyAgrum.ImportanceSampling method), 104
verbosity()      (pyAgrum.LoopyBeliefPropagation method), 79
verbosity()      (pyAgrum.LoopyGibbsSampling method), 110
verbosity()      (pyAgrum.LoopyImportanceSampling method), 129
verbosity()          (pyAgrum.LoopyMonteCarloSampling method),
verbosity()      (pyAgrum.LoopyWeightedSampling method), 123
verbosity()      (pyAgrum.MonteCarloSampling method), 91
verbosity()      (pyAgrum.WeightedSampling method), 98
VI()      (pyAgrum.LazyPropagation method), 55
VI()      (pyAgrum.ShaferShenoyInference method), 61

```

W

```

WeightedSampling (class in pyAgrum), 92
what()      (pyAgrum.DefaultInLabel method), 159
what()      (pyAgrum.DuplicateElement method), 159
what()      (pyAgrum.DuplicateLabel method), 159
what()      (pyAgrum.EmptyBSTree method), 160
what()      (pyAgrum.EmptySet method), 160
what()      (pyAgrum.FatalError method), 160
what()      (pyAgrum.FormatNotFound method), 160
what()      (pyAgrum.GraphError method), 160
what()      (pyAgrum.GumException method), 160
what()      (pyAgrum.IdError method), 161
what()      (pyAgrum.InvalidArc method), 161
what()      (pyAgrum.InvalidArgument method), 161
what()      (pyAgrum.InvalidArgumentsNumber method),
what()      (pyAgrum.InvalidDirectedCycle method), 161
what()      (pyAgrum.InvalidEdge method), 161
what()      (pyAgrum.InvalidNode method), 161
what()      (pyAgrum.IOError method), 160
what()      (pyAgrum.NoChild method), 161
what()      (pyAgrum.NoNeighbour method), 161
what()      (pyAgrum.NoParent method), 162
what()      (pyAgrum.NotFound method), 162
what()      (pyAgrum.NullElement method), 162
what()      (pyAgrum.OperationNotAllowed method),
what()      (pyAgrum.OutOfBounds method), 162
what()      (pyAgrum.OutOfLowerBound method), 162
what()      (pyAgrum.OutOfUpperBound method), 162
what()      (pyAgrum.ReferenceError method), 162
what()      (pyAgrum.SizeType method), 162
what()      (pyAgrum.SyntaxError method), 163
what()      (pyAgrum.UndefinedElement method), 163
what()      (pyAgrum.UndefinedIteratorKey method),
what()      (pyAgrum.UndefinedIteratorValue method),
what()      (pyAgrum.UndefinedJsonValue method), 163

```